BMW Media Information

5/2012

Valid from 7/2012

Specifications. The new BMW 1 Series 5 Door Hatch. M135i



Body No. of doors/seats LW/H ¹⁾ (unladen)		
No. of doors/seats		
		5/5
L/VV/H : (unladen)	mm	4340 / 1765 / 1411
Wheelbase	mm	2690
Front/rear track	mm	1512 / 1532
Ground clearance	mm	130
Turning circle	m	10.9
Fuel capacity	approx. I	52
Cooling and heating system	арргол. Г	6.7 (7.2)
reservoir capacity		· ·
Engine oil capacity ²⁾		6.5
Weight, unladen (DIN/EU)	kg	1430 / 1505 (1445 / 1520)
Payload (DIN)	kg	530
Permitted total weight	kg	1960 (1975)
Permitted axle load, front/rear	kg	950 (960) / 1110
Permitted trailer load (12%) braked/unbraked	kg	-1-
	and lea	75.1
Permitted roof load/trailer download		75 / - 360 - 1200
Luggage compartment capacity		
Aerodynamic drag	c _c x A	0.33 x 2.14
Engine		
Type/no. of cylinders/valves		in-line / 6 / 4
Engine technology		M TwinPower Turbo technology with twin-scroll turbocharger, High Precision Injection, VALVETRONIC fully variable valve control and Double-VANOS variable camshaft control
Effective capacity	CC	2979
Stroke/bore	mm	89.6 / 84.0
Compression ratio	:1	10.2
Fuel type		min. RON 91
Output	kW/hp	235 / 320
at rpm	min ⁻¹	5800
Torque (with overboost)	Nm	450
at rpm	min ⁻¹	1250–5000
Electrical		
	A.L. /	20.11
Battery charge/location	Ah/–	80 / luggage compartment
Alternator current/output	A/W	210/2940
Driving Dynamics and Safety	у	
Front suspension		Aluminium double-joint cross-strut axle with M-specific elastokinematics
Rear suspension		Lightweight steel five-link with double elastic bearing
Front brakes		Four-piston floating-calliper disc brakes
Diameter	mm	³⁾ /air-cooled
Rear brakes		Two-piston floating-calliper disc brakes
Diameter	mm	3)/air-cooled
Driving stability systems		As standard: DSC inc. ABS, ASC and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, hill assist
Safety equipment		As standard: driver and front-seat passenger airbags, driver and front-seat passenger side airbags, front and rear head airbags, three-point automatic seatbelts for all seats, seatbelt tensioners and seatbelt force limiters in front seats, crash sensors, tyre pressure warning
Steering		Electromechanical power steering (EPS), Variable Sport Steering
Overall steering ratio	:1	15.0
Front/rear tyres	.1	225/40 R18 88Y/ 245/35 R18 88Y
Front/rear wheels		7.5J x 18 light-alloy/ 8J x 18 light-alloy

BMW

Media Information

5/2012

Valid from 7/2012

Specifications. The new BMW 1 Series 5 Door Hatch.

		BMW M135
BMW ConnectedDrive		
Comfort		Optional: BMW Assist including information service,
Connect		remote functions, Real Time Traffic Information,
		BMW TeleServices, mobile device integration
Information and entertainment		Optional: Internet connectivity, BMW Online including parking
		information, country information, Google business search,
		news, real-time weather, BMW Routes, office functions,
		Bluetooth audio streaming, online music title update, apps
Safety		Optional: Adaptive Headlights with turning lights, variable light distribution,
		Adaptive Headlight range adjustment, high beam assistance,
		park distance control, reversing camera, cruise control with brake function,
		parking assistant, Lane Departure Warning with Collision Warning,
		speed limit and no passing information, extended emergency call
Transmission		
Type of gearbox		6-speed manual (optional: 8-speed automatic with Steptronic)
Gear ratios I	:1	4.110 (4.714
	:1	2.315 (3.143
III	:1	1.542 (2.106
IV	:1	1.179 (1.667
V	:1	1.000 (1.285
VI	:1	0.846 (1.000
VII	:1	- (0.839
VIII	:1	- (0.667
R	:1	3.727 (3.295
Differential ratio	:1	3.077 (3.077
Performance		
Weight-to-power ratio (DIN)	kg/kW	6.1 (6.1
Specific power output	kW/l	78.5
Acceleration 0–100 km/h	sec.	5.1 (4.9
0–1,000 m	sec.	23.9 (23.8
in 4th/5th gear 80–120 km/h	sec.	4.3 / 5.0
Max. speed	km/h	250 (250
BMW EfficientDynamics		
BMW EfficientDynamics Featu	ires	Brake Energy Regeneration, electromechanical power steering,
included as standard	1100	Automatic Start/Stop function, gear shift indicator (manual), ECO PRO mode,
		intelligent lightweight construction, automatically disconnecting ancillary
		components, map-regulated oil pump, differential with optimized-warm-up
		behaviour, tyres with reduced rolling resistance
Fuel consumption (EU)		
Urban	I/100 km	11.2 (10.3
Extra-urban	1/100 km	6.2 (5.8
Total	I/100 km	8.0 (7.5
CO ₂ emissions	g/km	188 (175
Emissions standard	y/KIII	100 (1/3 EU5
LITHSSIUIS STALINGIA		EUG

Technical data valid for ACEA countries/Some permitted weights valid only for Germany Figures in brackets are for vehicles with automatic transmission

Height with roof aerial: 1430 mm
 Oil change volume
 Not yet available