

# TECHNICAL SPECIFICATIONS.

## MINI COOPER S COUNTRYMAN ALL4.

## MINI COOPER S COUNTRYMAN ALL4 AUTOMATIC.



Body	MINI Cooper S Countryman ALL4	MINI Cooper S Countryman ALL4 Automatic
Number of doors/seats	5 / 5	5 / 5
Length/width/height (empty)	mm 4299 / 1822 / 1557	4299 / 1822 / 1557
Wheelbase	mm 2670	2670
Track width, front/rear	mm 1563 / 1565	1563 / 1565
Turning circle	m 11.4	11.4
Ground clearance (empty)	mm 165	165
Fuel tank capacity	approx. l 51	51
Engine oil	l 5.25	5.25
Transmission oil incl. drivetrain	l lifetime filling	lifetime filling
Unladen weight according to DIN/EU <sup>1)</sup>	kg 1510 / 1585	1530 / 1605
Payload according to DIN	kg 600	590
Permitted gross vehicle weight	kg 2110	2120
Permitted axle loads, front/rear	kg 1100 / 1050	1120 / 1050
Permitted trailer load		
braked (12 %) / unbraked	kg 1800 / 750	1800 / 750
Permitted roof load/permited download	kg 75 / 75	75 / 75
Luggage compartment volume	l 450 - 1390	450 - 1390
Aerodynamic drag $c_x / A / c_x \times A$	- / m <sup>2</sup> / m <sup>2</sup> 0.33 / 2.40 / 0.79	0.33 / 2.40 / 0.79
<b>Engine</b>		
Type/no. of cylinders/valves	in-line / 4 / 4	in-line / 4 / 4
Engine control	MEVD 17.2.3	MEVD 17.2.3
Capacity	cc 1998	1998
Bore/stroke	mm 82.0 / 94.6	82.0 / 94.6
Compression	:1 11.0	11.0
Fuel	RON 91 - 98	91 - 98
Output	kW/hp 141 / 192	141 / 192
at engine speed	rpm 5000 - 6000	5000 - 6000
Torque	Nm 280	280
at engine speed	rpm 1350 - 4600	1350 - 4600
<b>Electrical system</b>		
Battery/installation	Ah / - 70 / engine compartment	70 / engine compartment
Alternator	A 150	150
<b>Suspension</b>		
Front wheel suspension	Single-joint McPherson spring strut axle with aluminium swivel bearing and anti-dive control	
Rear wheel suspension	Multilink axle with weight-optimised trailing arms	
Brakes, front	disc, vented	disc, vented
Rear brakes	disc	disc
Driving stability systems	Hydraulic 2-circuit brake system with anti-lock brakes (ABS), electronic brake force distribution (EBD) and Cornering Brake Control (CBC), Dynamic Stability Control (DSC) with brake assistant, hill start assistant, brake dry function, Fading Brake Support, Dynamic Traction Control (DTC), Electronic Differential Lock Control (EDLC) and Performance Control; DSC control unit interconnected with all-wheel drive system MINI ALL4. Handbrake impacts electrically on rear wheels	
Steering	Electrically assisted EPS unit with Servotronic function	
Overall steering ratio	:1 14.0	14.0
Tyres	225/55 R17 97W	225/55 R17 97W
Rims	7,5J × 17 light alloy	7,5J × 17 light alloy
<b>Transmission</b>		
Transmission type	6-speed manual transmission	8-speed Steptronic transmission
Gear ratio	I :1 3.818	5.250
	II :1 2.040	3.029
	III :1 1.367	1.950
	IV :1 1.026	1.457
	V :1 0.949	1.221
	VI :1 0.791	1.000
	VIII :1 -	0.809
	VIII :1 -	0.673
Reverse gear	:1 4.140	4.015
Final drive ratio	:1 4.059	3.200
<b>Driving performance figures</b>		
Power-to-weight ratio according to DIN	kg/kW 10.7	10.9
Power output per litre	kW/l 70.6	70.6
Acceleration 0-100 km/h	s 7.3	7.2
in 5th gear 80-120 km/h	s 9.2	-
Top speed	km/h 222	222
<b>Fuel consumption in EU cycle<sup>2)</sup></b>		
Urban	l/100 km 9.0 - 8.8	7.9 - 7.8
Extra-urban	l/100 km 6.0 - 5.9	5.8 - 5.6
Total	l/100 km 7.1 - 7.0	6.6 - 6.4
CO <sub>2</sub>	g/km 162 - 159	150 - 146
<b>Other</b>		
Emission rating	EU6	EU6

Specifications apply to ACEA markets / data relevant to homologation applicable in part only to Germany (weight)

<sup>1)</sup> Weight of road-ready automobile (DIN) plus 75 kg for driver and luggage

<sup>2)</sup> Dependent on tyre format selected