



Media Information

BMW 530e iPerformance.

		BMW 530e iPerformance
Body		
No of doors/seats		4/5
Length/width/height 1) (unladen)	mm	4936 / 1868 / 1483
Wheelbase	mm	2975
Frack, front/rear	mm	1604 / 1631
Ground clearance	mm	150
Turning circle	m	12.05
Fuel tank capacity	approx ltr	46
Engine oil 2)	ltr	5.25
Weight, unladen, to DIN/EU		1770 / 1845
Max load to DIN	kg	650
	kg	
Max permissible weight	kg	2420
Max axle load, front/rear	kg	1120 / 1405
Max roofload/towbar download	kg	100 / –
Luggage comp capacity	ltr	410
Air resistance	c _d x A	0.26 x 2.35
Orive system Orive concept		Full hybrid drive, torque vectoring to rear wheels
nive concept		from one or both units
Sustain autout	LAA76-	185 / 252
System output	kW/hp	
System torque	Nm	420
Weight-to-power ratio (DIN)	kg/kW	9.6
Combustion engine		
Config/No of cyls/valves		in-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology: TwinScroll turbocharger,
angine teermology		High Precision Injection, VALVETRONIC fully variable valve control
		Double VANOS variable camshaft control
Effective capacity	cm ³	1998
Stroke/bore	mm	94.6 / 82.0
Compression ratio	:1	11.0
Fuel grade		min RON 91
	kW/hp	135 / 184
Output		
at	rpm	5000 - 6500
Torque	Nm	290
ət	rpm	1350 – 4250
Output per litre	kW/ltr	67.6
Electric motor		
		PMW-Dd - to-basic - a subseque a lastic materials of a con-
Motor technology		BMW eDrive technology: synchronous electric motor integrated in 8-spe Steptronic transmission, generator function for energy recuperation for the
		high-voltage battery
Max output	kW/hp	83 / 113
et		3170
Torque	rpm Nm	250
at Danisantina asitas t	rpm	0-3170
Recuperation output	kW	20
High-voltage battery		
Storage technology / installation		lithium-ion / underneath rear seat
Voltage	V	351
Capacity (gross)	kWh	9.2
	KVVn	
Charging time for 100% charge		2.9 h at 3.7 kW (16 A / 230 V)
Transmission		
Type of transmission		8-speed Steptronic
Gear ratios I	:1	4.714
Jean ratios	:1	3.143
III.	:1	2.106
IV	:1	1.667
V	:1	1.285
3.71	:1	1.000
VI		
VII	:1	0.839
	:1 :1	0.839 0.667
VII		

		BMW 530e iPerformance
Driving dynamics and safety		
Suspension, front		Double track control arm axle with separate lower track arm level in
		aluminium lightweight construction, small steering roll radius, traverse
		force compensation, anti-dive
Suspension, rear		Five-link axle in aluminium lightweight construction
Brakes, front		Four-piston fixed-calliper disc brakes, vented
Brakes, rear		Single-piston floating-calliper disc brakes, vented
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control),
		Cornering Brake Control (CBC), Dynamic Brake Control (DBC),
		Dry Braking function, Fading Compensation, Start-Off Assistant; optiona
		Dynamic Damper Control
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver
		and front passenger, head airbags for front and rear seats, three-point
		inertia-reel belts on all seats with belt stopper, belt latch tensioner and
		belt force limiter at the front seats, crash-active front head restraints,
		crash sensors, tyre pressure indicator
Steering		Electric Power Steering (EPS)
		with Servotronic function
Steering transmission, overall	:1	16.3
Tyres, front/rear		225/55 R17 97Y
Rims, front/rear		7.5J x 17 light-alloy
Performance		
Acceleration 0–100 km/h	s	6.2
Maximum speed	km/h	235
Maximum speed electric	km/h	140
BMW EfficientDynamics		
BMW EfficientDynamics		BMW eDrive technology, Electric Power Steering (EPS), hybrid-specific
standard measures		Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with
		coasting function and Proactive Driving Assistant,
		BMW EfficientLightweight, optimised aerodynamic attributes, active air
		vents, on-demand operation of ancillary units, map-controlled oil pump,
		detachable a/c compressor, rear differential with optimised warm-up
		behaviour, tyres with reduced roll resistance
Consumption in EU cycle for		
with standard wheels and tyres a	nd with rims 8J	x 18 and tyres 245/45 R18
Fuel consumption combined	ltr/100 km	1.9
CO ₂ emissions from fuel	g/km	44
Power consumption combined	kWh/100 km	13.1
Electric range	km	50
with rims 8J x 18 front, 9J x 18 re	ear and tyres 24	5/45 R18 front, 275/40 R18 rear,
with rims 8J x 19 and tyres 245/4	10 R19,	
		5/40 R19 front, 275/35 R19 rear,
with rims 8J x 20 front, 9J x 20 re		
and with runflat tyres	-	
Fuel consumption combined	ltr/100 km	2.0
CO ₂ emissions from fuel	g/km	46
Power consumption combined	kWh/100 km	
Electric range	km	
with winter tyres		
Fuel consumption combined	ltr/100 km	2.1
CO ₂ emissions from fuel	g/km	
Power consumption combined	kWh/100 km	
Electric range		
	km	46 EU6
Emission rating		LOO

Specifications apply to ACEA markets; data relevant to homologation applicable in part only to Germany (weight)

Height including roof aerial
 Oil change volume
 Fuel consumption and CO₂ emissions depend on the selected tyre format