

Specifications.

BMW 4 Series Coupe.

418d



BMW 418d Coupe		
Body		
No. of doors/seats		2 / 4
Length/width/height ¹⁾ (unladen)	mm	4638 / 1825 / 1377
Wheelbase	mm	2810
Front/rear track	mm	1545 / 1594
Ground clearance	mm	130
Turning circle	m	11.3
Fuel capacity	approx. l	57
Cooling and heating system reservoir capacity	l	7.0
Engine oil capacity ²⁾	l	5.0
Weight, unladen (DIN/EU)	kg	1460 / 1535 (1485 / 1560)
Payload (DIN)	kg	520
Permitted total weight	kg	1980 (2005)
Permitted axle load, front/rear	kg	930 / 1115
Permitted trailer load (12%) braked/unbraked	kg	1600 / 7450
Permitted roof load/trailer download	kg	75 / 75
Luggage compartment capacity	l	445
Aerodynamic drag	c _d x A	0.28 x 2.16
Engine		
Type/no. of cylinders/valves		in-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology: variable-geometry turbocharger, common-rail direct fuel injection with magnetic valve injectors, max. injection pressure: 2000 bar
Effective capacity	cc	1995
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel type		Diesel
Output	kW/hp	110 / 150
at rpm	min ⁻¹	4000
Torque	Nm	320
at rpm	min ⁻¹	1500 – 3000
Electrical		
Battery charge/location	Ah–	90 / luggage compartment
Alternator current/output	A/W	150 / 2100
Driving Dynamics and Safety		
Front suspension		Aluminium double-joint spring-strut axle with displaced camber, small positive steering roll radius, compensation of lateral forces, anti-dive
Rear suspension		Five-link axle in lightweight steel construction
Front brakes		Single-piston floating-calliper disc brakes, vented
Rear brakes		Single-piston floating-calliper disc brakes, vented
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, start-off assistant
Safety equipment		Standard: driver and front-seat passenger airbags, driver and front-seat passenger side airbags, head airbags front and rear, three-point automatic seatbelts for all seats, seatbelt tensioners and seatbelt force limiters in front seats, crash sensors, tyre pressure indicator
Steering		Electromechanical rack-and-pinion power steering (EPS) with Servotronic function, optional: Variable Sport Steering
Overall steering ratio	:1	15.0
Front/rear tyres		225/50 R17 94V
Front/rear wheels		7.5J x 17 light-alloy

Specifications. BMW 4 Series Coupe.

BMW 418d Coupe

Transmission

Type of gearbox	6-speed manual (optional: 8-speed Steptronic)		
Gear ratios	I	:1	4.002 (5.000)
	II	:1	2.130 (3.200)
	III	:1	1.396 (2.143)
	IV	:1	1.000 (1.720)
	V	:1	0.781 (1.314)
	VI	:1	0.668 (1.000)
	VII	:1	– (0.822)
	VIII	:1	– (0.640)
	R	:1	3.647 (3.456)
Differential ratio		:1	3.231 (2.813)

Performance

Weight-to-power ratio (DIN unladen)		kg/kW	13.3 (13.5)
Specific power output		kW/l	55.1
Acceleration	0–100 km/h	sec.	8.6 (8.6)
in 5th gear	80–120 km/h	sec.	9.9 (–)
Max. speed		km/h	215 (213)

BMW EfficientDynamics

BMW EfficientDynamics Features included as standard	Brake Energy Regeneration with recuperation display, electric power steering (EPS), Auto Start Stop function, gear shift indicator, ECO PRO mode with coasting function (automatic), intelligent lightweight construction, optimised aerodynamic attributes, on-demand operation of ancillary units, map-regulated oil pump, detachable a/c compressor, differential with optimized warm-up behaviour, tyres with reduced rolling resistance
---	--

Fuel consumption (EU)³⁾

with standard wheels and tyres			
Urban	l/100 km		5.0 (5.0)
Extra-urban	l/100 km		3.7 (3.6)
Total	l/100 km		4.2 (4.1)
CO ₂ emissions	g/km		110 (109)
with 8J x 18" rims and 225/45 R18 tyres and winter tyres, with 8J x 18" front rims, 8.5J x 18" rear rims, 225/45 R18 front tyres and 255/40 R18 rear tyres, with 8J x 19" front rims, 8.5J x 19" rear rims, 225/40 R19 front tyres and 255/35 R19 rear tyres			
Urban	l/100 km		5.4 (5.3)
Extra-urban	l/100 km		3.9 (3.9)
Combined	l/100 km		4.5 (4.4)
CO ₂ emissions	g/km		118 (117)
Emissions standard			EU6

Technical data valid for ACEA countries/Some permitted weights valid only for Germany
Figures in brackets are for vehicles with automatic transmission

¹⁾ Height including roof aerial

²⁾ Oil change volume

³⁾ Fuel consumption and CO₂ emissions depend on the selected tyre format