BMW Media Information

5/2015

Valid from 7/2015

Specifications. BMW 2 Series Coupe. 225d



mm mm mm mm mm kg kg kg kg kg kg	2 / 4 4432 / 1774 / 1418 2690 1521 / 1556 140 10.9 52 5.0 1430 / 1505 510 1940 920 / 1080 1500 / 710 75 / 75
mm mm mm orox. l kg kg kg kg	4432 / 1774 / 1418 2690 1521 / 1556 140 10.9 52 5.0 1430 / 1505 510 1940 920 / 1080
mm mm mm orox. l kg kg kg kg	4432 / 1774 / 1418 2690 1521 / 1556 140 10.9 52 5.0 1430 / 1505 510 1940 920 / 1080
mm mm mm orox. l kg kg kg kg	2690 1521 / 1556 140 10.9 52 5.0 1430 / 1505 510 1940 920 / 1080 1500 / 710
mm mm rox. l kg kg kg kg	1521 / 1556 140 10.9 52 5.0 1430 / 1505 510 1940 920 / 1080 1500 / 710
mm morox. I l kg kg kg kg kg	140 10.9 52 5.0 1430 / 1505 510 1940 920 / 1080 1500 / 710
m prox. I l kg kg kg kg kg kg	10.9 52 5.0 1430 / 1505 510 1940 920 / 1080 1500 / 710
kg kg kg kg kg	52 5.0 1430 / 1505 510 1940 920 / 1080
kg kg kg kg kg	5.0 1430 / 1505 510 1940 920 / 1080 1500 / 710
kg kg kg kg kg	1430 / 1505 510 1940 920 / 1080 1500 / 710
kg kg kg kg kg	510 1940 920 / 1080 1500 / 710
kg kg kg	1940 920 / 1080 1500 / 710
kg kg	920 / 1080 1500 / 710
kg kg	1500 / 710
kg I	
Ī	
Ī	
- 1	390
	0.29 x 2.14
c _c x A	U.29 X 2.14
	in-line / 4 / 4
	BMW TwinPower Turbo technology: multi-stage charging, high and low pressure turbocharger with variable-geometry, Common Rail direct injection with solenoid valve injectors (max. injection pressure: 2500 bar)
CC	1995
	90.0 / 84.0
	16.5
1	
	Diesel
	165 / 224
	4400
	450
min ⁻¹	1500 – 3000
Ah/-	90 / luggage compartment
A/W	150/2100
	Aluminium double-joint spring strut axle
	Five-link axle in lightweight steel construction with double elastic bearing
	Single-piston floating-calliper disc brakes
	Single-pistor floating-calliper disc brakes
	Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, start-off assistant
	Standard: driver and front-seat passenger airbags, driver and front-seat passenger side airbags, head airbags front and rear, three-point automatic seatbelts for all seats, seatbelt tensioners and seatbelt force limiters in front seats, crash sensors, tyre pressure indicator
	Electromechanical rack-and-pinion power steering (EPS); optional: Servotronic function, Variable Sport Steering
·1	15.0
	205/55 R17 89Y
	7J x 17 light-alloy

BMW

Media Information

5/2015

Valid from 7/2015

Specifications. BMW 2 Series Coupe.

			BMW 225d Coupe
_			
Transmission			2 12:
Type of gearbox			8-speed Steptronic
Gear ratios	<u> </u>	:1	5.000
		:1	3.200
		:1	2.143
	IV	:1	1.720
	V	:1	1.314
	VI	:1	1.000
	VII	:1	0.822
	VIII	:1	0.640
	R	:1	3.456
Differential ratio		:1	2.647
Performance			
Weight-to-power ra	atio		
(DIN unladen)		kg/kW	8.7
Specific power out	put	kW/l	88.6
<u> </u>	–100 km/h	sec.	6.2
in 5th gear 80-	-120 km/h	sec.	-
Max. speed	-	km/h	243
BMW EfficientDy	mamice		
BMW EfficientDyna			Brake Energy Regeneration with recuperation display, electric power steering
included as standar		•	(EPS), Auto Start Stop function, gear shift indicator, ECO PRO mode with coasting function, intelligent lightweight construction, optimised aerodynamic attributes, on-demand operation of ancillary units, map-regulated oil pump, differential with optimized-warm-up behaviour, tyres with reduced rolling resistance
F	(FII) 3)		
Fuel consumptio	<u> </u>		
with standard whee		100 1	
Urban		100 km	5.1
Extra-urban		100 km	3.9
Total	I/	100 km	4.3
CO ₂ emissions		g/km	114
with 7.5J x 17" from	nt rims, 8J x 17	''' rear rir	s and with winter tyres, ns, 225/45 R17 front tyres and 245/40 R17 rear tyres, ns, 225/40 R18 front tyres and 245/35 R18 rear tyres
Urban		100 km	5.4
Extra-urban		100 km	4.1
Combined		100 km	4.6
	I/		***
CO ₂ emissions		g/km	121
Emissions standard	d		EU6

Technical data valid for ACEA countries/Some permitted weights valid only for Germany

 $^{^{1)}}$ Height including roof aerial $^{2)}$ Oil change volume $^{3)}$ Fuel consumption and CO $_2$ emissions depend on the selected tyre format