BMW Media information

02/2014 Page 1

Valid from 04/2014

## Specifications. The new BMW X3. sDrive18d, xDrive20d.



		BMW X3 sDrive18d	BMW X3 xDrive20d		
Body					
No. of doors/seats		5/5	5/5		
Length/width/height (unladen)	mm	4657/1881/1661	4657/1881/1661		
Wheelbase	mm	2810	2810		
Track, front/rear	mm	1616/1632	1616/1632		
Ground clearance		204	204		
Turning circle	m	11.9	11.9		
Tank capacity	approx. Itr	67	67		
Cooling system incl. heating	Itr	3)	3)		
Engine oil <sup>1)</sup>	ltr	3)	3)		
Weight, unladen, to DIN/EU	kg	1660/1735 (1680/1755)	1730/1805 (1745/1820)		
Max. load to DIN	kg	640	620		
Max. permissible weight	kg	2300 (2320)	2350 (2365)		
Max. axle load, front/rear	kg	1020/1330	1050/1330 (1060/1330)		
Max. trailer load,	kg	2000/750	2000/750 (2400/750)		
braked (12%)/unbraked	1.9	2000/100	2000// 00 (2 100// 00)		
Max. roof load/towbar	kg	100/100	100/100		
download	3				
Luggage comp. capacity	ltr	550–1600	550–1600		
Air resistance	C <sub>d</sub> x A	0.33 x 2.65	0.33 x 2.65		
Engine					
Config./No. of cyls./valves		in-line/4/4 in-line/4/4			
Engine technology	BMW TwinPower Turbo technology: turbocharger with variable				
	2	inlet geometry, common rail direct injection			
Effective capacity	cm <sup>3</sup>	1995	1995		
Bore/stroke	mm	90.0/84.0	90.0/84.0		
Compression ratio	:1	16.5	16.5		
Fuel	1347/	diesel	diesel		
Output	kW/hp	110/150	140/190		
at	rpm	4000	4000		
Torque	Nm	360	400		
at	rpm	1500-2250	1750–2250		
Electrical System					
Battery/Installation	Ah/–	90/luggage comp.	90/luggage comp.		
Alternator	A/W	3)	3)		
Driving Dynamics and Safe Suspension, front	ety	Dauble igiet opring strut ovle in light.	voight steel construction		
		Double-joint spring strut axle in lightweight steel construction			
Suspension, rear		Five-link axle in lightweight steel construction			
Brakes, front		Single-piston floating-calliper disc brakes, vented			
Brakes, rear		Single-piston floating-calliper disc brakes, vented			
Driving stability systems	Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering Brake Control), DBC (Dynamic Brake Control),				
	Dry Braking function, Fading Compensation, Start-Off Assistant; DSC linked to				
	xDrive all-wheel-drive (X3 xDrive20d), HDC (Hill Descent Control);				
	optional: Performance Control, VDC (Vertical Dynamic Control)				
Safety equipment	Standard: airbags for driver and front passenger, side airbags for driver and front				
carety equipment	passenger, head airbags front and rear, three-point inertia-reel seatbelts on all				
		seats with belt stopper, belt tensioner and belt force limiter at the front			
Steering		Electromechanical rack-and-pinior			
Steering ratio, overall	:1	17.8	17.8		
Tyres, front/rear	.1	225/60 R17 99V	225/60 R17 99V		
Rims, front/rear		7.5J x 17 light-alloy	7.5J x 17 light-alloy		
		7.00 X 17 light alloy	7.50 X 17 light-alloy		

BMW Media information

02/2014 Page 2

Valid from 04/2014

			BMW X3 sDrive18d	BMW X3 xDrive20d	
Transmission					
Type of gearbox			6-speed manual transmission (optional: 8-speed automatic)		
Gear ratios	I	:1	4.110 (4.714)	4.110 (4.714)	
	II	:1	2.248 (3.143)	2.248 (3.143)	
	III	:1	1.403 (2.106)	1.403 (2.106)	
	IV	:1	1.000 (1.667)	1.000 (1.667)	
	V	:1	0.802 (1.285)	0.802 (1.285)	
	VI	:1	0.659 (1.000)	0.659 (1.000)	
	VII	:1	(0.839)	(0.839)	
	VIII	:1	(0.667)	(0.667)	
	R	:1	3.727 (3.295)	3.727 (3.295)	
Final drive		:1	3.462 (3.077)	3.727 (3.077)	
Performance					
Power-to-weigh	nt ratio (DIN)	kg/kW	15.1 (15.3)	12.4 (12.5)	
Output per litre		kW/ltr	55.1	70.2	
Acceleration	0-100 km/h	S	9.5 (9.8)	8.1 (8.1)	
	0–1000 m	S	3)	3)	
in 4th/5th gear	80-120 km/h	S	<sup>3)</sup> /10.3 (–)	<sup>3)</sup> /8.8 (–)	
Top speed		km/h	195 (195)	210 (210)	
BMW Efficient	tDynamics				
BMW EfficientDynamics, Brake Energy Regeneration, Electric Power S				Power Steering,	
standard feature	es		Auto Start Stop function, Optimum Shift Indicat	or (manual), ECO PRO mode,	
			intelligent lightweight design, on-demand operation of ancillary units,		
			final drive with optimised warm-up behaviour		
Fuel Consump	otion ECE <sup>2)</sup>				
With standard ty	yres				
Urban		l/100 km	5.6 (5.7)	6.2 (5.7)	
Extra-urban		l/100 km	4.6 (4.7)	5.0 (5.0)	
Combined		l/100 km	5.0 (5.1)	5.4 (5.2)	
CO <sub>2</sub>		g/km	131 (133)	143 (138)	
Emission rating			FU6	EU6	

Specifications apply to ACEA markets; data relevant to homologation applicable in part only to Germany (weight) Figures in brackets apply to automatic transmission

 $<sup>^{1)}</sup>$  Oil change  $^{2)}$  Fuel consumption and  $\rm CO_2$  emissions depend on the selected tyre format  $^{3)}$  Data not yet available