BMW Media Information

09/2018 Page 1

# **Specifications. BMW 6 Series Gran Turismo.**630i.



	BMW 630i Gran Turismo	
Body		
No. of doors/seats		4/5
Length/width/height 1) (unladen)	mm	5091 / 1902 / 1538
Wheelbase	mm	3070
Track, front/rear	mm	1615 / 1649
Ground clearance	mm	138
Turning circle	m	12.3
Tank capacity	approx. ltr	68
Engine oil 2)	ltr	5.25
Weight, unladen, to DIN/EU	kg	1720 / 1795
Max. load to DIN	kg	660
Max. permissible weight	kg	2380
Max. axle load, front/rear	kg	1110 / 1380
Max. trailer load,	kg	111071000
braked (12%)/unbraked	ng.	2100 / 750
Max. roof load/towbar download	kg	75 / 100
Luggage comp. capacity	itr	610 – 1800
Air resistance	C <sub>d</sub> x A	0.26 x 2.54
All resistance	Cuxx	0.20 X 2.04
Engine		
Config./No. of cyls./valves		in-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology: twin scroll turbocharger,
3 3		High Precision Injection, VALVETRONIC fully variable valve timing,
		Double-VANOS variable camshaft timing
Effective capacity	cm <sup>3</sup>	1998
Stroke/bore	mm	94.6 / 82.0
Compression ratio	:1	10.2
Fuel		min RON 91
Output	kW/hp	190 / 258
at	rpm	5000 – 6500
Torque	Nm	400
at	rpm	1550 – 4400
Electrical System		
Battery/Installation	Ah/–	90 / luggage comp.
Driving Dynamics and Safety		Last Caracita Market and control control of the con
Suspension, front	Al	luminium double track control arm axle with separate lower track arm level,
0		small steering roll radius, traverse force compensation, anti-dive
Suspension, rear	Г	Five-link axle in aluminium lightweight construction, double elastic bearing, air suspension with automatic self-levelling
Dueline fromt		
Brakes, front		Four-piston fixed-calliper disc brakes / vented
Brakes, rear		Single-piston floating-calliper disc brakes / vented
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control),
	(	CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying
		function, fading compensation, start-off assistant; optional: Adaptive
0.61		Suspension, Executive Drive
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and
		front passenger, head airbags for front and rear seats, three-point inertia-
	r	reel seatbelts on all seats with belt latch tensioner and belt force limiter at
Chandan		the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electromechanical rack-and-pinion power steering (EPS)
Chardina action as 100		with Servotronic function; optional: Integral Active Steering
Steering ratio, overall	:1	16.3
Tyres, front/rear		225/60 R17 99Y
Rims, front/rear		7.5J x 17 light-alloy

			BMW 630i Gran Turismo
Transmission			
Type of gearbox			8-speed Steptronic
Gear ratios	l	:1	5.250
	II	:1	3.360
	III	:1	2.172
	IV	:1	1.720
	V	:1	1.316
	VI	:1	1.000
	VII	:1	0.822
	VIII	:1	0.640
	R	:1	3.712
Final drive		:1	3.077
Performance			
Power-to-weight ratio (DIN)		kg/kW	9.1
Output per litre		kW/l	95.1
Acceleration 0–100 km	ı/h	S	6.3
Top speed		km/h	250

#### BMW EfficientDynamics

BMW EfficientDynamics standard features

Brake Energy Regeneration with recuperation display, EPS (Electric Power Steering), Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with coasting function and Proactive Driving Assistant, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, automatic rear spoiler, on-demand operation of ancillary units, mapcontrolled oil pump, differential with optimized-warm-up behaviour, tyres with reduced rolling resistance

Fuel consumption EU	cycle		
Urban	ltr/100 km	8.0 – 7.9	
Extra-urban	ltr/100 km	5.9 – 5.7	
Combined	ltr/100 km	6.7 – 6.5	
CO <sub>2</sub>	g/km	153 – 148	
Emission rating		EU6d-TEMP	

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

<sup>&</sup>lt;sup>1)</sup> Height including roof aerial <sup>2)</sup> Oil change volume

# BMW 6 Series Gran Turismo. 640i.

09/2018 Page 3	

		BMW 640i Gran Turismo
Body		
No. of doors/seats		4/5
Length/width/height 1) (unladen)	mm	5091 / 1902 / 1538
Wheelbase	mm	3070
Track, front/rear	mm	1615 / 1649
Ground clearance	mm	138
Turning circle	m	12.3
Tank capacity	approx. Itr	68
Engine oil 2)	ltr	6.5
Weight, unladen, to DIN/EU	kg	1770 / 1845
Max. load to DIN	kg	660
Max. permissible weight	kg	2450
Max. axle load, front/rear	kg	1175 / 1390
Max. trailer load,	kg	
braked (12%)/unbraked	J	2100 / 750
Max. roof load/towbar download	kg	75 / 100
Luggage comp. capacity	ltr	610 – 1800
Air resistance	c <sub>d</sub> x A	0.26 x 2.54
Engine		
Config./No. of cyls./valves		in-line / 6 / 4
Engine technology		BMW TwinPower Turbo technology: twin scroll turbocharger,
		High Precision Injection, VALVETRONIC fully variable valve timing,
		Double-VANOS variable camshaft timing
Effective capacity	cm <sup>3</sup>	2998
Stroke/bore	mm	94.6 / 82.0
Compression ratio	:1	11.0
Fuel		min RON 91
Output	kW/hp	250 / 340
at	rpm	5500 – 6500
Torque	Nm	450
at	rpm	1380 – 5200
Electrical System		
Battery/Installation	Ah/-	90 / luggage comp.
Datterynnstallation	Ail/	30 / luggage comp.
Driving Dynamics and Safety		
Suspension, front	А	luminium double track control arm axle with separate lower track arm level,
		small steering roll radius, traverse force compensation, anti-dive
Suspension, rear	F	Five-link axle in aluminium lightweight construction, double elastic bearing,
		air suspension with automatic self-levelling
Brakes, front		Four-piston fixed-calliper disc brakes / vented
Brakes, rear		Single-piston floating-calliper disc brakes / vented
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control),
		CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying
		function, fading compensation, start-off assistant, optional: Adaptive
		Suspension, Executive Drive
Safety equipment	5	Standard: airbags for driver and front passenger, side airbags for driver and
		front passenger, head airbags for front and rear seats, three-point inertia-
	İ	reel seatbelts on all seats with belt latch tensioner and belt force limiter at
		the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electromechanical rack-and-pinion power steering (EPS)
-		with Servotronic function; optional: Integral Active Steering
Steering ratio, overall	:1	16.3
Tyres, front/rear		225/60 R17 99Y
Rims, front/rear		7.5J x 17 light-alloy
-,		

			BMW 640i Gran Turismo
Transmissio	n		
Type of gearbo			8-speed Steptronic
Gear ratios	I	:1	5.000
	II	:1	3.200
	III	:1	2.143
	IV	:1	1.720
	V	:1	1.314
	VI	:1	1.000
	VII	:1	0.822
	VIII	:1	0.640
	R	:1	3.456
Final drive		:1	3.077
Performance	<u> </u>		
Power-to-weig	ht ratio (DIN)	kg/kW	7.1
Output per litre	Э	kW/l	83.4
Acceleration	0–100 km/h	S	5.4
Top speed		km/h	250
BMW Efficie	ntDynamics		
RMM Efficient	Dynamics	Brake Energ	ay Regeneration with reguneration display, EDS (Flectric Do)

BMW EfficientDynamics standard features

Brake Energy Regeneration with recuperation display, EPS (Electric Power Steering), Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with coasting function and Proactive Driving Assistant, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, automatic rear spoiler, on-demand operation of ancillary units, mapcontrolled oil pump, differential with optimized-warm-up behaviour, tyres with reduced rolling resistance

Fuel consumption El	J cycle		
Urban	ltr/100 km	10.2 – 10.1	
Extra-urban	ltr/100 km	6.4 – 6.1	
Combined	ltr/100 km	7.7 – 7.6	
CO <sub>2</sub>	g/km	176 – 173	
Emission rating		EU6d-TEMP	

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

<sup>&</sup>lt;sup>1)</sup> Height including roof aerial <sup>2)</sup> Oil change volume

Steering

Steering ratio, overall

Tyres, front/rear Rims, front/rear :1

09/2018 Page 5

### BMW 6 Series Gran Turismo. 640i xDrive.

		BMW 640i xDrive Gran Turismo		
Body				
No. of doors/seats		4/5		
Length/width/height 1) (unladen)	mm	5091 / 1902 / 1540		
Wheelbase	mm	3070		
Track, front/rear	mm	1615 / 1647		
Ground clearance	mm	138		
Turning circle	m	12.5		
Tank capacity	approx. ltr	68		
Engine oil 2)	ltr	6.5		
Weight, unladen, to DIN/EU	kg	1835 / 1910		
Max. load to DIN	kg	660		
Max. permissible weight	kg	2515		
Max. axle load, front/rear	kg	1220 / 1410		
Max. trailer load,	kg	12207 1110		
braked (12%)/unbraked	Ng.	2100 / 750		
Max. roof load/towbar download	kg	75 / 100		
Luggage comp. capacity	ltr	610 – 1800		
Air resistance	c <sub>d</sub> x A	0.27 x 2.54		
Engine				
Config./No. of cyls./valves		in-line / 6 / 4		
Engine technology		BMW TwinPower Turbo technology: twin scroll turbocharger,		
		High Precision Injection, VALVETRONIC fully variable valve timing,		
		Double-VANOS variable camshaft timing		
Effective capacity	cm <sup>3</sup>	2998		
Stroke/bore	mm	94.6 / 82.0		
Compression ratio	:1	11.0		
Fuel	1147	min RON 91		
Output	kW/hp	250 / 340		
at	rpm	5500 – 6500		
Torque	Nm	450		
at	rpm	1380 – 5200		
Electrical System				
Battery/Installation	Ah/-	90 / luggage comp.		
Driving Dynamics and Cafety				
Driving Dynamics and Safety Suspension, front	A	luminium double track control arm axle with separate lower track arm leve		
Casperision, were	, ,	small steering roll radius, traverse force compensation, anti-dive		
Suspension, rear	F	Five-link axle in aluminium lightweight construction, double elastic bearing		
, , , , ,		air suspension with automatic self-levelling		
Brakes, front	Four-piston fixed-calliper disc brakes / vented			
Brakes, rear	Single-piston floating-calliper disc brakes / vented			
Driving stability systems	Standard: DSC incl. ABS and DTC (Dynamic Traction Control),			
3, -, -,	CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying			
	function, fading compensation, start-off assistant, networked with xDrive al			
		wheel-drive system; optional: Adaptive Suspension, Executive Drive		
Safety equipment	5	Standard: airbags for driver and front passenger, side airbags for driver and		
	front passenger, head airbags for front and rear seats, three-point inertia-			
	reel seatbelts on all seats with belt latch tensioner and belt force limiter at			
		the front seats, crash sensors, Tyre Pressure Indicator		
Ctooring		Electromophopical rook and pinion power steering (EDC)		

Electromechanical rack-and-pinion power steering (EPS) with Servotronic function; optional: Integral Active Steering

16.3

225/60 R17 99Y 7.5J x 17 light-alloy

			BMW 640i xDrive Gran Turismo
Transmission			
Type of gearbo	X		8-speed Steptronic
Gear ratios		:1	5.000
	II	:1	3.200
	III	:1	2.143
	IV	:1	1.720
	V	:1	1.314
	VI	:1	1.000
	VII	:1	0.822
	VIII	:1	0.640
	R	:1	3.456
Final drive		:1	3.077
Performance			
Power-to-weig	ht ratio (DIN)	kg/kW	7.3
Output per litre	)	kW/l	83.4
Acceleration	0–100 km/h	S	5.3
Top speed		km/h	250
BMW Efficien	ntDynamics		
BMW EfficientI	Dynamics	В	rake Energy Regeneration with recuperation display, EPS (Electric Power
standard featur	res		Steering), Auto Start Stop function, Optimum Shift Indicator,
			ECO DDO made with accepting function and Dropative Driving Assistant

ECO PRO mode with coasting function and Proactive Driving Assistant,  ${\bf BMW\ Efficient Lightweight,\ optimised\ aerodynamic\ attributes,\ active\ air\ flap}$ control, automatic rear spoiler, on-demand operation of ancillary units, mapcontrolled oil pump, differential and power divider with optimized-warm-up behaviour, tyres with reduced rolling resistance

Fuel consumption El	J cycle		
Urban	ltr/100 km	10.9 – 10.8	
Extra-urban	ltr/100 km	6.7 – 6.5	
Combined	ltr/100 km	8.2 – 8.1	
CO <sub>2</sub>	g/km	187 – 184	
Emission rating		EU6d-TEMP	

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

<sup>&</sup>lt;sup>1)</sup> Height including roof aerial <sup>2)</sup> Oil change volume

# BMW 6 Series Gran Turismo. 620d.

09/2018
Page 7

		BMW 620d Gran Turismo
Body		A / F
No. of doors/seats		4/5
Length/width/height 1) (unladen)	mm	5091 / 1902 / 1538
Wheelbase	mm	3070
Track, front/rear	mm	1615 / 1647
Ground clearance	mm	138
Turning circle	m	12.3
Tank capacity	approx. ltr	66
Engine oil 2)	ltr	5.0
Weight, unladen, to DIN/EU	kg	1765 / 1840
Max. load to DIN	kg	680
Max. permissible weight	kg	2440
Max. axle load, front/rear	kg	1150 / 1425
Max. trailer load,	kg	
braked (12%)/unbraked		2100 / 750
Max. roof load/towbar download	kg	75 / 100
Luggage comp. capacity	ltr	610 – 1800
Air resistance	c <sub>d</sub> x A	0.25 x 2.54
Engine		
Config./No. of cyls./valves		in-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology: turbocharger with variable inlet
		geometry, common rail direct fuel injection with solenoid injectors
		(max. injection pressure: 2000 bar)
Effective capacity	cm <sup>3</sup>	1995
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel		Diesel
Output	kW/hp	140 / 190
at	rpm	4000
Torque	Nm	400
at	rpm	1750 – 2500
Electrical System		
Battery/Installation	Ah/-	90 / luggage comp.
Datter y/ii istaliation	All/	30 / luggage comp.
<b>Driving Dynamics and Safety</b>		
Suspension, front	А	luminium double track control arm axle with separate lower track arm level,
		small steering roll radius, traverse force compensation, anti-dive
Suspension, rear	F	Five-link axle in aluminium lightweight construction, double elastic bearing,
		air suspension with automatic self-levelling
Brakes, front		Four-piston fixed-calliper disc brakes / vented
Brakes, rear		Single-piston floating-calliper disc brakes / vented
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control),
		CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying
		function, fading compensation, start-off assistant; optional: Adaptive
		Suspension, Executive Drive
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and
		front passenger, head airbags for front and rear seats, three-point inertia-
		reel seatbelts on all seats with belt latch tensioner and belt force limiter at
		the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electromechanical rack-and-pinion power steering (EPS)
		with Servotronic function; optional: Integral Active Steering
Steering ratio, overall	:1	16.3
Tyres, front/rear		225/60 R17 99Y
Rims, front/rear		7.5J x 17 light-alloy

			BMW 620d Gran Turismo
Transmission			
Type of gearbox			8-speed Steptronic
Gear ratios	I	:1	5.250
	II	:1	3.360
	III	:1	2.172
	IV	:1	1.720
	V	:1	1.316
	VI	:1	1.000
	VII	:1	0.822
	VIII	:1	0.640
	R	:1	3.712
Final drive		:1	3.077
Performance			
Power-to-weight ratio	(DIN)	kg/kW	12.6
Output per litre		kW/l	70.2
Acceleration 0-1	00 km/h	S	7.9
Top speed		km/h	220

#### BMW EfficientDynamics

BMW EfficientDynamics standard features

Brake Energy Regeneration with recuperation display, EPS (Electric Power Steering), Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with coasting function and Proactive Driving Assistant,  ${\bf BMW\ Efficient Lightweight,\ optimised\ aerodynamic\ attributes,\ active\ air\ flap}$ control, automatic rear spoiler, on-demand operation of ancillary units, mapcontrolled oil pump, differential with optimized-warm-up behaviour, tyres with reduced rolling resistance, BMW Blue Performance technology including SCR catalytic converter

Fuel consumption El	J cycle		
Urban	ltr/100 km	5.4 – 5.4	
Extra-urban	ltr/100 km	4.6 – 4.5	
Combined	ltr/100 km	4.9 – 4.8	
CO <sub>2</sub>	g/km	129 – 127	
Emission rating		EU6d-TEMP	

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

<sup>&</sup>lt;sup>1)</sup> Height including roof aerial <sup>2)</sup> Oil change volume

# BMW 6 Series Gran Turismo. 630d.

09/2018
Page 9

		BMW 630d Gran Turismo
Body No. of doors/cooks		AIF
No. of doors/seats		4/5
Length/width/height 1) (unladen)	mm	5091 / 1902 / 1538
Wheelbase	mm	3070
Track, front/rear	mm	1615 / 1649
Ground clearance	mm	138
Turning circle	m .	12.3
Tank capacity	approx. ltr	66
Engine oil 2)	ltr	6.5
Weight, unladen, to DIN/EU	kg	1825 / 1900
Max. load to DIN	kg	680
Max. permissible weight	kg	2510
Max. axle load, front/rear	kg	1180 / 1425
Max. trailer load,	kg	
braked (12%)/unbraked		2100 / 750
Max. roof load/towbar download	kg	75 / 100
Luggage comp. capacity	ltr	610 – 1800
Air resistance	c <sub>d</sub> x A	0.25 x 2.54
Engine		
Config./No. of cyls./valves		in-line / 6 / 4
Engine technology		BMW TwinPower Turbo technology: turbocharger with variable inlet
3		geometry, common rail direct fuel injection with piezo injectors
		(max. injection pressure: 2500 bar)
Effective capacity	cm <sup>3</sup>	2993
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel		Diesel
Output	kW/hp	195 / 265
at	rpm	4000
Torque	Nm	620
at	rpm	2000 – 2500
	тртт	2000 2000
Electrical System	A	00.41
Battery/Installation	Ah/–	90 / luggage comp.
Driving Dynamics and Safety		
Suspension, front	Δ	Aluminium double track control arm axle with separate lower track arm level
		small steering roll radius, traverse force compensation, anti-dive
Suspension, rear	F	Five-link axle in aluminium lightweight construction, double elastic bearing,
		air suspension with automatic self-levelling
Brakes, front	Four-piston fixed-calliper disc brakes / vented	
Brakes, rear		Single-piston floating-calliper disc brakes / vented
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control),
		CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying
		function, fading compensation, start-off assistant; optional: Adaptive
		Suspension, Executive Drive
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and
		front passenger, head airbags for front and rear seats, three-point inertia-
		reel seatbelts on all seats with belt latch tensioner and belt force limiter at
		the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electromechanical rack-and-pinion power steering (EPS)
		with Servotronic function; optional: Integral Active Steering
Steering ratio, overall	:1	16.3
Tyres, front/rear		225/60 R17 99Y
Rims, front/rear		7.5J x 17 light-alloy

			BMW 630d Gran Turismo
Transmission			
Type of gearbox			8-speed Steptronic
Gear ratios	I	:1	5.000
	II	:1	3.200
	III	:1	2.143
	IV	:1	1.720
	V	:1	1.313
	VI	:1	1.000
	VII	:1	0.823
	VIII	:1	0.640
	R	:1	3.478
Final drive		:1	2.563
Performance			
Power-to-weight ra	atio (DIN)	kg/kW	9.4
Output per litre		kW/l	65.2
Acceleration (	)–100 km/h	S	6.1
Top speed		km/h	250

#### BMW EfficientDynamics

BMW EfficientDynamics standard features

Brake Energy Regeneration with recuperation display, EPS (Electric Power Steering), Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with coasting function and Proactive Driving Assistant,  ${\bf BMW\ Efficient Lightweight,\ optimised\ aerodynamic\ attributes,\ active\ air\ flap}$ control, automatic rear spoiler, on-demand operation of ancillary units, mapcontrolled oil pump, differential with optimized-warm-up behaviour, tyres with reduced rolling resistance, BMW Blue Performance technology including SCR catalytic converter

Fuel consumption EU cycle				
Urban	ltr/100 km	6.9 – 6.8		
Extra-urban	ltr/100 km	5.1 – 4.8		
Combined	ltr/100 km	5.8 – 5.5		
CO <sub>2</sub>	g/km	152 – 146		
Emission rating		EU6c		

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

<sup>&</sup>lt;sup>1)</sup> Height including roof aerial <sup>2)</sup> Oil change volume

Information 09/2018 Page 11

# BMW 6 Series Gran Turismo. 630d xDrive.

		BMW 630d xDrive Gran Turismo
Body		
No. of doors/seats		4/5
Length/width/height 1) (unladen)	mm	5091 / 1902 / 1540
Wheelbase	mm	3070
Track, front/rear	mm	1615 / 1647
Ground clearance	mm	138
Turning circle	m	12.5
Tank capacity	approx. ltr	66
Engine oil 2)	Itr	6.5
Weight, unladen, to DIN/EU	kg	1880 / 1955
Max. load to DIN	kg	680
Max. permissible weight	kg	2580
Max. axle load, front/rear		1250 / 1445
Max. trailer load,	kg kg	12307 1443
braked (12%)/unbraked	kg	2100 / 750
Max. roof load/towbar download	l.a	75 / 100
	kg ltr	
Luggage comp. capacity	ltr	610 – 1800
Air resistance	c <sub>d</sub> x A	0.26 x 2.54
Engine		
Config./No. of cyls./valves		in-line / 6 / 4
Engine technology		BMW TwinPower Turbo technology: turbocharger with variable inlet
3 3,		geometry, common rail direct fuel injection with piezo injectors
		(max. injection pressure: 2500 bar)
Effective capacity	cm <sup>3</sup>	2993
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel		Diesel
Output	kW/hp	195 / 265
at	rpm	4000
Torque	Nm	620
at	rpm	2000 – 2500
ut	тріті	2000 2000
Electrical System		
Battery/Installation	Ah/-	90 / luggage comp.
Driving Dynamics and Safety		
Suspension, front	A	luminium double track control arm axle with separate lower track arm leve
		small steering roll radius, traverse force compensation, anti-dive
Suspension, rear	F	Five-link axle in aluminium lightweight construction, double elastic bearing
		air suspension with automatic self-levelling
Brakes, front		Four-piston fixed-calliper disc brakes / vented
Brakes, rear		Single-piston floating-calliper disc brakes / vented
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control),
		CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying
		unction, fading compensation, start-off assistant, networked with xDrive a
		wheel-drive system; optional: Adaptive Suspension, Executive Drive
Safety equipment	5	Standard: airbags for driver and front passenger, side airbags for driver an
y 112 12 2 2		front passenger, head airbags for front and rear seats, three-point inertia
		reel seatbelts on all seats with belt latch tensioner and belt force limiter a
		the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electromechanical rack-and-pinion power steering (EPS)
		with Servotronic function; optional: Integral Active Steering
Steering ratio, overall	:1	16.3
Tyres, front/rear		225/60 R17 99Y
Rims, front/rear		
riino, iiunureai		7.5J x 17 light-alloy

			BMW 630d xDrive Gran Turismo
Transmission			
Type of gearbox	,		8-speed Steptronic
Gear ratios	1	:1	5.000
Geal Tallos	· I	:1	3.200
	<u>"</u>	:1	2.143
	IV		1.720
	V		1.313
	V	:1	1.000
	VII	:1	
	VII		0.823
		:1	0.640
Et al. 12 a	R	:1	3.478
Final drive		:1	2.563
Performance			
Power-to-weigh	t ratio (DIN)	kg/kW	9.6
Output per litre		kW/l	65.2
Acceleration	0-100 km/h	S	6.0
Top speed		km/h	250
BMW Efficient			
BMW EfficientD	,		Brake Energy Regeneration with recuperation display, EPS (Electric Power
standard feature	es .		Steering), Auto Start Stop function, Optimum Shift Indicator,
			ECO PRO mode with coasting function and Proactive Driving Assistant,
			BMW EfficientLightweight, optimised aerodynamic attributes, active air flap
			control, automatic rear spoiler, on-demand operation of ancillary units, map-
			controlled oil pump, differential and power divider with optimized-warm-up
			behaviour, tyres with reduced rolling resistance,
			BMW Blue Performance technology including SCR catalytic converter
Fuel consump	tion EU cycle		
Urban		Itr/100 km	7.1 – 6.7
Extra-urban		ltr/100 km	5.2 – 5.2
Combined		ltr/100 km	5.9 – 5.7
CO <sub>2</sub>		g/km	156 – 151
Emission rating			EU6c

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

<sup>&</sup>lt;sup>1)</sup> Height including roof aerial <sup>2)</sup> Oil change volume

### BMW 6 Series Gran Turismo. 640d xDrive.

09/2018
Page 13

		BMW 640d xDrive Gran Turismo
Body		415
No. of doors/seats		4/5
Length/width/height 1) (unladen)	mm	5091 / 1902 / 1540
Wheelbase	mm	3070
Track, front/rear	mm	1615 / 1647
Ground clearance	mm	138
Turning circle	m	12.5
Tank capacity	approx. ltr	66
Engine oil 2)	ltr	6.5
Weight, unladen, to DIN/EU	kg	1935 / 2010
Max. load to DIN	kg	680
Max. permissible weight	kg	2615
Max. axle load, front/rear	kg	1270 / 1460
Max. trailer load,	kg	
braked (12%)/unbraked		2100 / 750
Max. roof load/towbar download	kg	75 / 100
Luggage comp. capacity	ltr	610 – 1800
Air resistance	c <sub>d</sub> x A	0.27 x 2.54
Engine		
Config./No. of cyls./valves		in-line / 6 / 4
Engine technology		BMW TwinPower Turbo technology: multi-stage charging,
Engine technology		high and low pressure turbocharger with variable inlet geometry, common
		rail direct fuel injection with piezo injectors
		(max. injection pressure: 2500 bar)
Effective capacity	cm <sup>3</sup>	2993
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel		Diesel
Output	kW/hp	235 / 320
		4400
Torque	rpm Nm	680
Torque at		1750 – 2250
at	rpm	1730 - 2230
Electrical System		
Battery/Installation	Ah/-	90 / luggage comp.
Driving Dynamics and Safety		
Suspension, front		Aluminium double track control arm axle with separate lower track arm level
, , , , , , , , , , , , , , , , , , , ,		small steering roll radius, traverse force compensation, anti-dive
Suspension, rear		Five-link axle in aluminium lightweight construction, double elastic bearing,
Casponolon, real		air suspension with automatic self-levelling
Brakes, front		Four-piston fixed-calliper disc brakes / vented
Brakes, rear		Single-piston floating-calliper disc brakes / vented
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control),
Driving stability systems		CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying
	f	function, fading compensation, start-off assistant, networked with xDrive all-
	'	wheel-drive system; optional: Adaptive Suspension, Executive Drive
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and
carety equipment		front passenger, head airbags for front and rear seats, three-point inertia-
		reel seatbelts on all seats with belt latch tensioner and belt force limiter at
		the front seats, crash sensors, Tyre Pressure Indicator
Ctaorina		Electromechanical rack-and-pinion power steering (EPS)
21660100		with Servotronic function; optional: Integral Active Steering
Steering		
	•1	, ,
Steering ratio, overall	:1	16.3
	:1	, ,

			BMW 640d xDrive Gran Turismo
Transmission			
Type of gearbox	·		8-speed Steptronic
Gear ratios	<u>`</u>	:1	5.000
acai ratios	· II	:1	3.200
		:1	2.143
	IV	:1	1.720
	V	:1	1.313
	VI	:1	1.000
	VII	:1	0.823
	VIII	:1	0.640
	R	:1	3.478
Final drive		:1	2.563
Performance			
Power-to-weigh	t ratio (DIN)	kg/kW	
Output per litre		kW/l	
Acceleration	0–100 km/h	S	5.3
Top speed		km/h	250
BMW Efficient			
BMW EfficientD	,		Brake Energy Regeneration with recuperation display, EPS (Electric Power
standard feature	es .		Steering), Auto Start Stop function, Optimum Shift Indicator,
			ECO PRO mode with coasting function and Proactive Driving Assistant,
			BMW EfficientLightweight, optimised aerodynamic attributes, active air flap
			control, automatic rear spoiler, on-demand operation of ancillary units, map- controlled oil pump, differential and power divider with optimized-warm-up
			behaviour, tyres with reduced rolling resistance,
			BMW Blue Performance technology including SCR catalytic converter
			Bivivy Blue Performance technology including 5CR catalytic converter
Fuel consump	tion EU cycle		
Urban		Itr/100 km	7.2 – 7.0
Extra-urban		ltr/100 km	5.5 – 5.3
Combined		ltr/100 km	6.1 – 5.9
CO <sub>2</sub>		g/km	161 – 155
Emission rating			EU6c

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

<sup>&</sup>lt;sup>1)</sup> Height including roof aerial <sup>2)</sup> Oil change volume