BMW Media Information 01/2021 Page 1

The new BMW M5 CS. Specifications.



| | | BMW M5 CS |
|-----------------------------------|-----------|---|
| | | |
| Body No of doors / cooks | | AIA |
| No of doors / seats | 2000 | 4/4 |
| Length / width / height (unladen) | mm | 5001 / 1903 / 1468 |
| Wheelbase | mm | 2982 |
| Track, front / rear | mm | 1625 / 1594 |
| Ground clearance | mm | 119 |
| Turning circle | m | 12.6 |
| Fuel tank capacity | approx. I | 68 |
| Engine oil ¹⁾ | прргод. 1 | 10.0 |
| Weight, unladen, to DIN / EU | kg | 1825 / 1900 |
| Max load to DIN | kg | 465 |
| Max permissible weight | kg | 2290 |
| Max axle load, front / rear | kg | 1165 / 1170 |
| Max roofload / max towbar | kg | 100 / 90 |
| download | ĸy | 1007 90 |
| Luggage comp capacity | 1 | 530 |
| Air resistance | Cd X A | 0.80 |
| 7 III TOSISTATIOS | Ou X Y Y | 0.00 |
| Power Unit | | |
| Config / No of cyls / valves | | V/8/4 |
| Engine technology | | M TwinPower Turbo technology with cross-bank exhaust manifold: |
| 0 0 | N | M TwinScroll twin turbocharger, indirect charge air cooling, High Precision Injection (maximum injection pressure: 350 bar), VALVETRONIC fully variable valve timing, Double-VANOS variable camshaft timing |
| Effective capacity | CC | 4395 |
| Stroke/bore | mm | 88.3 / 89.0 |
| Compression ratio | :1 | 10.0 |
| Fuel | | RON 98 (min. RON 91) |
| Max output | kW/hp | 467 / 635 |
| at | rpm | 6000 |
| Max torque | Nm | 750 |
| at | rpm | 1800 – 5950 |
| | трпп | 1000 0300 |
| Electrical System | | |
| Battery/installation | Ah/- | 70 (Li-ion) / luggage |
| | | compartment |
| | | |
| Driving Dynamics and Safe | ety | |
| Suspension, front | C | Adaptive M suspension with double wishbone axle in lightweight aluminium construction, M-specific kinematics and elastokinematics, Variable Damper Control |
| Suspension, rear | | Adaptive M suspension with five-link axle in lightweight aluminium construction, |
| Brakes, front | | M-specific elastokinematics, Variable Damper Control M Carbon ceramic brakes with six-piston fixed callipers; vented brake discs |
| Brakes, rear | | |
| | | M Carbon ceramic brakes with single-piston floating callipers; vented brake discs |
| Driving stability systems | , | Standard: DSC incl. ABS, ASC and M Dynamic Mode (MDM), can be switched off, CBC (Cornering Brake Control), DBC (Dynamic Brake Control), Dry Braking function, Start-Off Assistant, Active M Differential, |
| | | all-wheel-drive system M xDrive linked with DSC |
| Safety equipment | | Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags front and rear, three-point inertia-reel seatbelts on all seats with belt stopper, belt tensioner and belt force limiter at the front, crash-active front head restraints, crash sensors, tyre pressure indicator |
| Steering | | Electric Power Steering (EPS) with M-specific Servotronic function and variable sport ratio |
| Steering ratio, overall | :1 | 14.3 |
| Tyres, front / rear | | 275/35 ZR20 102Y XL 285/35 ZR20 104Y XL |
| Rims, front / rear | | 9.5J x 20 light-alloy |
| | | 10.5J x 20 light-alloy |
| | | 10.00 X 20 light diloy |

BMW M5 CS Power Transfer M xDrive intelligent all-wheel drive, central transfer case with fully variable multiplate clutch, fully variable torque distribution between front and rear axle, rear differential with fully variable Active M Differential, locking effect 0 - 100 per cent Transmission Eight-speed M Steptronic transmission with Drivelogic, transmission oil cooling Type of transmission Gear ratios 5.000 Ш :1 3.200 Ш 2.143 IV :1 1.720 V :1 1.313 \/I 1.000 VII 0.823 VIII :1 0.640 R :1 3.478 Final drive :1 3.154 Performance Power-to-weight ratio (DIN) 3.9 kg/hp Output per litre kW/l 106.3 Acceleration 0-100 km/h S 3.0 Acceleration 0-200 km/h 10.4 Top speed km/h 305 2) **BMW EfficientDynamics** BMW EfficientDynamics Brake Energy Regeneration, Electric Power Steering, Auto Start Stop function, Optimum Shift Indicator in manual shift mode, BMW EfficientLightweight, standard features on-demand operation of ancillary units, Li-ion battery, map-regulated oil pump, rear differential and transfer case with optimised efficiency, optimised aerodynamic attributes (underbody panelling, front spoiler, rear spoiler) **Fuel Consumption ECE** l/100 km Urban 16.9 – 16.6 Extra-urban I/100 km 8.1 – 7.7 11.3 – 11.1 Combined I/100 km CO2 g/km 258 - 253

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

Emission rating

The fuel consumption and CO_2 emission figures are determined according to the European Regulation (EC) 2007/715 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO_2 emissions, the CO_2 values may differ from the values stated here (depending on national legislation).

Further information on official fuel consumption figures and specific CO₂ emission values of new passenger cars is included in the following guideline: 'Leitfaden über den Kraftstoffverbrauch, die CO₂-Emissionen und den Stromverbrauch neuer Personenkraftwagen' (Guide to the fuel economy, CO₂ emissions and electric power consumption of new passenger cars), which can be obtained free of charge from all dealerships, from Deutsche Automobil Treuhand GmbH (DAT), Hellmuth-Hirth-Str. 1, 73760 Ostfildern-Scharnhausen and at https://www.dat.de/co2/.

¹⁾ Oil change

²⁾ Limited

BMW Media Information

Output and torque diagrams. The new BMW M5 CS.





