# **Technical specifications.** The new BMW 4 Series Convertible.



**420i.** 

	BMW 420i Convertible		
Body			
No of doors/seats		2/4	
Length/width/height (unladen)	mm	4768 / 1852 / 1384	
Wheelbase	mm	2851	
Track, front/rear	mm	1575 / 1611	
Ground clearance	mm	124	
Turning circle	m	11.4	
Fuel tank capacity	approx. I	59	
Engine oil 1)		5.25	
Veight, unladen, to DIN/EU	kg	1690 / 1765	
Max load to DIN	kg	495	
Vlax permissible weight	kg	2185	
Vax axle load, front/rear		990 / 1240	
Vlax axie load, irontreal Vlax trailer load	kg	9907 1240	
braked (12%)/unbraked	kg	1600 / 750	
Max roofload/max towbar	kg	-/75	
download			
_uggage comp capacity		385	
Air resistance	c <sub>d</sub> x A	0.28 x 2.19	
Power Unit			
Config/No of cyls/valves		In-line / 4 / 4	
Engine technology		BMW TwinPower Turbo technology: TwinScroll turbocharger, High Precision Injection, VALVETRONIC fully variable valve timing, Double-	
		VANOS variable camshaft timing	
Effective capacity	CC	1998	
Stroke/bore	mm	94.6 / 82.0	
Compression ratio	:1	11.0	
Fuel		min. RON 91	
Vax output	kW/hp	135 / 184	
at	rpm	5000 – 6500	
Max torque	Nm	300	
at	rpm	1350 – 4000	
Electrical System			
Battery/installation	Ah/–	80 / luggage compartment	
Driving Dynamics and Safety	,		
Suspension, front		Double-joint spring strut axle in lightweight aluminium-steel construction,	
		hydraulically damped torque strut bearing	
Suspension, rear		Five-link axle in lightweight aluminium-steel construction	
Brakes, front		Vented disc brakes, with single-piston floating callipers	
Brakes, rear		Vented disc brakes, with single-piston floating calipers	
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC	
Shiring stability systems		(Cornering Brake Control), DBC (Dynamic Brake Control), Performance	
		Control, Dry Braking function, Fading Compensation, Start-Off Assistant;	
		optional: Adaptive M suspension	
Safety equipment	Standard: airbags for driver and front passenger, side airbags for driver and		
balety equipment	front passenger with combined head airbags, three-point inertia-reel		
		seatbelts on all seats with belt tensioner and belt force limiter at the front	
		crash sensors, rollover protection system, tyre pressure indicator	
Steering		Electric Power Steering (EPS)	
		with Servotronic function, optional: variable sport steering	
Steering ratio, overall	:1	14.1	
Tyres, front/rear		225/50 R17 98Y XL	
Rims, front/rear		7.5J x 17 light-alloy	

			BMW 420i Convertible
Transmission			
Type of transmission	on		Eight-speed Steptronic transmission
Gear ratios		:1	5.250
		:1	3.360
		:1	2.172
	IV	:1	1.720
	V	:1	1.316
	VI	:1	1.000
	VII	:1	0.822
	VIII	:1	0.640
	R	:1	3.712
Final drive		:1	2.813
Performance			
Power-to-weight ra	atio (DIN)	kg/kW	12.5
Output per litre		kW/l	67.6
Acceleration 0	–100 km/h	S	8.2
Top speed		km/h	236

#### BMW EfficientDynamics

BMW EfficientDynamics standard features

Brake Energy Regeneration with recuperation display, Electric Power Steering, Auto Start Stop function, Optimum Shift Indicator, ECO PRO and COMFORT mode with coasting function, Proactive Driving Assistant, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, differential with optimised warm-up behaviour, tyres with reduced rolling resistance

Fuel Consumption ECE				
Urban	l/100 km	9,2 - 9,8		
Extra-urban	l/100 km	5,8 - 6,2		
Combined	l/100 km	6,7 - 7,2		
CO <sub>2</sub>	g/km	152 - 164		
Emission rating		Euro 6d		

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

<sup>1)</sup> Oil change

The fuel consumption, CO<sub>2</sub> emissions and electric power consumption figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO<sub>2</sub> emissions, the CO<sub>2</sub> values may differ from the values stated here (depending on national legislation).

Further information on official fuel consumption figures and specific CO<sub>2</sub> emission values of new passenger cars is included in the following guideline: Leitfaden über den Kraftstoffverbrauch, die CO<sub>2</sub>-Emissionen und den Stromverbrauch neuer Personenkraftwagen' (Guide to the fuel economy, CO<sub>2</sub> emissions and electric power consumption of new passenger cars), which can be obtained free of charge from all dealerships, from Deutsche Automobil Treuhand GmbH (DAT), Hellmuth-Hirth-Str. 1, 73760 Ostfildern-Scharnhausen and at https://www.dat.de/co2/.

## The new BMW 4 Series Convertible. M440i xDrive.

	BMW M440i xDrive Convertible			
Body				
No of doors/seats		2/4		
Length/width/height (unladen)	mm	4770 / 1852 / 1394		
Wheelbase	mm	2851		
Track, front/rear	mm	1575 / 1611		
Ground clearance	mm	126		
Turning circle	m	12.0		
Fuel tank capacity	approx. I	59		
Engine oil 1)	1	7.2		
Weight, unladen, to DIN/EU	kg	1890 / 1965		
Max load to DIN	kg	500		
Max permissible weight	kg	2390		
Max axle load, front/rear	kg	1120 / 1300		
Max trailer load	kg			
braked (12%)/unbraked	-	1800 / 750		
Max roofload/max towbar	kg	-175		
download				
Luggage comp capacity	1	385		
Air resistance	c <sub>d</sub> x A	0.28 x 2.19		
Power Unit				
Config/No of cyls/valves		In-line / 6 / 4		
Engine technology		BMW TwinPower Turbo technology: TwinScroll turbocharger, High		
		Precision Injection, VALVETRONIC fully variable valve timing, Double-		
		VANOS variable camshaft timing		
Effective capacity	CC	2998		
Stroke/bore	mm	94.6 / 82.0		
Compression ratio	:1	10.2		
Fuel		min. RON 91		
Max output	kW/hp	275/374		
at	rpm	5500 - 6500		
Max torque	Nm	500		
at	rpm	1900 – 5000		
48V mild hybrid technology				
Max output	kW/hp	8/11		
Electrical System		<b>66</b> /4		
12V battery/installation	Ah/-	80 / luggage compartment		
48V battery/installation	Ah/–	11 / engine compartment		
Driving Dynamics and Safety				
		Double-joint spring strut axle in lightweight aluminium-steel construction,		
Suspension, front		hydraulically damped torque strut bearing		
Cuonancian rear				
Suspension, rear		Five-link axle in lightweight aluminium-steel construction		
Brakes, front		Vented disc brakes, with four-piston fixed callipers		
Brakes, rear		Vented disc brakes, with single-piston floating callipers		
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC		
	C	(Cornering Brake Control), DBC (Dynamic Brake Control), Performance Control, Dry Braking function, Fading Compensation, Start-Off Assistant, all-		
	Ĺ			
		wheel-drive system xDrive linked with DSC, M Sport differential; optional: Adaptive M suspension		
		Standard: airbags for driver and front passenger, side airbags for driver and		
Salety equipment	Ň	front passenger with combined head airbags, three-point inertia-reel		
		seatbelts on all seats with belt tensioner and belt force limiter at the front,		
		crash sensors, rollover protection system, tyre pressure indicator		
Steering		Electric Power Steering (EPS)		
Steering		Electric Power Steering (EPS)		
	·1	variable sport steering with Servotronic function		
Steering ratio, overall	:1	variable sport steering with Servotronic function 13.6		
Steering Steering ratio, overall Tyres, front/rear	:1	variable sport steering with Servotronic function 13.6 225/45 R18 95Y XL		
Steering ratio, overall	:1	variable sport steering with Servotronic function 13.6		

			BMW M440i xDrive Convertible
Transmissior	1		
Type of transm	nission		Eight-speed Steptronic transmission
Gear ratios		:1	5.250
		:1	3.360
		:1	2.172
	IV	:1	1.720
	V	:1	1.316
	VI	:1	1.000
	VII	:1	0.822
	VIII	:1	0.640
	R	:1	3.712
Final drive		:1	2.813
Performance			
Power-to-weig	ht ratio (DIN)	kg/kW	6.9
Output per litre	)	kW/l	91.7
Acceleration	0–100 km/h	S	4.9
Top speed		km/h	250
BMW Efficier	ntDynamics		
<b>BMW</b> Efficient	Dynamics standard		Mild hybrid technology with 48V starter-generator, Brake Energy
features			egeneration with recuperation display, Auto Start Stop function, ECO PRC

Regeneration with recuperation display, Auto Start Stop function, ECO PRO and COMFORT mode with coasting function, Proactive Driving Assistant, Optimum Shift Indicator, Electric Power Steering, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, efficiency-optimised allwheel drive, differential with optimised warm-up behaviour, tyres with reduced rolling resistance

Fuel Consumption E	CE		
Urban	l/100 km	11,7 - 12,3	
Extra-urban	l/100 km	6,6 - 7,2	
Combined	l/100 km	7,8 - 8,4	
CO <sub>2</sub>	g/km	177 - 192	
Emission rating		Euro 6d	

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

<sup>1)</sup> Oil change

The fuel consumption, CO<sub>2</sub> emissions and electric power consumption figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO<sub>2</sub> emissions, the CO<sub>2</sub> values may differ from the values stated here (depending on national legislation).

Further information on official fuel consumption figures and specific CO<sub>2</sub> emission values of new passenger cars is included in the following guideline: "Leitfaden über den Kraftstoffverbrauch, die CO<sub>2</sub>-Emissionen und den Stromverbrauch neuer Personenkraftwagen' (Guide to the fuel economy, CO<sub>2</sub> emissions and electric power consumption of new passenger cars), which can be obtained free of charge from all dealerships, from Deutsche Automobil Treuhand GmbH (DAT), Hellmuth-Hirth-Str. 1, 73760 Ostfildern-Scharnhausen and at https://www.dat.de/co2/.

### The new BMW 4 Series Convertible. 420d.

	BMW 420d Convertible			
Body				
No of doors/seats		2/4		
Length/width/height (unladen)	mm	4768 / 1852 / 1384		
Wheelbase	mm	2851		
Track, front/rear	mm	1575 / 1611		
Ground clearance	mm	124		
Turning circle	m	11.4		
Fuel tank capacity	approx. I	59		
Engine oil 1)		5.5		
Weight, unladen, to DIN/EU	kg	1775 / 1850		
Max load to DIN	kg	495		
Max permissible weight	kg	2270		
Max axle load, front/rear	kg	1025 / 1280		
Max trailer load		10237 1200		
braked (12%)/unbraked	kg	1600 / 750		
· · · · · · · · · · · · · · · · · · ·	ka	-/75		
Max roofload/max towbar download	kg	-775		
		205		
Luggage comp capacity		385		
Air resistance	c <sub>d</sub> x A	0.27 x 2.19		
Dewer Linit				
Power Unit		In line 1414		
Config/No of cyls/valves				
Engine technology		BMW TwinPower Turbo technology: multi-stage turbocharging,		
		common-rail direct injection with solenoid injectors		
		(max. injection pressure: 2500 bar)		
Effective capacity	CC	1995		
Stroke/bore	mm	90.0 / 84.0		
Compression ratio	:1	16.5		
Fuel		Diesel		
Max output	kW/hp	140 / 190		
at	rpm	4000		
Max torque	Nm	400		
at	rpm	1750 – 2500		
48V mild hybrid technology				
Max output	kW/hp	8/11		
Electrical System				
12V battery/installation	Ah/–	80 / luggage compartment		
48V battery/installation	Ah/–	11 / engine compartment		
Driving Dynamics and Safet	v			
Suspension, front		Double-joint spring strut axle in lightweight aluminium-steel construction,		
		hydraulically damped torque strut bearing		
Suspension, rear		Five-link axle in lightweight aluminium-steel construction		
Brakes, front		Vented disc brakes, with single-piston floating callipers		
Brakes, rear		Vented disc brakes, with single-piston floating callipers		
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC		
Driving stability systems		(Cornering Brake Control), DBC (Dynamic Brake Control), Performance		
		Control, Dry Braking function, Fading Compensation, Start-Off Assistant;		
		optional: Adaptive M suspension		
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and		
		front passenger with combined head airbags, three-point inertia-reel		
		seatbelts on all seats with belt tensioner and belt force limiter at the front,		
		crash sensors, rollover protection system, tyre pressure indicator		
Stooring		Electric Power Steering (EPS)		
Steering		with Servotronic function, optional: variable sport steering		
Stooring ratio overall	:1	· · · · · · ·		
Steering ratio, overall	:1	14.1 225/50 D17 09X XI		
Tyres, front/rear		225/50 R17 98Y XL		
Rims, front/rear		7.5J x 17 light-alloy		

			BMW 420d Convertible		
Transmission	1				
Type of transm	nission		Eight-speed Steptronic transmission		
Gear ratios		:1	5.250		
	I	:1	3.360		
	III	:1	2.172		
	IV	:1	1.720		
	V	:1	1.316		
	VI	:1	1.000		
	VII	:1	0.822		
	VIII	:1	0.640		
	R	:1	3.712		
Final drive		:1	2.813		
Performance					
Power-to-weig	ht ratio (DIN)	kg/kW	12.7		
Output per litre	9	kW/l	70.2		
Acceleration	0–100 km/h	S	7.6		
Top speed	Top speed		236		
BMW Efficien	ntDynamics				
BMW Efficient	BMW EfficientDynamics standard		Mild hybrid technology with 48V starter-generator, Brake Energy		
features		Regeneration with recuperation display, Auto Start Stop function, ECO PRO and COMFORT mode with coasting function, Proactive Driving Assistant, Optimum Shift Indicator, Electric Power Steering, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, differential with optimised warm-up behaviour, tyres with reduced rolling resistance,			

BMW Blue Performance technology with SCR catalytic converter

Fuel Consumption E	CE		
Urban	l/100 km	6,2 - 6,5	
Extra-urban	l/100 km	4,3 - 4,7	
Combined	l/100 km	4,9 - 5,3	
CO <sub>2</sub>	g/km	127 - 138	
Emission rating		Euro 6d	

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

<sup>1)</sup> Oil change

The fuel consumption, CO<sub>2</sub> emissions and electric power consumption figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO<sub>2</sub> emissions, the CO<sub>2</sub> values may differ from the values stated here (depending on national legislation).

Further information on official fuel consumption figures and specific CO<sub>2</sub> emission values of new passenger cars is included in the following guideline: Leitfaden über den Kraftstoffverbrauch, die CO<sub>2</sub>-Emissionen und den Stromverbrauch neuer Personenkraftwagen' (Guide to the fuel economy, CO<sub>2</sub> emissions and electric power consumption of new passenger cars), which can be obtained free of charge from all dealerships, from Deutsche Automobil Treuhand GmbH (DAT), Hellmuth-Hirth-Str. 1, 73760 Ostfildern-Scharnhausen and at https://www.dat.de/co2/.

BMW Media Information

09/2020

### Exterioar and interior dimensions. The new BMW 4 Series Convertible. 420i.







