

BMW X6. X6 M60i xDrive.

BMW X6 M60i xDrive		
Body		
No. of doors / seats		5 / 5
Length/width/height (unladen)	mm	4960 / 2004 / 1700
Wheelbase	mm	2975
Track, front/rear	mm	1679 / 1688
Turning circle	m	12.0
Fuel tank capacity	approx. l	83
Engine oil ¹⁾	l	³⁾
Weight, unladen, to DIN/EU	kg	2315 / 2390
Max. load to DIN	kg	770
Max. permissible weight	kg	3085
Max. axle load, front/rear	kg	1430 / 1680
Max. trailer load		
braked (12%)/unbraked	kg	3500 / 750
Max. roofload/towbar download	kg	100 / 140
Luggage comp. capacity	l	580 – 1530
Air resistance	cx x A	0.35 x 2.86
Power Unit		
Engine technology	M TwinPower Turbo technology with cross-bank exhaust manifold: two twin-scroll turbochargers, High Precision Injection, VALVETRONIC fully variable valve timing, Double-VANOS variable camshaft timing, 48V mild hybrid technology using an electric motor integrated into the transmission	
Max. output, overall ²⁾	kW/hp	390 / 530
Max. torque, overall ²⁾	Nm	750
Petrol Engine		
Config./No. of cyls./valves		V / 8 / 4
Effective capacity	cc	4395
Stroke/bore	mm	88.3 / 89.0
Compression ratio	:1	10.5
Fuel		Min. RON 91
Nominal power	kW/hp	390 / 530
at	rpm	5500 – 6000
Nominal torque	Nm	750
at	rpm	1800 – 4600
Output per litre	kW/l	88.7
Electric Motor		
Nominal power	kW/hp	9 / 12
Nominal torque	Nm	200
Electrical System		
12V battery/installation	Ah/–	90 / luggage compartment
48V battery/installation	Ah/–	20 / engine compartment
Driving Dynamics and Safety		
Suspension, front	Double-wishbone axle in aluminium construction, adaptive M suspension; optional: air suspension with automatic self-levelling	
Suspension, rear	Five-link axle in lightweight steel construction, adaptive M suspension; optional: air suspension with automatic self-levelling	
Brakes, front	Four-piston fixed-calliper disc brakes	
Brakes, rear	Single-piston floating-calliper disc brakes	
Driving stability systems	Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering Brake Control), DBC (Dynamic Brake Control), Dry Braking function, fading compensation, drive-off assistant, DSC networked with xDrive all-wheel-drive system, ADB-X (Automatic Differential Brake), HDC (Hill Descent Control), trailer stability control, M Sport differential; optional: active roll stabilisation	
Safety equipment	Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia-reel seatbelts on all seats with belt tensioner and belt force limiter in the front, crash sensors, tyre pressure indicator	
Steering	Electric Power Steering (EPS) with Servotronic function, Integral Active Steering	
Steering ratio, overall	:1	17.6
Tyres, front/rear	275/40 R21 107Y XL / 315/35 R21 111Y XL	
Rims, front/rear	9.5J x 21 light-alloy / 10.5J x 21 light-alloy	

BMW X6 M60i xDrive			
Transmission			
Type of transmission		Eight-speed Steptronic transmission	
Gear ratios	I	:1	5.501
	II	:1	3.520
	III	:1	2.200
	IV	:1	1.720
	V	:1	1.301
	VI	:1	1.000
	VII	:1	0.833
	VIII	:1	0.640
	R	:1	4.543
Final drive		:1	3.154
Performance			
Power-to-weight ratio (DIN)	kg/kW		5.9
Acceleration 0–100 km/h	s		4.3
Top speed	km/h		250
Off-road Characteristics			
Angle of approach/departure	°		25.1 / 21.7
Breakover angle	°		17.9
Ground clearance (unladen)	mm		216
Fording depth (at 7 km/h)	mm		500
BMW EfficientDynamics			
BMW EfficientDynamics standard features		48V mild hybrid technology, Brake Energy Regeneration with recuperation display, Automatic Start/Stop function, COMFORT and ECO PRO modes with coasting function, Proactive Driving Assistant, Optimum Shift Indicator, Electric Power Steering, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, efficiency-optimised all-wheel drive, differential with optimised warm-up behaviour, tyres with reduced rolling resistance	
Fuel Consumption ECE			
Combined (WLTP)	l/100		12.3 – 11.4
Combined (NEDC)	l/100		–
CO ₂ (WLTP)	g/km		279 – 258
CO ₂ (NEDC)	g/km		–
Emission rating			Euro 6d

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

¹⁾ Oil change

²⁾ Developed by the combination of the combustion engine (stated nominal figure) and the electric motor (up to stated nominal figure)

³⁾ Data not yet available

The fuel consumption, CO₂ emissions, electric power consumption and electric range figures are determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany and the range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment.

All values were calculated based on the new WLTP test cycle. WLTP values are taken as the basis for determining vehicle-related taxes or other duties based (at least inter alia) on CO₂ emissions as well as eligibility for any applicable vehicle-specific subsidies. Further information on the WLTP and NEDC measurement procedures can also be found at www.bmw.de/wltp.

Further information on official fuel consumption figures and specific CO₂ emission values of new passenger cars is included in the following guideline: 'Leitfaden über den Kraftstoffverbrauch, die CO₂-Emissionen und den Stromverbrauch neuer Personenkraftwagen' (Guide to the fuel economy, CO₂ emissions and electric power consumption of new passenger cars), which can be obtained free of charge from all dealerships, from Deutsche Automobil Treuhand GmbH (DAT), Hellmuth-Hirth-Str. 1, 73760 Ostfildern-Scharnhausen and at <https://www.dat.de/co2>.

BMW X6. X6 xDrive30d.

BMW X6 xDrive30d		
Body		
No. of doors / seats		5 / 5
Length/width/height (unladen)	mm	4960 / 2004 / 1700
Wheelbase	mm	2975
Track, front/rear	mm	1683 / 1694
Turning circle	m	12.6
Fuel tank capacity	approx. l	80
Engine oil ¹⁾	l	³⁾
Weight, unladen, to DIN/EU	kg	2220 / 2295
Max. load to DIN	kg	730
Max. permissible weight	kg	2950
Max. axle load, front/rear	kg	1380 / 1680
Max. trailer load		
braked (12%)/unbraked	kg	3500 / 750
Max. roofload/towbar download	kg	100 / 140
Luggage comp. capacity	l	580 – 1530
Air resistance	cx x A	0.31 x 2.86
Power Unit		
Engine technology	BMW TwinPower Turbo technology: multi-stage turbocharging, low-pressure turbocharger with variable inlet geometry, common-rail direct injection with solenoid injectors (max. injection pressure: 2500 bar), 48V mild hybrid technology using an electric motor integrated into the transmission	
Max. output, overall ²⁾	kW/hp	219 / 298
Max. torque, overall ²⁾	Nm	670
Diesel Engine		
Config./No. of cyls./valves		In-line / 6 / 4
Effective capacity	cc	2993
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel		Diesel
Nominal power	kW/hp	210 / 286
at	rpm	4000
Nominal torque	Nm	650
at	rpm	1500 – 2500
Output per litre	kW/l	70.2
Electric Motor		
Nominal power	kW/hp	9 / 12
Nominal torque	Nm	200
Electrical System		
12V battery/installation	Ah/–	90 / luggage compartment
48V battery/installation	Ah/–	20 / engine compartment
Driving Dynamics and Safety		
Suspension, front	Double-wishbone axle in aluminium construction, adaptive M suspension; optional: air suspension with automatic self-levelling	
Suspension, rear	Five-link axle in lightweight steel construction, adaptive M suspension; optional: air suspension with automatic self-levelling	
Brakes, front	Four-piston fixed-calliper disc brakes	
Brakes, rear	Single-piston floating-calliper disc brakes	
Driving stability systems	Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering Brake Control), DBC (Dynamic Brake Control), Dry Braking function, fading compensation, drive-off assistant, DSC networked with xDrive all-wheel-drive system, ADB-X (Automatic Differential Brake), HDC (Hill Descent Control), trailer stability control; optional: active roll stabilisation, M Sport differential	
Safety equipment	Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia-reel seatbelts on all seats with belt tensioner and belt force limiter in the front, crash sensors, tyre pressure indicator	
Steering	Electric Power Steering (EPS) with Servotronic function; optional: Integral Active Steering	
Steering ratio, overall	:1	17.6
Tyres, front/rear	275/45 R20 110Y XL / 305/40 R20 112Y XL	
Rims, front/rear	9J x 20 light-alloy / 10.5J x 20 light-alloy	

BMW X6 xDrive30d			
Transmission			
Type of transmission		Eight-speed Steptronic transmission	
Gear ratios	I	:1	5.501
	II	:1	3.520
	III	:1	2.200
	IV	:1	1.720
	V	:1	1.301
	VI	:1	1.000
	VII	:1	0.833
	VIII	:1	0.640
	R	:1	4.543
Final drive		:1	2.929
Performance			
Power-to-weight ratio (DIN)	kg/kW		10.1
Acceleration 0–100 km/h	s		6.1
Top speed	km/h		233
Off-road Characteristics			
Angle of approach/departure	°		25.1 / 21.7
Breakover angle	°		17.9
Ground clearance (unladen)	mm		216
Fording depth (at 7 km/h)	mm		500
BMW EfficientDynamics			
BMW EfficientDynamics standard features	48V mild hybrid technology, Brake Energy Regeneration with recuperation display, Automatic Start/Stop function, COMFORT and ECO PRO modes with coasting function, Proactive Driving Assistant, Optimum Shift Indicator, Electric Power Steering, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, efficiency-optimised all-wheel drive, differential with optimised warm-up behaviour, tyres with reduced rolling resistance, BMW Blue Performance technology with SCR catalytic converter		
Fuel Consumption ECE			
Combined (WLTP)	l/100		7.9 – 7.0
Combined (NEDC)	l/100		–
CO ₂ (WLTP)	g/km		208 – 184
CO ₂ (NEDC)	g/km		–
Emission rating			Euro 6d

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

¹⁾ Oil change

²⁾ Developed by the combination of the combustion engine (stated nominal figure) and the electric motor (up to stated nominal figure)


³⁾ Data not yet available

The fuel consumption, CO₂ emissions, electric power consumption and electric range figures are determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany and the range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment.

All values were calculated based on the new WLTP test cycle. WLTP values are taken as the basis for determining vehicle-related taxes or other duties based (at least inter alia) on CO₂ emissions as well as eligibility for any applicable vehicle-specific subsidies. Further information on the WLTP and NEDC measurement procedures can also be found at www.bmw.de/wltp.

Further information on official fuel consumption figures and specific CO₂ emission values of new passenger cars is included in the following guideline: 'Leitfaden über den Kraftstoffverbrauch, die CO₂-Emissionen und den Stromverbrauch neuer Personenkraftwagen' (Guide to the fuel economy, CO₂ emissions and electric power consumption of new passenger cars), which can be obtained free of charge from all dealerships, from Deutsche Automobil Treuhand GmbH (DAT), Hellmuth-Hirth-Str. 1, 73760 Ostfildern-Scharnhausen and at <https://www.dat.de/co2>.

Exterior and interior dimensions. BMW X6.



The dimensions indicated in the technical drawing are in millimetres and may vary depending on the model and the items of optional equipment fitted.