BMW Media Information

7/2011

Valid from 9/2011

Specifications. The new BMW 6 Series Coupé. 640i, 650i



		BMW 640i Coupe	BMW 650i Coupe		
Body		0.14	0.14		
Number of doors/seats		2/4	2/4		
Length/Width/Height (unladen)	mm	4894 / 1894 / 1369 2855	4894 / 1894 / 1369		
Wheelbase	mm		2855		
Track front/rear	mm	1600 / 1657	1600 / 1657		
Ground clearance	mm	124	124		
Turning circle	m	11.7	11.7		
Tank capacity	appr l	70	70		
Cooling system incl. heating		10.2 6.5	14.6 8.5		
Engine oil ¹⁾	<u> </u>	1660 / 1735	8.5 1770 / 1845		
Weight, unladen, to DIN/EU	kg	450	450		
Max. load to DIN	kg		2280		
Max. perm. weight, overall	kg	2180			
Max perm axle load front/rear	kg	1090 / 1180	1165 / 1220		
Max perm trailer load (12%) braked/unbraked	kg	·	-1-		
Perm roof load/trail download	kg	75 / –	75/-		
Luggage capacity	I	460	460		
Air resistance	cd x A	0.30 x 2.23	0.31 x 2.23		
Engine Configuration/No. of outs. hydroge		R/6/4	V90/8/4		
Configuration/No. of cyls. /valves Engine technology		BMW TwinPower Turbo with	BMW TwinPower Turbo		
Engine technology		Twin-Scroll turbocharger,	with two turbochargers		
		direct injection and fully variable	and direct injection		
		valve control (VALVETRONIC)	, ,		
Capacity	CC	2979	4395		
Stroke/bore	mm	89.6 / 84.0	88.3 / 89.0		
Compression ratio	:1	10.2	10.0		
Fuel grade		At least RON 91	At least RON 91		
Max output	kW/hp	235 / 320	300 / 407		
at	rpm	5800 – 6000	5500 - 6400		
Max torque	Nm	450	600		
at	rpm	1300 – 4500	1750 – 4500		
Electrical system					
Battery/installation	Ah/–	90 / luggage comp	105 / luggage comp		
Alternator	A/W	210 / 2940	220 / 3080		
Driving dynamics and safety					
Suspension, front		Double track control arm with separate lower track arm level,			
	aluminium, small steering roll radius, anti-dive				
Suspension, rear		Integral-V multi-arm axle, aluminium, with steering function, anti-squat and anti-dive, double acoustic separation			
Brakes, front		Single-piston aluminium floating-calliper disc brakes in frame structure			
Diameter	mm	348 x 30 / vented	374 x 36 / vented		
Brakes, rear			floating-calliper disc brakes		
Diameter	mm	345 x 24 / vented	345 x 24 / vented		
Driving stability systems			SC and DTC (Dynamic Traction		
		Control), CBC (Cornering E	Brake Control), ĎBC (Dynamic		
		,, ,	function, Fading Compensation,		
		<u> </u>	optional: Adaptive Drive		
Safety features Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear se three-point inertia-reel seatbelts on all seats with belt latch					
			ints at the front, crash sensors,		
		runflat tyres, Ty	re Defect Indicator		
Steering			ng (EPS) with Servotronic; ral Active Steering		
Overall steering transmission	:1	17.2	17.2		
Tyres front/rear		225/55 R17 97Y RSC	245/45 R18 96Y RSC		
Wheels front/rear		8J x 17 LM	8J x 18 LM		
- TOOLS HOHBICAL		OO A 17 LIVI	00 x 18 LIVI		

BMW Media Information

7/2011

Valid from 9/2011

Specifications. The new BMW 6 Series Coupé. 640i, 650i

			BMW 640i Coupe	BMW 650i Coupe		
BMW Connec	otodDrivo					
Comfort	cteuDrive		Optional: BMW Assist incl. Enquiry Service	, remote-control		
		functions, Real-Time Traffic Information, BMW TeleServices, integration of mobile devices				
Infotainment			, , ,			
motamment			Optional: Internet access, BMW Online incl. Park Info, National Info, Google Local Search, News, Realtime Weather,			
		BMW Routes, Office functions, Bluetooth Audio Streaming,				
0.1.		Online Update Music Tracks, Apps				
Safety		Optional: Adaptive Headlights with cornering lights, variable light distribution and adaptive headlight range control,				
		High Beam Assistant, Park Distance Control, rear-view camera,				
		Surround View incl. Top View and Side View, BMW Night Vision with				
			pedestrian recognition, Head-Up Display, P			
		Active Cruise Control including rear-end collision warning with braking function, Lane Change Warning, Lane Departure Warning,				
			Speed Limit Info, Automatic/Advanced En			
Transmission Type	n		Eight-speed automatic with Step	tronic		
Gear ratios	I	:1	4.714	4.714		
acai ratios	il i	:1	3.143	3.143		
	III	:1	2.106	2.106		
	IV	:1	1.667	1.667		
	V	:1	1.285	1.285		
	VI	:1	1.000	1.000		
	VII	:1	0.839	0.839		
	VIII	:1	0.667	0.667		
	R	:1	3.295	3.317		
Final drive		:1	3.231	3.077		
Performance	<u> </u>					
Power-to-weig	ht ratio	kg/kW	7.1	5.9		
Output per litre		kW/ltr	78.9	68.3		
Acceleration	0–100 km/h	S	5.4	4.9		
	0–1000 m	S	24.8	23.2		
In 4th gear Top speed	80–120 km/h	s km/h	250			
Top speed		NIII/II	250			
BMW Efficier						
BMW Efficient	•		Brake Energy Regeneration with recuperation dis function (BMW 640i), ECO PRO mode (BMW 640			
measures as st	tandard		construction, on-demand operation of ancillary			
			(BMW 640i), Electric Power Steering (EPS), detact			
			tyres with reduced rolling resist	ance		
Fuel consum	ntion El I ²⁾					
	wheels and tyres					
		5/55 R17 ty	res (SA 2K1), BMW 650i: 8J x 18 wheels, 245/45 R1	18 tyres (SA 2SR)		
Urban	,	I/100km	10.3	15.4		
Extra-urban		l/100km	6.0	7.7		
Composite		l/100km	7.6	10.5		
CO ₂		g/km	177	245		
	heels and 245/45		and with winter tyres (SA 2SR, 9WR, 931)			
Urban		I/100km	10.4			
Extra-urban		I/100km	6.1			
Composite		I/100km	7.7 179			
CO ₂	haala at frant O I	g/km	rear and 245/45 R18 tyres at front, 275/45 R18 at the	no roor (CA ODNI)		
	,		rear and 245/45 R18 tyres at front, 275/45 R18 at tr ne rear and 245/40 R19 tyres at front, 275/35 R19 at	'''		
			ne rear and 245/35 R20 tyres at front, 275/30 R20 at			
Urban		I/100km	10.5	15.5		
Extra-urban		I/100km	6.2	7.7		
Composite		l/100km	7.8	10.6		
CO ₂		g/km	181	246		
Emission class	ification		EU5	EU5		

Technical data valid for ACEA markets/part of data relevant to homologation only apply to Germany (weight)

 $^{^{1)}\,}$ Oil change quantity $^{2)}\,$ Fuel consumption and CO_2 emissions depend on the selected tyre format