BMW Media Information

8/2011

Valid from 9/2011

Specifications BMW X3. X3 xDrive20i



		BMW X3 xDrive20i
Body		
Number of doors/seats		5/5
Length/Width/Height (unladen)	mm	4648 / 1881 / 1661 ¹
Wheelbase	mm	2810
Track front/rear	mm	1616 / 1632
Turning cycle	m	11,9
Tank capacity	appr ltr	67
Cooling system incl. heating	ltr	7.5
Engine oil 2)	ltr	5.75
Weight, unladen, to DIN/EU	kg	1695 / 1770 (1705 / 1780)
Max. load to DIN	kg	590
Max. perm. weight, overall	kg	2285 (2295)
Max perm axle load front/rear	kg	1070 / 1290
Max perm trailer load (12 %) braked/unbraked	kg	2000 (2400) / 750
Perm roof load/trail download	kg	100 / 100
Luggage capacity	ltr	550–1600
Air resistance	cd x A	0.34 x 2.65
Engine		
Config/no of cyls/valves		R/4/4
Engine technology		BMW TwinPower Turbo with Twin-Scrol
		turbocharger, direct injection and fully variable valve control (VALVETRONIC)
Capacity	CC	1997
Stroke/bore	mm	90,1/84.0
Compression ratio	:1	11.0
Fuel grade		At least RON 91
Max output	kW/bhp	135 / 184
At rpm	rpm	5000
Torque	Nm	270
At rpm	rpm	1250–4500
Electrical system		
Battery/installation	Ah/-	90 / luggage comp
Alternator	A/W	210 / 2940
Aitemator	~~~	21072310
Driving dynamics and safety	<i>'</i>	D. H. Malana and A.
Suspension, front Suspension, rear		Double-joint tension-rod spring-strut suspension, anti-dive Five-link rear axle, spatial suspension with anti-squat and anti-dive
Brakes, front		Single-piston floating-caliper disc brakes
Diameter	mm	328 x 28 / vented
Brakes, rear		Single-piston floating-caliper disc brakes
Diameter	mm	330 x 20 / vented
Driving stability systems		Fitted as standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, rain brake support, fading compensation, hill-start assistant; DSC networked with xDrive four-wheel drive, HDC Hill Descent Control, optional: Dynamic Damper Control, Performance Control
Safety features		Fitted as standard: Airbags for driver and front seat passenger, side airbags for driver and front seat passenger, head airbags for the first and second seat row, crash-active headrests at the front, three-point automatic belts on all seats, on the front seats with pretensioners, belt-force limiters and belt stoppers, crash sensors, tyre defect indicator
Steering		EPS Electric Power Steering with Servotronic function, optional: variable sports steering
Overall steering transmission	:1	17,8
Tyres front/rear		225/60 R17 99 V
Wheels front/rear		7.5J x 17 LM

Valid from 9/2011





			BMW X3 xDrive20i
BMW Connect	tedDrive		
Comfort			Optional extras: BMW Assist featuring, inter alia, information service, remote functions, Real-Time Traffic Information, BMW TeleServices, integration of mobile devices
Infotainment			Optional extras: Internet access, BMW Online featuring, inter alia, parking info, country-relevant info, Google search by type of business, news, weather realtime, BMW Routes, office functions, Bluetooth audio streaming and online update of music tracks, Apps
Safety			Adaptive Cornering Headlights with variable light distribution and adaptive levelling, High-beam Assistant, Park Distance Control, reversing camera with Top View, Head-up Display, speed control with braking function, automatic/advanced emergency call
Transmission			
Type			6-speed manual (optional: 8-speed automatic with Steptronic)
Gear ratios	1	:1	4.110 (4.714)
	II	:1	2.315 (3.143)
	III	:1	1.542 (2.106
)	IV	:1	1.179 (1.667)
<u></u>	V	:1	1.000 (1.285)
	VI	:1	0.846 (1.000)
	VII	:1	- (0.839)
	VIII	:1	- (0.667)
	R	:1	3.727 (3.295)
Final Drive	11	:1	3.636 (3.385)
			()
Performance			40.0
Power-to-weigh	it ratio	kg/kW	12.6
Output per litre		kW/ltr	67.6
Acceleration	0–100 km/h	S	8.3 (8.6)
	0–1000 m	S	29.7 (30.1)
in 4th/5th gear	80–120 km/h	S	7.9 / 9.5 (–)
Top speed		km/h	210 (210)
Off-road chara	acteristics		
Overhang angle			
front/rear		0	25.7 / 22.6
Ramp angle		0	19.4
Ground-clearand	ce when	mm	212
Wading depth		mm	500
BMW Efficient	Dvnamics		
BMW EfficientD			Brake Energy Regeneration with recuperation display,
measures as sta	,		EPS (Electric Power Steering), Auto Start Stop function, gearshift point indicator (on manual gearbox model) demand-controlled ancillary components, map- controlled oil pump, intelligent lightweight construction, final drive with optimised warm-up behaviour
Final and the st	Films		
Fuel con in the Urban	e EU cycle	ltr/100	9.9 (8.9)
			9.9 (o.9) 6.7 (6.7)
Extra-urban		ltr/100	· · · · · · · · · · · · · · · · · · ·
Composite		ltr/100	7.9 (7.5)
CO ₂		g/km	184 (175)
Emission classif	ication		EU5

Technical data valid for ACEA markets/Part of registration-specific data only apply to Germany (weights, top speed) Figures in brackets apply to automatic transmission models

- Height without roof aerial: 1675 mm Oil filling quantity