BMW Media Information

9/2011

Valid from 9/2011

## Specifications BMW X1. X1 xDrive28i



		BMW X1 xDrive28i
Body		
No. of doors/seats		5/5
Length/width/height <sup>1)</sup> (unladen)		4454 / 1798 / 1545
Wheelbase	mm	2760
	mm	1500 / 1529
Track, front/rear	mm	13007/1328
Turning circle	m	
Tank capacity	approx. I	63
Cooling system incl heating		8.2 (8.5)
Engine oil <sup>2)</sup>		5.75
Weight, unladen, to DIN/EU Max load to DIN	kg	1580 (1595) / 1655 (1670) 550
	kg	
Max permissible weight	kg	2130 (2150)
Max axle load, front/rear	kg	1015 / 1175
Max trailer load, braked (12%)/unbraked	kg	2000 / 750
Max roof load/towbar download	kg	75 / 80
Luggage comp capacity		420 – 1350
Air drag	c <sub>X</sub> x A	0.34 x 2.34
Engine		
Configuration/No of cyls/valves		R/4/4
Engine technology		BMW TwinPower Turbo technology with twin-scroll charging, High Precision Injection direct petrol injection, Valvetronic fully variable valve control, double-VANOS fully variable camshaft control
Effective capacity	cm <sup>3</sup>	1997
Stroke/bore	mm	90.1 / 84.0
Compression ratio	:1	10.0
Fuel grade		min RON 91
Output	kW/hp	180 / 245
at	min <sup>-1</sup>	5000 - 6500
Torque	Nm	350
at	min <sup>-1</sup>	1250 – 4800
Electrical system		
Battery/Installation	Ah/-	80 (70) / luggage comp
Alternator	A/W	170 / 2380
Driving dynamics and safety	,	
Suspension, front		Double-joint spring-strut thrust bar axle
Suspension, rear		Five-arm axle with longitudinal control arm and double wishbone
Brakes, front		Single-piston frame calliper disc brakes
Diameter	mm	330 x 24 / vented
Brakes, rear		Single-piston swing calliper disc brakes
Diameter	mm	330 x 20 / vented
Driving stability systems		Standard: DSC incl ABS and DTC (Dynamic Traction Control), CBC (Cornering Brake Control), DBC Dynamic Brake Control), Dry Braking function, Fading Compensation, hill-start assistant, DSC integrated with xDrive all-wheel drive, HDC (Hill Descent Control); optional: Performance Control
Safety equipment		Standard: Airbags for driver and front passenger, side airbags for driver and front passenger, head airbags front and rear, three-point inertia-reel seatbelts on all seats with belt latch tensioner and belt force limiter in the front, crash sensors, Tyre Defect Indicator
Steering		Hydraulic rack-and-pinion power steering, optional: Servotronic
Steering ratio, overall	:1	18.5
Tyres, front/rear		225/50 R17 94H
. , ,		EE0/00 KT/ 5 III

Valid from 9/2011



## **Specifications BMW X1.**

			BMW X1 xDrive28i			
BMW Connect	tedDrive					
Comfort		Optional: BMW Assist incl inter alia Enquiry Service, remote-control functions Real-Time Traffic Information, BMW TeleServices, integration of mobile device				
Infotainment		Optional: internet access, BMW Online incl inter alia Park Info, National Info, Google Local Search, News, Realtime Weather, BMW Routes, Office functions, Bluetooth Audio Streaming, Online Update Music Tracks, Apps				
Safety		Optional: Adaptive Headlights with cornering lights, High-Beam Assistant, Park Distance Control, rear-view camera, Cruise Control with braking function, Automatic/Advanced Emergency Call				
Transmission						
Type of gearbox	(	Six-speed manual (optional: eight-speed automatic with Steptronic)				
Gear ratios	I	:1	4.110 (4.714)			
	II	:1	2.315 (3.143)			
	III	:1	1.542 (2.106)			
	IV	:1	1.179 (1.667)			
	V	:1	1.000 (1.285)			
	VI	:1	0.846 (1.000)			
	VII	:1	- (0.839)			
	VIII	:1	- (0.667)			
	R	:1	3.727 (3.295)			
Final drive		:1	3.385 (3.154)			
Performance						
Power-to-weigh	t ratio	kg/kW	8.8 (8.9)			
Output per litre	0.4001 #	kW/l	90.1			
Acceleration	0–100 km/h	S	6.1 (6.5)			
. 411-7511	0–1000 m	S	26.4 (26.8)			
in 4th/5th gear	80–120	S	6.0 / 7.1 (- / -)			
Top speed		km/h	240 (240)			
Offroad specif						
Overhang angle front/rear	,	0	18.0/21.5			
Ramp angle		0	16.8			
Ground clearance	re unladen	mm	194			
around clearance	be unlauen	111111	13-			
<b>BMW Efficient</b>						
BMW EfficientD			Brake Energy Regeneration, Optimum Shift Indicator and Auto Start-Stop			
standard feature	es		function (manual gearbox), on-demand operation of ancillary units, final drive with optimised warm-up running qualities, intelligent lightweight design, detachable a/c compressor, map-controlled oil pump			
Fuel consump	tion FIJ					
Urban	don LO	l/100 km	9.9 (10.4)			
Extra-urban		I/100 km	6.7 (6.4)			
Combined		I/100 km	7.9 (7.9)			
CO <sub>2</sub>		g/km	183 (183)			
Emission rating		gnan	EU5			

Specifications apply to ACEA markets; data relevant to homologation applicable in part only to Germany (weights, top speed) Figures in brackets apply to automatic transmission

- Height including roof antenna: 1573 mm Oil change