## BMW Media Information

1/2012

Valid from 3/2012

## Specifications. BMW M550d xDrive Sedan.



		BMW M550d xDrive Sedan
Body		
No. of doors/seats		4/5
Length/width/height <sup>1)</sup> (unladen)	mm	4910 / 1860 / 1454
Wheelbase	mm	2968
Track, front/rear	mm	1594 / 1599
Ground clearance	mm	131
Turning circle	m	11.95
Tank capacity	approx. I	70
Cooling system incl heating	1	12.6
Engine oil <sup>2)</sup>		6.5
Weight, unladen, to DIN/EU	kg	1895 / 1970
Max load to DIN	kg	580
Max permissible weight	kg	2475
Max axle load, front/rear	kg	1240 / 1330
Max trailer load,	kg	
braked (12%)/unbraked	9	2000 / 750
Max roof load/towbar download	kg	100/90
Luggage comp capacity	Ī	520
Air drag	c <sub>d</sub> x A	0.31 x 2.35
<b>—</b>		
Engine Configuration/No of autobrohype		5/2/
Configuration/No of cyls/valves		R/6/4
Engine technology		M Performance TwinPower Turbo technology with three turbochargers, multi-stage charging
		and variable turbine geometry, common-rail
		direct injection (max pressure: 2200 bar)
Effective capacity	cm <sup>3</sup>	2993
Bore/stroke	mm	90.0 / 84.0
Compression ratio	:1	16.0
Fuel grade		diesel
Output	kW/hp	280 / 381
at	min <sup>-1</sup>	4000 – 4400
Torque	Nm	740
at	min <sup>-1</sup>	2000 – 3000
Electrical system		
Battery/Installation	Ah/-	90 / luggage comp
Alternator	A/W	220 / 3080
Duiving dynamics and sefety		
Driving dynamics and safety		Double treel, central arm with concrete lever treel, arm level aluminium
Suspension, front		Double track control arm with separate lower track arm level, aluminium, M-specific damping and suspension tuning, small steering roll radius, anti-dive
Suspension, rear		Integral-V multi-arm axle, aluminium, double acoustic separation,
		M-specific damping and suspension tuning, with anti-dive
		and anti-squat
Brakes, front		Single-piston aluminium floating-calliper disc brakes in frame structure
Diameter	mm	374 x 36 / vented
Brakes, rear		Single-piston aluminium floating-calliper disc brakes
Diameter	mm	345 x 24 / vented
Driving stability systems	S	Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering Brake Control), DBC (Dynamic Brake Control), Dry Braking function, Fading Compensation, Start-Off Assistant, DSC and xDrive all-wheel drive linked through ICM (Integrated Chassis Management); optional: Dynamic Damper Control, Adaptive Drive
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia-reel seatbelts on all seats with belt latch tensioner and belt force limiter at the front, crash-activated head restraints at the front, crash sensors, runflat tyres, Tyre Defect Indicator
Steering		Hydraulic rack-and-pinion steering with M-specific Servotronic function
Steering ratio, overall	:1	17.9
Tyres, front/rear		245/40 R19 94Y 275/35 R19 96Y
Rims, front/rear		8.5J x 19 LM
		9J x 19 LM

## **BMW** Media Information

1/2012

Valid from 3/2012

## Specifications.

			BMW M550d xDrive Sedan
BMW Connec	tedDrive		
Convenience	teabilive		Optional: BMW Assist incl. Enquiry Service, remote-control functions, Real-Time Traffic Information, BMW TeleServices, integration of mobile devices
Infotainment			Optional: internet access, BMW Online incl. Park Info, National Info, Google Local Search, News, Realtime Weather, BMW Routes, Office functions, Bluetooth Audio Streaming, Online Update Music Tracks, Apps
Safety			Optional: Adaptive Headlights with cornering lights, variable light distribution and adaptive headlight range control, High Beam Assistant, Park Distance Control, rear-view camera, Surround View including Side View nd Top View, BMW Night Vision with pedestrian recognition, Head-Up Display, ollision warning with braking function in conjunction with Active Cruise Control with Stop & Go function, Lane Change Warning, Lane Departure Warning, Speed Limit Info, Active Protection, Automatic/Advanced Emergency Call
Transmission			
Type of gearbox			Eight-speed automatic with Steptronic
Gear ratios	I	:1	4.714
	II	:1	3.143
	III	:1	2.106
	IV	:1	1.667
	V	:1	1.285
	VI	:1	1.000
	VII	:1	0.839
	VIII	:1	0.667
	R	:1	3.317
Final drive		:1	2.813
Performance			
Power-to-weigh	nt ratio (DIN)	kg/kW	6.8
Output per litre		kW/l	93.6
Acceleration	0–100 km/h	S	4.7
	0–1000 m	S	23.7
in 4 <sup>th</sup> /5th gear	80–120	S	-1-
Top speed		km/h	250
BMW Efficien			
BMW EfficientE standard feature	,	A	Brake Energy Regeneration with recuperation display, Auto Start-Stop function, ECO PRO mode, intelligent lightweight construction, on-demand operation of ancillary units, detachable a/c compressor, BMW BluePerformance technology
Fuel economic	tion EU		
Fuel consump			
Urban	1100	l/100km	7.1
Extra-urban		1/100km	5.8
Combined		1/100km	6.3
CO <sub>2</sub>		g/km	165
Emission rating		gmii	EU6
Litiosion rating			LOU

Specifications apply to ACEA markets; data relevant to homologation applicable in part only to Germany (weight)

Height including roof fin: 1465 millimetres
 Oil change