BMW Media Information

3/2012

Valid from 4/2012

Specifications BMW X6. X6 xDrive35i, X6 xDrive50i



		BMW X6 xDrive35i	BMW X6 xDrive50i	
Body				
No of doors/seats		5 / 4 (5) 1)	5 / 4 (5) 1)	
Length/width/height (unladen)	mm	4877 / 1983 / 1699 ²⁾	4877 / 1983 / 1699 ²⁾	
Wheelbase	mm	2933	2933	
Track, front/rear	mm	1644 / 1706	1644 / 1706	
Turning circle	m	12.8	12.8	
Tank capacity	app ltr	85	85	
Cooling system incl heater	Itr	10.9	17.2	
Engine oil 3)	ltr	6.5	8.5	
Weight, unladen, to DIN/EU	kg	2070 / 2145	2190 / 2265	
Max load to DIN	kg	600 (650) 4)	600 (650) 4)	
Max permissible	kg	2670 (2720) ⁴⁾	2790 (2840) ⁴⁾	
Max axle load, front/rear		1275 / 1475	1375 / 1490	
	kg	(1275 / 1515) 4)	(1375 / 1530) 4)	
Max trailer load (12%),	kg		5)	
braked/unbraked		2700 (3500) ⁵⁾ / 750	2700 (3500) ⁵⁾ / 750	
Max roofload/max towbar downl	kg	100 / 120 (140) ⁵⁾	100 / 120 (140) ⁵⁾	
Luggage comp capacity	ltr	570-1450	570-1450	
Air drag	Cd x A	0.34 x 2.82	0.36 x 2.82	
Engine				
Config/No of cyls/valves		In-line / 6 / 4	V/8/4	
Engine technology		BMW TwinPower Turbo	BMW TwinPower Turbo	
		with Twin-Scroll	with two turbochargers	
		turbocharger,	an direct injection (High	
		direct injection and fully variable valve control	Precision Injection)	
		(VALVETRONIC)		
O		2979	4395	
Capacity, effective	CC	89.6 / 84.0	88.3 / 89.0	
Stroke / bore	mm			
Compression ratio	:1	10.2	10.0	
Fuel	13477	min ROZ 91	min ROZ 91	
Max output	kW/hp	225 / 306	300 / 407	
at	rpm	5800	5500-6400	
Max torque	Nm/lb-ft	400	600	
at	rpm	1200-5000	1750-4500	
Electrical System		22.11		
Battery/location	Ah/–	90 / luggage comp	90 / luggage comp	
Alternator	A/W	210 / 2940	220 / 3080	
Driving Dynamics and Safety	/			
Suspension, front			axle, small steering roll radius, anti-dive	
Suspension, rear	Integral-IV multi-arm axle, anti-squat and anti-dive, optional: air suspension with automatic self-levelling			
Brakes, front		Single-piston floating- calliper disc brakes	Double-piston floating- calliper disc brakes	
Diameter	mm	348 x 30 / vented	385 x 36 / vented	
Brakes, rear		Single-pis	ston floating-calliper disc brakes	
Diameter	mm	320 x 20 / vented	345 x 24 / vented	
Driving stability systems			d DTC Dynamic Traction Control, CBC Cornering	
		Compensation, Start-Off A	Dynamic Brake Control, Dry Braking, Fading Assistant, DSC cross-linked with xDrive, Dynamic I descent control HDC, optional: Adaptive Drive	
Safety equipment	Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags front and rear, active headrests at the front, three-point inertia-reel seat belts on all seats, belt latch tensioners at the front, crash sensors, roll-over sensors, Tyre Defect Indicator			
Steering	Hydraulic rack-and-pinion power steering with servotronic function, optional: Active steering			
Steering transmission, overall	:1	19.5	19.5	
Tyres, front/rear	2	255/50 R19 107V XL RSC	255/50 R19 107W XL RSC	
Rims, front/rear		9J x 19 LM	9J x 19 LM	

BMW Media

Information

3/2012

Valid from 4/2012

Specifications BMW X6.

		BMW X6 xDrive35i	BMW X6 xDrive50i		
BMW ConnectedDrive					
Comfort		Opt. BMW Assist including Enquiry Se	rvice, remote-control function, Real-		
		Time Traffic Information, BMW TeleSe			
Infotainment	Opt: Internet, BMW Online incl Parkinfo, National Info, Google Local Search, News, Realtime Weather, BMW Routes, Office Functions, Bluetooth Audio Streaming, Online Update Music Tracks, Apps				
Safety	Т	Opt: Adaptive Headlights with Bendin ligh-Beam Assistant, Park Distance Co op View, BMW Head-Up Display, Active Departure Warning, Speed Limit Info, A	ntrol, Side View, back-up camera with e Cruise Control with Stop & Go, Lane		
Transmission					
Type of transmission		Eight-speed automati Steptronic function a			
Gear ratios I	:1	4.714	4.714		
	:1	3.143	3.143		
	:1	2.106	2.106		
IV	:1	1.667	1.667		
V	:1	1.285	1.285		
VI	:1	1.000	1.000		
VII	:1	0.839	0.839		
VIII	:1	0.667	0.667		
R	:1	3.295	3.317		
Final drive	:1	3.154	3.154		
Performance					
Power-to-weight ratio (DIN)	kg/kW	9.2	7.3		
Output per litre	kW/hp	75.5	68.3		
Acceleration 0-100 km/h	sec	6.7	5.4		
Standing-start	sec	27.2	24.6		
Top speed	km/h	240	250		
Offroad characteristics					
Overhang angle	0	05.4.105.5	05.4.405.5		
front / rear	0	25.1 / 25.5	25.1 / 25.5		
Ramp breakover angle		19.1	19.1		
Ground cleerance	mm	212	212		
BMW EfficientDynamics					
BMW EfficientDynamics		Brake Energy Regeneration, on-de			
standard features		map-controlled oil pump (BMW X6 technology, air flap control (BMW X6 xI tyres with reduce	Orive35i), a/c compressor detachable,		
Fuel Consumption in EU Cy	vcle				
Urban	Itr/100 km	13.2	17.5		
		8.3	9.6		
	ITT/ [()() KM				
Extra-urban Combined	ltr/100 km	10.1	12.5		
Extra-urban					

Specifications applicable to ACEA markets/homologation data applicable in part only to Germany (weights, top speed)

- With optional third seat in rear
 Height without roof antenna: 1690 mm
 Oil change
 With Adaptive Drive and / or levelling system with air suspension
 With option extended trailer load in combination with levelling system incl. air suspension