## BMW Media Information

2/2012

Valid from 3/2012

## Specifications BMW X3. X3 xDrive30d, X3 xDrive35d



		BMW X3 xDrive30d	BMW X3 xDrive35d	
Body		5/5	5/5	
Number of doors/seats		4648 / 1881 / 1661 1)	4648 / 1881 / 1661 1	
Length/Width/Height (unladen)	mm	2810	2810	
Wheelbase	mm	1616 / 1632		
Track front/rear	mm	11.9	11.9	
Turning cycle	m		67	
Tank capacity	appr ltr	67		
Cooling system incl. heating	ltr.	7.2	12.0 7.2	
Engine oil 2) Weight, unladen, to DIN/EU	ltr	1800 / 1875	1850 / 1925	
	kg	590	590	
Max. load to DIN	kg	2390	2440	
Max. perm. weight, overall	kg	1140 / 1320	1160 / 1320	
Max perm axle load front/rear	kg	114071320	110071320	
Max perm trailer load (12 %) braked/unbraked	kg	2400 / 750	2400 / 750	
	l.a	100 / 100	100 / 100	
Perm roof load/trail download	kg	550–1600	550–1600	
Luggage capacity	ltr	0.34 x 2.65	0.35 x 2.65	
<u>Air resistance</u>	cd x A	0.34 X 2.03	0.53 x 2.05	
Engine				
Config/no of cyls/valves		R/6/4	R/6/4	
Engine technology		BMW TwinPower Turbo:	BMW TwinPower Turbo:	
		Turbocharger with variable intake geometry,	Two turbochargers (Variable Twin Turbo),	
		Common Rail direct	Common Rail direct	
		injection with solenoid	injection with solenoid	
		valve injectors (max.	valve injectors (max.	
		injection pressure:	injection pressure:	
		1800 bar)	2000 bar)	
Capacity	CC	2993	2993	
Stroke/bore	mm	90.0 / 84.0	90.0 / 84.0	
Compression ratio	:1	16.5	16.5	
Fuel grade		Diesel	Diesel	
Max output	kW/bhp	190 / 258	230 / 313	
At rpm	rpm	4000	4400	
Torque	Nm	560	630	
At rpm	rpm	1500-3000	1500-2500	
Electrical system				
Battery/installation	Ah/-	80 / luggage comp	90 / luggage comp	
Alternator	A/W	210 / 2940	210 / 2940	
Driving dynamics and safety	,			
Suspension, front		Double-ioint tens	ion-rod spring-strut suspension, anti-dive	
Suspension, rear			rear axle, spatial suspension with	
Suspension, real		1 100 11110	anti-squat and anti-dive	
Brakes, front		Single-p	iston floating-caliper disc brakes	
Diameter	mm	328 x 28 / vented	356 x 30 / vented	
Brakes, rear			siston floating-caliper disc brakes	
Diameter	mm	330 x 20 / vented	330 x 20 / vented	
Driving stability systems			cl. ABS and DTC (Dynamic Traction Control), CBC	
Driving dtability dydtorno			DBC Dynamic Brake Control, rain brake support,	
	fading compensation, hill-start assistant; DSC networked with xDrive four-			
			drive, HDC Hill Descent Control,	
			ic Damper Control, Performance Control	
Safety features			for driver and front seat passenger, side airbags for	
			nger, head airbags for the first and second seat row,	
			ne front, three-point automatic belts on all seats, on sioners, belt-force limiters and belt stoppers, crash	
			nsors, tyre defect indicator	
Steering			ower Steering with Servotronic function,	
C.C.C.IIIIg			onal: variable sports steering	
Overall steering transmission	:1	17.8	17.8	
Tyres front/rear		225/60 R17 99 V	245/50 R18 100 W	
Wheels front/rear		7.5J x 17 LM	8J x 18 LM	
vincelo irontiredi		7.30 × 17 LIVI	00 x 10 EW	

Valid from 3/2012

## **Specifications BMW X3.**



			BMW X3 xDrive30d	BMW X3 xDrive35d		
BMW Connec	tedDrive					
Comfort	teabilite	Optional extras: BMW Assist featuring, inter alia, information service, remote functions, Real-Time Traffic Information, BMW TeleServices, integration of mobile devices				
Infotainment		Optional extras: Internet access, BMW Online featuring, inter alia, parking info, country-relevant info, Google search by type of business, news, weather realtime, BMW Routes, office functions, Bluetooth audio streaming and online update of music tracks, Apps				
Safety		Adaptive Cornering Headlights with variable light distribution and adaptive levelling, High-beam Assistant, Park Distance Control, reversing camera with Top View, Head-up Display, speed control with braking function, Lane Departure Warning with Collision Warning, speed limit and no passing information, automatic/advanced emergency call				
Transmission						
Type			8-speed automatic transmission	on with Steptronic		
Gear ratios	ı	:1	4.714	4.714		
	<u> </u>	:1	3.143	3.143		
	ill	:1	2.106	2.106		
	IV	:1	1.667	1,667		
	V	:1	1.285	1.285		
	VI	:1	1.000	1.000		
	VII	:1	0.839	0.839		
	VIII	:1	0.667	0.667		
	R	:1	3.317	3.317		
Final Drive		:1	2.813	2.813		
Performance						
Power-to-weigh	nt ratio (DIN)	kg/kW	9.5	8.0		
Output per litre		kW/ltr	63.5	76.8		
Acceleration	0-100 km/h	S	6.2	5.8		
	0–1000 m	S	26.5	25.5		
in 4th/5th gear	80-120 km/h	S	-	-		
Top speed		km/h	230	244		
Off-road char	acteristics					
Overhang angle front/rear	)	0	25.7 / 22.6	25.7 / 22.6		
Ramp angle		0	19.4	19.4		
Ground-clearan	co whon	mm	212	212		
Wading depth	ce when	mm	500	500		
BMW Efficien	tDvnamics					
BMW Efficient			Brake Energy Regeneration wit	h recuperation display,		
measures as sta	•		EPS (Electric Power Steering), Auto Start demand-controlled ancillary components, i final drive with optimised w	Stop function, ECO PRO mode, ntelligent lightweight construction,		
Fuel consump	ntion (FII)					
Urban		ltr/100	6.8	6.7		
Extra-urban		Itr/100	5.6	5.8		
Composite		Itr/100	6.0	6.1		
COmposite CO <sub>2</sub>		g/km	159	162		
Emission classif	fication	giniii	EU5	EU5		
Emission classif	IICatiOH		LUJ	E03		

Technical data valid for ACEA markets/Part of registration-specific data only apply to Germany (weights, top speed)

- Height without roof aerial: 1675 mm Oil filling quantity