



Specifications.

MINI Cooper Countryman.

MINI Cooper Countryman Automatic.

Body		MINI Cooper Countryman	MINI Cooper Countryman Automatic
No of doors / seats		5 / 4 (5)	5 / 4 (5)
Length / width / height (unladen)	mm	4097 / 1789 / 1561	4097 / 1789 / 1561
Wheelbase	mm	2595	2595
Track, front / rear	mm	1534 / 1559	1534 / 1559
Turning circle	m	11.6	11.6
Tank capacity	approx. l	47	47
Cooling system incl. heater	l	5.5	6.0
Engine oil	l	4.2	4.2
Transmission oil incl. drive train	l	Lifetime	Lifetime
Weight, unladen to DIN / EU ¹⁾	kg	1265 / 1340	1295 / 1370
Max load to DIN	kg	470	470
Max permissible load to DIN	kg	1735	1765
Max axle load, front / rear	kg	930 / 855	960 / 855
Max trailer load ²⁾ braked (12%) / unbraked	kg	- / -	1000 / 500
Max roofload / max download	kg	75 / -	75 / 75
Luggage comp to DIN	l	350 / 450 / 1170	350 / 450 / 1170
Air drag c _x / A / c _x × A	- / m ² / m ²	0.35 / 2.36 / 0.83	0.35 / 2.36 / 0.83
Engine			
Config / No of cyls / valves		Inline / 4 / 4	Inline / 4 / 4
Engine management		MEV 17.2.2	MEV 17.2.2
Capacity	cm ³	1598	1598
Bore / stroke	mm	77 / 85.8	77 / 85.8
Compression ratio	:1	11.0	11.0
Fuel grade	RON	91-98	91-98
Max output	kW / PS	90 / 122	90 / 122
At	min ⁻¹	6000	6000
Max torque	Nm	160	160
At	min ⁻¹	4250	4250
Electrical System			
Battery / installation	Ah / -	60 / Engine compartment	55 / Engine compartment
Alternator	A	150	120
Chassis			
Suspension, front		Single-joint MacPherson spring strut axle with anti-dive control	
Suspension, rear		Multi-link axle with longitudinal struts in lightweight aluminium design	
Front brakes		Vented disc	Vented disc
Diameter	mm	294 × 22	294 × 22
Rear brakes		Disc	Disc
Diameter	mm	280 × 10	280 × 10
Driving stability systems		Hydraulic two-circuit brake system with anti-lock brakes (ABS), Electronic Brake Force Distribution (EBD) and Cornering Brake Control (CBC), Dynamic Stability Control (DSC) with Brake Assist and Hill Start Assistant, optional: Dynamic Traction Control (DTC) and Electronic Differential Lock Control (EDLC). Parking brake acts mechanically on rear wheels	
Steering		Electric power steering (EPS); 2.4 rotations in total	
Steering transmission, overall	:1	14.1	14.1
Tyres		205/60 R16 92H	205/60 R16 92H
Wheels		6.5J × 16 LM	6.5J × 16 LM
Transmission			
Type of gearbox		6-gear manual transmission	6-speed automatic transmission
Gear ratios	I	:1	3.214
	II	:1	1.792
	III	:1	1.194
	IV	:1	0.914
	V	:1	0.784
	VI	:1	0.683
Reverse gear	:1	3.143	3.394
Final drive ratio	:1	4.722	4.643
Performance			
Power-to-weight ratio to DIN	kg/kW	14.1	14.4
Output per litre	kW/l	56.3	56.3
Acceleration	0-100 km/h	s	10.5
	0-1000 m	s	32.2
In 4 th / 5 th gear	80-120 km/h	s	11.6 / 14.9
Top speed	km/h	190	182
Fuel Consumption in EU Cycle			
Urban	l/100 km	7.4	9.3
Extra-urban	l/100 km	5.2	6.0
Composite	l/100 km	6.0	7.2
CO ₂	g/km	140	168
Miscellaneous			
Emission rating		EU5	EU5
Ground clearance	mm	149	149

Specifications apply to ACEA markets / data relevant to homologation applicable in part only to Germany (weight)

¹⁾ Weight of the car in road trim (DIN) plus 75 kg for driver and luggage.

²⁾ Deviations are possible under certain circumstances.