



Specifications.

MINI Cooper S Countryman.

MINI Cooper S Countryman Automatic.

Body		MINI Cooper S Countryman	MINI Cooper S Countryman Automatic
No of doors / seats		5 / 4 (5)	5 / 4 (5)
Length / width / height (unladen)	mm	4110 / 1789 / 1561	4110 / 1789 / 1561
Wheelbase	mm	2595	2595
Track, front / rear	mm	1525 / 1551	1525 / 1551
Turning circle	m	11.6	11.6
Tank capacity	approx. l	47	47
Cooling system incl. heater	l	5.5	6.0
Engine oil	l	4.2	4.2
Transmission oil incl. drive train	l	Lifetime	Lifetime
Weight, unladen to DIN / EU ¹⁾	kg	1310 / 1385	1335 / 1410
Max load to DIN	kg	470	470
Max permissible load to DIN	kg	1780	1805
Max axle load, front / rear	kg	960 / 855	980 / 855
Max trailer load ²⁾ braked (12%) / unbraked	kg	750 / 500	1000 / 500
Max roofload / max download	kg	75 / 75	75 / 75
Luggage comp to DIN	l	350 / 450 / 1170	350 / 450 / 1170
Air drag c_x / A / $c_x \times A$	– / m ² / m ²	0.36 / 2.36 / 0.85	0.36 / 2.35 / 0.85
Engine			
Config / No of cyls / valves		Inline / 4 / 4	Inline / 4 / 4
Engine management		MEVD 17.2.2	MEVD 17.2.2
Capacity	cm ³	1598	1598
Bore / stroke	mm	77.0 / 85.8	77.0 / 85.8
Compression ratio	:1	10.5	10.5
Fuel grade	RON	91–98	91–98
Max output	kW / PS	135 / 184	135 / 184
At	min ^{–1}	5500	5500
Max torque	Nm	240 (260)	240 (260)
At	min ^{–1}	1600–5000 (1700–4500)	1600–5000 (1700–4500)
Electrical System			
Battery / installation	Ah / –	60 / Engine compartment	55 / Engine compartment
Alternator	A	150	120
Chassis			
Suspension, front		Single-joint MacPherson spring strut axle with anti-dive control	
Suspension, rear		Multi-link axle with longitudinal struts in lightweight aluminium design	
Front brakes		Vented disc	Vented disc
Diameter	mm	307 × 24	307 × 24
Rear brakes		Disc	Disc
Diameter	mm	280 × 10	280 × 10
Driving stability systems		Hydraulic two-circuit brake system with anti-lock brakes (ABS), Electronic Brake Force Distribution (EBD) and Cornering Brake Control (CBC), Dynamic Stability Control (DSC) with Brake Assist and Hill Start Assistant, optional: Dynamic Traction Control (DTC) and Electronic Differential Lock Control (EDLC). Parking brake acts mechanically on rear wheels	
Steering		Electric power steering (EPS); 2.4 rotations in total	
Steering transmission, overall	:1	14.1	14.1
Tyres		205/55 R17 91V RSC	205/55 R17 91V RSC
Wheels		7J × 17 LM	7J × 17 LM
Transmission			
Type of gearbox		6-gear manual transmission	6-speed automatic transmission
Gear ratios	I	:1	3.308
	II	:1	2.130
	III	:1	1.483
	IV	:1	1.139
	V	:1	0.949
	VI	:1	0.816
Reverse gear	:1	3.231	3.193
Final drive ratio	:1	3.706	3.683
Performance			
Power-to-weight ratio to DIN	kg/kW	9.7	9.9
Output per litre	kW/l	84.5	84.5
Acceleration	0–100 km/h	s	7.6
	0–1000 m	s	28.2
In 4 th / 5 th gear	80–120 km/h	s	7.1 / 8.6
Top speed	km/h	215	210
Fuel Consumption in EU Cycle			
Urban	l/100 km	7.5	9.5
Extra-urban	l/100 km	5.4	5.7
Composite	l/100 km	6.1	7.1
CO ₂	g/km	143	166
Miscellaneous			
Emission rating		EU5	EU5
Ground clearance	mm	149	149

Specifications apply to ACEA markets / data relevant to homologation applicable in part only to Germany (weight)

¹⁾ Weight of the car in road trim (DIN) plus 75 kg for driver and luggage.

²⁾ Deviations are possible under certain circumstances.