



Specifications.

MINI Cooper SD Countryman.

MINI Cooper SD Countryman Automatic.

Body	MINI Cooper SD Countryman	MINI Cooper SD Countryman Automatic
No of doors / seats	5 / 4 (5)	5 / 4 (5)
Length / width / height (unladen)	4110 / 1789 / 1561	4110 / 1789 / 1561
Wheelbase	2595	2595
Track, front / rear	1525 / 1551	1525 / 1551
Turning circle	11.6	11.6
Tank capacity	47	47
Cooling system incl. heater	5.2	5.2
Engine oil	5.2	5.2
Transmission oil incl. drive train	Lifetime	Lifetime
Weight, unladen to DIN / EU ¹⁾	1320 / 1395	1345 / 1420
Max load to DIN	470	470
Max permissible load to DIN	1790	1815
Max axle load, front / rear	995 / 855	1015 / 855
Max trailer load ²⁾		
braked (12%) / unbraked	800 / 500	1200 / 500
Max roofload / max download	75 / 75	75 / 75
Luggage comp to DIN	350 / 450 / 1170	350 / 450 / 1170
Air drag c_x / A / $c_x \times A$	0.35 / 2.36 / 0.83	0.35 / 2.36 / 0.83
Engine		
Config / No of cyls / valves	Inline / 4 / 4	Inline / 4 / 4
Engine management	MEVD 7.01	MEVD 7.01
Capacity	1995	1995
Bore / stroke	84 / 90	84 / 90
Compression ratio	16.5	16.5
Fuel grade	RON	Diesel
Max output	105 / 143	105 / 143
At	4000	4000
Max torque	305	305
At	1750–2700	1750–2700
Electrical System		
Battery / installation	Ah / –	70 / Engine compartment
Alternator	A	150
Chassis		
Suspension, front	Single-joint MacPherson spring strut axle with anti-dive control	
Suspension, rear	Multi-link axle with longitudinal struts in lightweight aluminium design	
Front brakes	Vented disc	
Diameter	294 × 22	294 × 22
Rear brakes	Disc	
Diameter	280 × 10	280 × 10
Driving stability systems	Hydraulic two-circuit brake system with anti-lock brakes (ABS), Electronic Brake Force Distribution (EBD) and Cornering Brake Control (CBC), Dynamic Stability Control (DSC) with Brake Assist, Hill Start Assistant, Dynamic Traction Control (DTC) and Electronic Differential Lock Control (EDLC). Parking brake acts mechanically on rear wheels	
Steering	Electric power steering (EPS); 2.4 rotations in total	
Steering transmission, overall	:1	14.1
Tyres	205/55 R17 91V RSC	205/55 R17 91V RSC
Wheels	7J × 17 LM	7J × 17 LM
Transmission		
Type of gearbox	6-gear manual transmission	6-speed automatic transmission
Gear ratios	I :1	2.308
II	:1	2.130
III	:1	1.483
IV	:1	1.139
V	:1	0.949
VI	:1	0.816
Reverse gear	:1	3.231
Final drive ratio	:1	3.706
Performance		
Power-to-weight ratio to DIN	kg/kW	12.6
Output per litre	kW/l	52.6
Acceleration	0– 100 km/h	9.3
0– 1000 m	s	30.5
In 4 th / 5 th gear	80– 120 km/h	10.1
Top speed	km/h	198
Fuel Consumption in EU Cycle		
Urban	l/100 km	5.2
Extra-urban	l/100 km	4.3
Composite	l/100 km	4.6
CO ₂	g/km	122
Miscellaneous		
Emission rating	EU5	EU5
Ground clearance	mm	149

Specifications apply to ACEA markets / data relevant to homologation applicable in part only to Germany (weight)

¹⁾ Weight of the car in road trim (DIN) plus 75 kg for driver and luggage.

²⁾ Deviations are possible under certain circumstances.