



Specifications.

MINI Cooper SD Coupé.

MINI Cooper SD Coupé Automatic.

Body		MINI Cooper SD Coupé	MINI Cooper SD Coupé Automatic
No of doors / seats		2 / 2	2 / 2
Length / width / height (unladen)	mm	3734 / 1683 / 1384	3734 / 1683 / 1384
Wheelbase	mm	2467	2467
Track, front / rear	mm	1453 / 1461	1453 / 1461
Turning circle	m	10.7	10.7
Tank capacity	approx. l	40	40
Cooling system incl. heater	l	6.6	7.0
Engine oil	l	5.2	5.2
Transmission oil incl. drive train	l	Lifetime	Lifetime
Weight, unladen to DIN / EU ¹⁾	kg	1175 / 1250	1195 / 1270
Max load to DIN	kg	290	290
Max permissible load to DIN	kg	1465	1485
Max axle load, front / rear	kg	890 / 600	905 / 600
Max trailer load braked (12%) / unbraked	kg	- / -	- / -
Max roofload / max download	kg	- / -	- / -
Luggage comp to DIN	l	280	280
Air drag c _x / A / c _x × A	- / m ² / m ²	0.35 / 1.98 / 0.69	0.35 / 1.98 / 0.69
Engine			
Config / No of cyls / valves		Inline / 4 / 4	Inline / 4 / 4
Engine management		DDE 7.2.1	DDE 7.2.1
Capacity	cm ³	1995	1995
Bore / stroke	mm	84.0 / 90.0	84.0 / 90.0
Compression ratio	:1	16.5	16.5
Fuel grade	RON	Diesel	Diesel
Max output	kW / hp	105 / 143	105 / 143
At	min ⁻¹	4000	4000
Max torque	Nm	305	305
At	min ⁻¹	1750-2700	1750-2700
Electrical System			
Battery / installation	Ah / -	70 / Engine compartment	70 / Engine compartment
Alternator	A	150	150
Chassis			
Suspension, front		Single-joint MacPherson spring strut axle with anti-dive control	
Suspension, rear		Multi-link axle with aluminium longitudinal struts and centrally-pivoted control arms	
Front brakes		Vented disc	Vented disc
Diameter	mm	²⁾	²⁾
Rear brakes		Disc	Disc
Diameter	mm	²⁾	²⁾
Driving stability systems		Hydraulic two-circuit brake system with anti-lock brakes (ABS), Electronic Brake Force Distribution (EBD) and Cornering Brake Control (CBC), Dynamic Stability Control (DSC) with Brake Assist and Hill Start Assistant, optional: Dynamic Traction Control (DTC) and Electronic Differential Lock Control (EDLC). Parking brake acts mechanically on rear wheels	
Steering		Electric power steering (EPS); 2.4 rotations in total	
Steering transmission, overall	:1	14.1	14.1
Tyres		195/55 R16 87V	195/55 R16 87V
Wheels		6.5J × 16 light-alloy	6.5J × 16 light-alloy
Transmission			
Type of gearbox		6-gear manual transmission	6-speed automatic transmission
Gear ratios	I	:1	3.308
	II	:1	1.870
	III	:1	1.194
	IV	:1	0.872
	V	:1	0.721
	VI	:1	0.596
Reverse gear		:1	3.231
Final drive ratio		:1	3.706
Performance			
Power-to-weight ratio to DIN	kg/kW	11.2	11.4
Output per litre	kW/l	52.6	52.6
Acceleration	0-100 km/h	s	7.9
	0-1000 m	s	29.0
in 4 th / 5 th gear	80-120 km/h	s	6.5 / 7.7
Top speed	km/h	216	206
Fuel consumption in EU cycle			
Urban	l/100 km	5.1	6.9
Extra-urban	l/100 km	3.9	4.3
Composite	l/100 km	4.3	5.3
CO ₂	g/km	114	139
Miscellaneous			
Emission rating		EU5	EU5
Ground clearance (empty)	mm	139	139

Specifications apply to ACEA markets / data relevant to homologation applicable in part only to Germany (weight)

¹⁾ Weight of the car in road trim (DIN) plus 75 kg for driver and luggage.

²⁾ Data not yet available.