BMW Media Information Specifications BMW Z4. Z4 sDrive20i, Z4 sDrive28i

2/2013

Valid from 3/2013



		BMW Z4 sDrive20i	BMW Z4 sDrive28i	
Body				
No of doors / seats		2/2	2/2	
Length/width/height (unladen)	mm	4239 / 1790 / 1291	4239 / 1790 / 1291	
Wheelbase	mm	2496	2496	
Track, front / rear	mm	1511 / 1559	1511 / 1559	
Ground clearance	mm	130	130	
Turning circle	m	10.7	10.7	
Tank capacity	app ltr	55	55	
Cooling system incl heater	ltr	8.2 (8.5)	8.2 (8.5	
Engine oil <sup>1)</sup>	ltr	5.75	5.75	
Weight, unladen, to DIN/EU	kg	1395 / 1470 (1420 / 1495)	1400 / 1475 (1420 / 1495)	
Payload (DIN)	kg	330	330	
Permitted total weight	kg	1725 (1750)	1730 (1750)	
Permitted axle load, front/rear	kg	800 / 970	800 / 970	
	ltr	180 - 310	180 - 310	
Luggage compartment capacity		0.34 x 1.96	0.34 x 1.96	
Air drag	cd x A	0.34 x 1.90	0.54 X 1.90	
Power Unit				
Config/No of cyls/valves		inline / 4 / 4	inline / 4 / 4	
Engine technology		BMW TwinPower Turbo	BMW TwinPower Turbo	
		technology with twin-scroll	technology with twin-scrol	
		turbocharger, High Precision Injection,	turbocharger High Precision Injection	
		VALVETRONIC fully	VALVETRONIC fully	
		variable valve control	variable valve contro	
		and Double-VANOS	and Double-VANOS	
		variable camshaft control	variable camshaft control	
Capacity, effective	CC	1997	1997	
Stroke / bore	mm	90.1 / 84.0	90.1 / 84.0	
Compression ratio	:1	10.0	10.0	
Fuel		min RON 91	min RON 91	
Max output	kW/hp	135 / 184	180 / 245	
at	rpm	5000	5000 – 6500	
Max torque	Nm	270	350	
at	rpm	1250 – 4500	1250 – 4800	
	ipiii			
Electrical System		70.//	00.11	
Battery/location	Ah/–	70 / luggage comp	80 / luggage comp	
Alternator	AW	170 / 2380	170 / 2380	
<b>Driving Dynamics and Safety</b>				
Suspension, front	Double wishbone spring strut tiebar axle in aluminium with displaced castor, small positive steering roll radius, compensation of lateral forces, anti-dive			
Suspension, rear	Central arm axle, separate springs and dampers, anti-squat and anti-dive			
Brakes, front	Single-piston floating-calliper disc brakes			
Diameter	mm	300 x 24 / vented	330 x 24 / vented	
Brakes, rear		Single-p	iston floating-calliper disc brakes	
Diameter	mm	300 x 20 / vented	300 x 20 / vented	
Driving stability systems		Standard: DSC incl ABS and DTC Dynamic Traction Control, CBC Cornering Brake Control, DBC Dynamic Brake Assistant, Dry Braking, Fading Compensation		
Safety equipment		Standard: airbags for driver and passenger, seat-integrated side airbags for driver and passenger, three-point inertia-reel seat belts with belt latch tensioners and belt force limiters, crash sensors, Tyre Defect Indicator		
Steering		EPS Electr	ic Power Steering with Servotronic	
Steering transmission, overall	:1	14.4	14.4	
oteening transmission, overall				
Tyres, front/rear		225/45 R17 91W RSC	225/45 R17 91W RSC	

2/2013

Valid from 3/2013

## Specifications BMW Z4.

			BMW Z4 sDrive20i	BMW Z4 sDrive28i			
BMW Connec	tedDrive						
Comfort		Optional: BMW Assist including Enquiry Service, remote-control function, Real Time Traffic Information, BMW TeleServices, integration of mobile devices					
Infotainment		Optional: access to the internet, BMW Online including features such as Parkinfo, National Info, Google directory service, News, realtime weather, BMW Routes, office functions, Bluetooth Audio Streaming, online music title update, Apps					
Safety		Optional: Adaptive Headlights, High-Beam Assistant, Park Distance Control, cruise control with brake function, Automatic/Enhanced Emergency Call					
Transmission							
Type of transmi	ssion	Six-speed manual (optional: eight-speed automatic)		ight-speed automatic)			
Gear ratios	I	:1	3.683 (4.714)	3.683 (4.714)			
	Ш	:1	2.062 (3.143)	2.062 (3.143)			
III V	III	:1	1.313 (2.106)	1.313 (2.106)			
	IV	:1	1.000 (1.667)	1.000 (1.667)			
	V	:1	0.809 (1.285)	0.809 (1.285)			
	VI	:1	0.677 (1.000)	0.677 (1.000)			
VII	VII	:1	- (0.839)	- (0.839)			
	VIII	:1	- (0.667)	- (0.667)			
Revers	Reverse	: :1	3.348 (3.295)	3.348 (3.295)			
Final drive		:1	3.727 (3.077)	3.077 (3.727)			
Performance							
Power-to-weigh (DIN unladen)	nt-ratio	kg/kW	10.3 (10.5)	7.8 (7.9)			
Specific power	output	kW/I	67.6	90.1			
Acceleration	0–100 km/h	sec	6.9 (6.9)	5.7 (5.5)			
Acceleration	0–1,000 m	sec	27.4 (27.8)	25.2 (25.3)			
in 4th/5th gear	80–120 km/h	sec	6.1 / 7.9 (–)	5.2 / 6.7 (-			
Max. speed		km/h	235 (232)	250 (250)			
BMW Efficient	tDynamics						
BMW EfficientDynamics standard features		C	Brake Energy Regeneration, EPS Electric Power Steering, Auto Start Stop function, gearshift point indicator (manual models), intelligent lightweight construction, on-demand operation of ancillary units, map-controlled oil pump, detachable a/c compressor, tyres with reduced roll resistance				
Fuel Consump	otion in EU						
Urban		l/100 km	8.9 (9.4)	9.1 (9.4)			
Extra-urban		I/100 km	5.6 (5.3)	5.5 (5.3)			
Combined		I/100 km	6.8 (6.8)	6.8 (6.8			
CO <sub>2</sub>		g/km	159 (159)	159 (159)			
			• •				

Specifications applicable to ACEA markets/homologation data applicable in part only to Germany (weight). Figures in brackets apply to automatic transmission models.

<sup>1)</sup> Öil change