



Specifications.

MINI Cooper Countryman ALL4.

MINI Cooper Countryman ALL4 Automatic.

Body		MINI Cooper Countryman ALL4	MINI Cooper Countryman ALL4 Automatic
No of doors/seats		5 / 4	5 / 4
Length/width/height (unladen)	mm	4097 / 1789 / 1561	4097 / 1789 / 1561
Wheelbase	mm	2596	2596
Track, front/rear	mm	1537 / 1564	1537 / 1564
Turning circle	m	11.6	11.6
Tank capacity	approx l	47	47
Cooling system incl heater	l	7.5	7.5
Engine oil	l	4.2	4.2
Transmission oil incl drive train	l	Lifetime	Lifetime
Weight, unladen to DIN/EU ¹⁾	kg	1340 / 1415	1385 / 1460
Max load to DIN	kg	510	510
Max permissible weight	kg	1850	1895
Max axle load, front/rear	kg	960 / 930	1005 / 930
Max trailer load braked (12%) / unbraked	kg	- / -	1000 / 500
Max roofload/max download	kg	75 / -	75 / 75
Luggage compartment	l	350 - 1170	350 - 1170
Air drag $c_d / A / c_d \times A$	- / m ² / m ²	0.35 / 2.36 / 0.83	0.35 / 2.36 / 0.83
Engine			
Config/No of cyls/valves		In-line / 4 / 4	In-line / 4 / 4
Engine management		MEV 17.2.2	MEVD 17.2.2
Capacity	cm ³	1598	1598
Bore/stroke	mm	77.0 / 85.8	77.0 / 85.8
Compression ratio	:1	11.0	11.0
Fuel grade	RON	91-98	91-98
Max output	kW / hp	90 / 122	90 / 122
at	rpm	6000	6000
Max torque	Nm	160	190
at	rpm	4250	4250
Electrical system			
Battery/installation	Ah / -	55 / Engine compartment	55 / Engine compartment
Alternator	A	120	120
Chassis			
Suspension, front		Single-joint MacPherson spring strut axle with anti-dive control	
Suspension, rear		Multi-link axle with longitudinal struts in lightweight aluminium design	
Front brakes		Vented disc	Vented disc
Diameter	mm	294 × 22	294 × 22
Rear brakes		Disc	Disc
Diameter	mm	280 × 10	280 × 10
Driving stability systems		Hydraulic two-circuit brake system with anti-lock brakes (ABS), Electronic Brake Force Distribution (EBD) and Cornering Brake Control (CBC), Dynamic Stability Control (DSC) with Brake Assist, Hill Start Assistant, Dynamic Traction Control (DTC) and Electronic Differential Lock Control (EDLC), DSC control unit with integrated control electronics for the MINI ALL4 all-wheel-drive system. Parking brake acts mechanically on rear wheels	
Steering		Electric power steering (EPS); 2.4 rotations in total	
Steering transmission, overall	:1	14.1	14.1
Tyres		205/60 R16 92H	205/60 R16 92H
Wheels		6,5J × 16 light-alloy	6,5J × 16 light-alloy
Transmission			
Type of gearbox		6-gear manual transmission	6-speed automatic transmission
Gear ratios	I	:1	3.308
	II	:1	2.130
	III	:1	1.483
	IV	:1	1.139
	V	:1	0.949
	VI	:1	0.816
Reverse gear	:1	3.231	3.394
Final drive ratio	:1	4.353	3.683
Performance			
Power-to-weight ratio to DIN	kg/kW	14.9	15.4
Output per litre	kW/l	56.3	56.3
Acceleration	0-100 km/h	s	11.9
	0-1000 m	s	33.5
in 4th/5th gear	80-120 km/h	s	11.4 / 14.8
Top speed	km/h	184	182
Fuel consumption in EU cycle			
Urban	l/100 km	8.4	10.0
Extra-urban	l/100 km	6.0	6.1
Composite	l/100 km	6.9	7.5
CO ₂	g/km	160	175
Miscellaneous			
Emission rating		EU6	EU6
Ground clearance (empty)	mm	160	160

Specifications apply to ACEA markets / data relevant to homologation applicable in part only to Germany (weight)

¹⁾ Weight of the car in road trim (DIN) plus 75 kg for driver and luggage