BMW Media Information

10/2013

Valid from 11/2013





BMW 420i xDrive Coupe

		BMW 4201 XDrive Coupe	
Body			
No. of doors/seats		2/4	
Length/width/height ¹⁾ (unladen)	mm	4638 / 1825 / 1392	
Wheelbase	mm	281	
Front/rear track	mm	1545 / 1594	
Ground clearance	mm	14	
Turning circle	m	11.8	
Fuel capacity	approx. I	60	
Cooling and heating system	1	7.2 (7.5	
Engine oil capacity ²⁾		4.8	
Weight, unladen (DIN/EU)	kg	1520 / 1595 (1530 / 1605	
Payload (DIN)	kg	520	
Permitted total weight	kg	2040 (2050	
Permitted axle load, front/rear	kg	975/1110	
Permitted trailer load (12%) braked/unbraked	kg	1700 / 750 (1700 / 750	
Permitted roof load/trailer download	kg	75/75	
Luggage compartment capacity		445	
Aerodynamic drag	c _c x A	443 0.30 × 2.16	
Engine			
Type/no. of cylinders/valves		in-line / 4 / 4	
Engine technology		BMW TwinPower Turbo technology with twin-scroll turbocharger, High Precision Injection, VALVETRONIC fully variable valve control and Double-VANOS variable camshaft control	
Effective capacity	CC	1997	
Stroke/bore	mm	90.1/84.0	
Compression ratio	:1	11.0	
Fuel type		min. RON 97	
Output	kW/hp	135 / 184	
at rpm	min ⁻¹	5000 – 6250	
Torque	Nm	270	
at rpm	min ⁻¹	1250 - 4500	
Electrical			
Battery charge/location	Ah/–	90 / luggage compartmen	
Alternator current/output	A/W	170/2380	
Driving Dynamics and Safety Front suspension		Aluminium double-joint spring-strut axle with displaced camber, small positive	
		steering roll radius, compensation of lateral forces, anti-dive	
Rear suspension		Five-link axle in lightweight steel construction	
Front brakes		Single-piston floating-calliper disc brakes, inner-vented	
Rear brakes		Single-piston floating-calliper disc brakes, inner-vented	
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, start-off assist, linked to xDrive all-wheel-drive system in Integrated Chassis Management (ICM);	
Safety equipment		Standard: driver and front-seat passenger airbags, driver and front-seat passenger side airbags, front and rear head airbags, three-point automatic seatbelts for all seats, seatbelt tensioners and seatbelt force limiters in front seats, crash sensors, tyre defect indicator	
Steering		Electromechanical rack-and-pinion power steering (EPS) with Servotronic function; optional: Variable Sport Steering	
Overall steering ratio	:1	15.2	
Front/rear tyres		225/50 R17 94V	
Front/rear wheels		7,5J x 17 light-alloy	
		, 5,	

10/2013

Valid from 11/2013

Specifications. BMW 4 Series Coupe.

Ш

|||

IV

ν

VI

VII

VIII

R

6-speed manual (optional: 8-speed automatic with Steptronic) 4.110 (4.714) :1 :1 2.315 (3.143) 1.542 (2.106) :1 1.179 (1667) :1 :1 1.000 (1.285) :1 0.846 (1.000) :1 - (0.839) - (0.667) :1 :1 3.727 (3.295) 3.385 (3.154) :1

BMW 420i xDrive Coupe

Performance

Differential ratio

Transmission Type of gearbox

Gear ratios

1 cmonnanoc			
Weight-to-pow (DIN unladen)	er ratio	kg/kW	11.3 (11.3)
Specific power	output	kW/I	67.6
Acceleration	0–100 km/h	sec.	7.4 (7.5)
	0–1,000 m	sec.	28.0 (28.3)
in 4th/5th gear	80–120 km/h	sec.	7.3/8.7
Max. speed		km/h	233 (231)

BMW EfficientDynamics

BMW EfficientDynamics Features included as standard

Brake Energy Regeneration with recuperation display, electric power steering (EPS), Auto Start Stop function, gear shift indicator (manual), ECO PRO mode with coasting function, intelligent lightweight construction, optimised aerodynamic attributes, on-demand operation of ancillary units, map-regulated oil pump, differential with optimized-warm-up behaviour, tyres with reduced rolling resistance

Fuel consumption (EU) ³⁹ With standard wheels and tyres				
Extra-urban	l/100 km	5.6 (5.1)		
Total	l/100 km	6.8 (6.4)		
CO ₂ emissions	a/km	159 (149)		

With 8J x 18" rims and 225/45 R18 tyres and winter tyres, With 8J x 18" front rims, 8.5J x 18" rear rims, 225/45 R18 front tyres and 255/40 R18 rear tyres, With 8J x 19" front rims, 8.5J x 19" rear rims, 225/40 R19 front tyres and 255/35 R19 rear tyres

Urban	l/100 km	9.1 (8.8)
Extra-urban	l/100 km	5.7 (5.2)
Combined	l/100 km	7.0 (6.5)
CO ₂ emissions	g/km	162 (152)
Emissions standard		EU6

Technical data valid for ACEA countries/Some permitted weights valid only for Germany Figures in brackets are for vehicles with automatic transmission

Height including roof aerial
 Oil change volume
 Fuel consumption and CO₂ emissions depend on the selected tyre format