BMW Media Information

5/2014

Valid from 7/2014

Specifications. BMW 4 Series Convertible.

425d



		BMW 425d Convertible
Body		
No. of doors/seats		2/4
Length/width/height (unladen)	mm	4638 / 1825 / 1384
Wheelbase	mm	2810
Front/rear track	mm	1545 / 1594
Ground clearance		134371332
	mm	
Turning circle	m	11.3
Fuel capacity	approx. I	57
Cooling and heating system	I	7.0
reservoir capacity Engine oil capacity 1)		7.0 5.2
Weight, unladen (DIN/EU)	kg	1715 / 1790
Wolgin, aniadon (Bilweo)	ng.	(1730 / 1805
Payload (DIN)	kg	450
Permitted total weight	kg	2165 (2180)
Permitted axle load, front/rear	kg	980 / 1230
Permitted trailer load (12%)	kg	3007 1200
braked/unbraked ` ´		1800 / 750
Permitted roof load/trailer	kg	-175
download		
Luggage compartment capacity	I	370
Aerodynamic drag	c _c x A	0.30 x 2.16
Engine		
Type/no. of cylinders/valves		in-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology with two turbochargers
		high pressure charger with variable inlet geometry Common Rail direct injection with piezo injectors (max. injection pressure: 2000 bar
Titta atti va anna atti		
Effective capacity	CC	1995
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel type		Diese
Output	kW/hp	160 / 218
at rpm	min ⁻¹	4400
Torque	Nm	450
at rpm	min ⁻¹	1500 – 2500
Electrical		
Battery charge/location	Ah/-	90 / luggage compartment
Alternator current/output	A/W	170 / 2380
Driving Dynamics and Safety Front suspension	1	Aluminium double-ioint spring-strut axle with displaced camber, small positive
Priving Dynamics and Safety Front suspension	1	Aluminium double-joint spring-strut axle with displaced camber, small positive steering roll radius, compensation of lateral forces, anti-dive
Front suspension Rear suspension	1	steering roll radius, compensation of lateral forces, anti-dive Five-link axle in lightweight steel construction
Front suspension	<i>'</i>	steering roll radius, compensation of lateral forces, anti-dive
Front suspension Rear suspension	<i>'</i>	steering roll radius, compensation of lateral forces, anti-dive Five-link axle in lightweight steel construction
Front suspension Rear suspension Front brakes		steering roll radius, compensation of lateral forces, anti-dive Five-link axle in lightweight steel construction Single-piston floating-calliper disc brakes, inner-vented
Front suspension Rear suspension Front brakes Rear brakes Driving stability systems		steering roll radius, compensation of lateral forces, anti-diversity for the steel construction. Single-piston floating-calliper disc brakes, inner-vented Single-piston floating-calliper disc brakes, inner-vented Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, start-off assist; optional: Adaptive Suspension Standard: driver and front-seat passenger airbags, driver and front-seat passenger side airbags with combined head airbags, three-point automatic seatbelts for all seats, seatbelt tensioners and seatbelt force limiters in front
Front suspension Rear suspension Front brakes Rear brakes		steering roll radius, compensation of lateral forces, anti-dive Five-link axle in lightweight steel constructior Single-piston floating-calliper disc brakes, inner-vented Single-piston floating-calliper disc brakes, inner-vented Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control) CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying
Front suspension Rear suspension Front brakes Rear brakes Driving stability systems Safety equipment Steering		steering roll radius, compensation of lateral forces, anti-diversity five-link axle in lightweight steel construction. Single-piston floating-calliper disc brakes, inner-vented Single-piston floating-calliper disc brakes, inner-vented Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, start-off assist; optional: Adaptive Suspension. Standard: driver and front-seat passenger airbags, driver and front-seat passenger side airbags with combined head airbags, three-point automatic seatbelts for all seats, seatbelt tensioners and seatbelt force limiters in front seats, crash sensors, tyre pressure indicator. Electromechanical rack-and-pinion power steering (EPS)
Front suspension Rear suspension Front brakes Rear brakes Driving stability systems Safety equipment	:1	steering roll radius, compensation of lateral forces, anti-diversity of the construction of the construc

BMW

Media Information

5/2014

Valid from 7/2014

Specifications. BMW 4 Series Convertible.

		BMW 425d Convertible
Transmission		
		Conced manual (antionals Conced Ctantrania)
Type of gearbox Gear ratios	:1	6-speed manual (optional: 8-speed Steptronic) 4.110 (4.714)
Gearratios i	:1	2.248 (3.143)
<u> </u>		2.248 (3.143)
	* * * * * * * * * * * * * * * * * * * *	
V	• • • • • • • • • • • • • • • • • • • •	1.000 (1.667)
V	• • • • • • • • • • • • • • • • • • • •	0.802 (1.285) 0.659 (1.000)
V		(0.00.1) eco.0 (0.839) –
V	**	- (0.839) - (0.667)
v R	***	(/
Differential ratio	:1	3.727 (3.295) 3.462 (2.813)
Differential ratio		3.402 (2.813)
Performance		
Weight-to-power ratio (DIN unladen)	kg/kW	10.7 (10.8)
Specific power output	kW/l	80.2
Acceleration 0–100	km/h sec.	7.3 (7.1)
0–1,00	0 m sec.	2)
in 5th gear 80–120 k	m/h sec.	7.2 (–)
Max. speed	km/h	241 (241)
BMW EfficientDynami		
BMW EfficientDynamics included as standard	Features	Brake Energy Regeneration with recuperation display, electric power steering (EPS), Auto Start Stop function, gear shift indicator (manual), ECO PRO mode with coasting function (automatic), intelligent lightweight construction, optimised aerodynamic attributes, on-demand operation of ancillary units, differential with optimized-warm-up behaviour, tyres with reduced rolling resistance, BMW BluePerformance technology
Fuel consumption (EU	l) ³⁾	
With standard wheels and	d tyres	
Urban	l/100 km	6.5 (6.0)
Extra-urban	l/100 km	4.5 (4.4)
Total	l/100 km	5.2 (5.0)
CO ₂ emissions	g/km	138 (132)
	8.5J x 18" rear rin	and winter tyres, ns, 225/45 R18 front tyres and 255/40 R18 rear tyres, ns, 225/40 R19 front tyres and 255/35 R19 rear tyres
Urban	l/100 km	6.6 (6.2)
Extra-urban	l/100 km	4.7 (4.5)
Combined	l/100 km	5.4 (5.2)
CO ₂ emissions	g/km	142 (136)
Emissions standard		EU6

Technical data valid for ACEA countries/Some permitted weights valid only for Germany Figures in brackets are for vehicles with automatic transmission

 $^{^{1)}}$ Oil change volume $^{2)}$ Data not yet available $^{3)}$ Fuel consumption and CO_2 emissions depend on the selected tyre format