

# Specifications.

## BMW 4 Series Coupe.

### 420d xDrive



BMW 420d xDrive Coupe		
<b>Body</b>		
No. of doors/seats		2 / 4
Length/width/height <sup>1)</sup> (unladen)	mm	4638 / 1825 / 1392
Wheelbase	mm	2810
Front/rear track	mm	1545 / 1594
Ground clearance	mm	145
Turning circle	m	11.8
Fuel capacity	approx. l	57
Cooling and heating system reservoir capacity	l	7.0
Engine oil capacity <sup>2)</sup>	l	5.0
Weight, unladen (DIN/EU)	kg	1540 / 1615 (1560 / 1635)
Payload (DIN)	kg	520
Permitted total weight	kg	2060 (2080)
Permitted axle load, front/rear	kg	995 / 1125
Permitted trailer load (12%) braked/unbraked	kg	1600 / 750
Permitted roof load/trailer download	kg	75 / 75
Luggage compartment capacity	l	445
Aerodynamic drag	c <sub>d</sub> x A	0.29 x 2.16
<b>Engine</b>		
Type/no. of cylinders/valves		in-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology: variable-geometry turbocharger, common-rail direct fuel injection with magnetic valve injectors, max. injection pressure: 2000 bar
Effective capacity	cc	1995
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel type		Diesel
Output	kW/hp	140 / 190
at rpm	min <sup>-1</sup>	4000
Torque	Nm	400
at rpm	min <sup>-1</sup>	1750 – 2500
<b>Electrical</b>		
Battery charge/location	Ah–	90 / luggage compartment
Alternator current/output	AW	150 / 2100
<b>Driving Dynamics and Safety</b>		
Front suspension		Aluminium double-joint spring-strut axle with displaced camber, small positive steering roll radius, compensation of lateral forces, anti-dive
Rear suspension		Five-link axle in lightweight steel construction
Front brakes		Single-piston floating-calliper disc brakes, vented
Rear brakes		Single-piston floating-calliper disc brakes, vented
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, start-off assistant, linked to xDrive all-wheel-drive system in Integrated Chassis Management (ICM)
Safety equipment		Standard: driver and front-seat passenger airbags, driver and front-seat passenger side airbags, head airbags front and rear, three-point automatic seatbelts for all seats, seatbelt tensioners and seatbelt force limiters in front seats, crash sensors, tyre pressure indicator
Steering		Electromechanical rack-and-pinion power steering (EPS) with Servotronic function, optional: Variable Sport Steering
Overall steering ratio	:1	15.2
Front/rear tyres		225/50 R17 94W
Front/rear wheels		7.5J x 17 light-alloy

## Specifications. BMW 4 Series Coupe.

### BMW 420d xDrive Coupe

#### Transmission

Type of gearbox	6-speed manual (optional: 8-speed Steptronic)		
Gear ratios	I	:1	4.110 (5.000)
	II	:1	2.248 (3.200)
	III	:1	1.403 (2.143)
	IV	:1	1.000 (1.720)
	V	:1	0.802 (1.314)
	VI	:1	0.659 (1.000)
	VII	:1	– (0.822)
	VIII	:1	– (0.640)
	R	:1	3.727 (3.456)
Differential ratio		:1	3.154 (2.813)

#### Performance

Weight-to-power ratio (DIN unladen)		kg/kW	11.0 (11.1)
Specific power output		kW/l	70.2
Acceleration	0–100 km/h	sec.	7.4 (7.2)
in 5th gear	80–120 km/h	sec.	8.1 (–)
Max. speed		km/h	236 (230)

#### BMW EfficientDynamics

BMW EfficientDynamics Features included as standard	Brake Energy Regeneration with recuperation display, electric power steering (EPS), Auto Start Stop function, gear shift indicator, ECO PRO mode with coasting function (automatic), intelligent lightweight construction, optimised aerodynamic attributes, on-demand operation of ancillary units, map-regulated oil pump, detachable a/c compressor, differential and power divider with optimized-warm-up behaviour, tyres with reduced rolling resistance
---	--

#### Fuel consumption (EU)<sup>3)</sup>

with standard wheels and tyres			
Urban	l/100 km		5.3 (5.2)
Extra-urban	l/100 km		3.9 (4.0)
Total	l/100 km		4.4 (4.4)
CO <sub>2</sub> emissions	g/km		117 (117)
with 8J x 18" rims and 225/45 R18 tyres and winter tyres, with 8J x 18" front rims, 8.5J x 18" rear rims, 225/45 R18 front tyres and 255/40 R18 rear tyres, with 8J x 19" front rims, 8.5J x 19" rear rims, 225/40 R19 front tyres and 255/35 R19 rear tyres			
Urban	l/100 km		5.8 (5.6)
Extra-urban	l/100 km		4.1 (4.2)
Combined	l/100 km		4.7 (4.7)
CO <sub>2</sub> emissions	g/km		125 (125)
Emissions standard			EU6

Technical data valid for ACEA countries/Some permitted weights valid only for Germany  
Figures in brackets are for vehicles with automatic transmission

<sup>1)</sup> Height including roof aerial

<sup>2)</sup> Oil change volume

<sup>3)</sup> Fuel consumption and CO<sub>2</sub> emissions depend on the selected tyre format