

Technical specifications.

MINI One 5 door, MINI One Automatic 5 door.



Body		MINI One 5 door	MINI One Automatic 5 door
Number of doors/seats		5 / 5	5 / 5
Length/width/height (empty)	mm	3982 / 1727 / 1425	3982 / 1727 / 1425
Wheelbase	mm	2567	2567
Track width, front/rear	mm	1501 / 1501	1501 / 1501
Turning circle	m	11,02	11,02
Fuel tank capacity	approx. l	40	40
Cooling system incl. heating	l	4,9	4,9
Engine oil	l	4,25	4,25
Transmission oil incl. drivetrain	l	lifetime filling	lifetime filling
Unladen weight according to DIN/EU ¹⁾	kg	1150 / 1225	1175 / 1250
Payload according to DIN	kg	530	530
Permitted gross vehicle weight	kg	1680	1705
Permitted axle loads, front/rear	kg	900 / 845	925 / 845
Permitted trailer load braked (12 %) / unbraked	kg	- / -	- / -
Permitted roof load/permited download	kg	75 / -	75 / -
Luggage compartment capacity	l	278	278
Aerodynamic drag $c_x / A / c_x \times A$	- / m ² / m ²	0,29 / 2,07 / 0,6	0,29 / 2,07 / 0,6
Engine			
Type/no. of cylinders/valves		in-line / 3 / 4	in-line / 3 / 4
Engine control		MEVD 17.2.3	MEVD 17.2.3
Capacity	cc	1198	1198
Bore/stroke	mm	78,0 / 83,6	78,0 / 83,6
Compression	:1	10,2	10,2
Fuel	RON	91-98	91-98
Output	kW/bhp	75 / 102	75 / 102
at engine speed	rpm	4000	4000
Torque	Nm	180	180
at engine speed	rpm	1400	1400
Electrical system			
Battery/installation	Ah / -	70 / engine compartment	70 / engine compartment
Alternator	A	150	150
Suspension			
Front wheel suspension		Single-joint McPherson spring strut axle with aluminium swivel bearing and anti-dive control	
Rear wheel suspension		Multilink axle with weight-optimised trailing arms	
Brakes, front		disc, vented	disc, vented
Rear brakes		disc	disc
Driving stability systems		Hydraulic 2-circuit brake system with anti-lock brakes (ABS), electronic brake force distribution (EBD) and Cornering Brake Control (CBC), Dynamic Stability Control (DSC) with brake assistant, hill start assistant, brake dry function, Fading Brake Support, Dynamic Traction Control (DTC) and Electronic Differential Lock Control (EDLC). Handbrake impacts mechanically on rear wheels	
Steering		Electrically assisted EPS unit with Servotronic function	
Overall steering ratio	:1	14.2	14.2
Tyres		175/65 R15 84H	175/65 R15 84H
Rims		5.5J x 15 steel	5.5J x 15 steel
Transmission			
Transmission type		6-speed manual transmission	6-speed automatic transmission
Gear ratio	I	:1 3,615	4,459
	II	:1 1,952	2,508
	III	:1 1,241	1,556
	IV	:1 0,969	1,142
	V	:1 0,806	0,851
	VI	:1 0,683	0,672
Reverse gear	:1	3,538	3,185
Final drive ratio	:1	3,632	3,683
Driving performance figures			
Power-to-weight ratio according to DIN	kg/kW	15,3	15,7
Power output per litre	kW/l	62,6	62,6
Acceleration	0-100 km/h	s 10,1	10,5
	0-1000 m	s ²⁾	²⁾
in 4th/5th gear	80-120 km/h	s ²⁾ / 12,8	- / -
Top speed	km/h	192	192



03/2015

Valid from
03/2015

Fuel consumption in EU cycle ³⁾			
Urban	l/100 km	5,9	5,9
Extra-urban	l/100 km	4,2	4,3
Total	l/100 km	4,8	4,9
CO ₂	g/km	112	114
Other			
Emission rating		EU6	EU6
Insurance rating in Germany	3rd party / Fully comprehensive / 3rd party fire + theft	15 / 17 / 20	15 / 17 / 20
Ground clearance (empty)	mm	146	146

Technical specifications valid for ACEA markets / authorisation data only relevant to Germany in some cases (weights)

¹⁾ Weight of road-ready automobile (DIN) plus 75 kg for driver and luggage

²⁾ Details not yet available

³⁾ Dependent on tyre format selected