



Technical specifications.

MINI One Countryman,

MINI One Countryman Automatic.

Body		MINI One Countryman	MINI One Countryman Automatic
Number of doors/seats		5 / 5	5 / 5
Length/width/height (empty)	mm	4097 / 1789 / 1561	4097 / 1789 / 1561
Wheelbase	mm	2595	2595
Track width, front/rear	mm	1534 / 1559	1534 / 1559
Turning circle	m	11.6	11.6
Fuel tank capacity	approx. l	47	47
Cooling system incl. heating	l	5.5	6.0
Engine oil	l	4.2	4.2
Transmission oil incl. drivetrain	l	lifetime filling	lifetime filling
Unladen weight according to DIN/EU ¹	kq	1265 / 1340	1295 / 1370
Payload according to DIN	kq	510	510
Permitted gross vehicle weight	kq	1775	1805
Permitted axle loads, front/rear	kq	935 / 880	965 / 880
Permitted trailer load ²			
braked (12 %) / unbraked	kg	- / -	- / -
Permitted roof load/permitted	kq	75 / -	75 / -
Luggage compartment capacity	l	350 - 1170	350 - 1170
Aerodynamic drag $c_x / A / c_x \times A$	- / m ² / m ²	0.36 / 2.36 / 0.85	0.36 / 2.36 / 0.85
Engine			
Type/no. of cylinders/valves		in-line/ 4 / 4	in-line/ 4 / 4
Engine control		MEV 17.2.2	MEV 17.2.2
Capacity	cc	1598	1598
Bore/stroke	mm	77 / 85.8	77 / 85.8
Compression	:1	11.0	11.0
Fuel	RON	91-98	91-98
Output	kW/bhp	72 / 98	72 / 98
at engine speed	rpm	6000	6000
Torque	Nm	153	153
at engine speed	rpm	3000	3000
Electrical system			
Battery/installation	Ah / -	60 / engine compartment	55 / engine compartment
Alternator	A	150	120
Suspension			
Front wheel suspension		Single-joint Mc Pherson spring strut axle with anti-dive control	
Rear wheel suspension		Multilink axle with trailing arms in aluminium lightweight construction	
Brakes, front		disc, vented	disc, vented
Diameter	mm	294 x 22	294 x 22
Rear brakes		disc	disc
Diameter	mm	280 x 10	280 x 10
Driving stability systems		Hydraulic 2-circuit brake system with anti-lock brakes (ABS), electronic brake force distribution (EBD) and Cornering Brake Control (CBC), Dynamic Stability Control (DSC) with brake assistant, hill start assistant, optional: Dynamic Traction Control (DTC) and Electronic Differential Lock Control (EDLC). Handbrake impacts mechanically on rear wheels	
Steering		Electrically supported steering (EPS); 2.4 revolutions from lock to lock	
Overall steering ratio	:1	14.1	14.1
Tyres		205 / 60 R16 92H	205 / 60 R16 92H
Rims		6.5J x 16	6.5J x 16
Transmission			
Transmission type		6-speed manual transmission	6-speed automatic transmission
Gear ratio	I	:1	4.148
	II	:1	2.370
	III	:1	1.556
	IV	:1	1.155
	V	:1	0.859
	VI	:1	0.686
Reverse gear	:1	3.143	3.394
Final drive ratio	:1	4.353	4.643
Driving performance figures			
Power-to-weight ratio according to	kq/kW	17.6	18.0
Power output per litre	kW/l	45.1	45.1
Acceleration	0-100 km/h	s	11.9
	0-1000 m	s	33.7
in 5th gear	80-120 km/h	s	17.6
Top speed	km/h	175	170



04/2014

Valid from
07/2014

Fuel consumption in EU cycle			
Urban	l/100 km	7.1	9.0
Extra-urban	l/100 km	5.0	5.6
Total	l/100 km	5.7	6.9
CO ₂	g/km	134	159
Other			
Emission rating		EU6	EU6
Insurance rating	3rd party/fully comprehensive/3rd party fire + theft	15 / 15 / 22	15 / 15 / 22
Ground clearance	mm	145	145

Technical specifications valid for ACEA markets / registration-related data only relevant to Germany in some cases (weights)

¹⁾ Weight of road-ready automobile (DIN) plus 75 kg for driver and luggage

²⁾ Details not yet available