



Technical specifications.

MINI Cooper Countryman ALL4, MINI Cooper Countryman ALL4 Automatic.

Body		MINI Cooper Countryman ALL4	MINI Cooper Countryman ALL4 Automatic
Number of doors/seats		5 / 5	5 / 5
Length/width/height (empty)	mm	4100 / 1789 / 1561	4100 / 1789 / 1561
Wheelbase	mm	2596	2596
Track width, front/rear	mm	1537 / 1564	1537 / 1564
Turning circle	m	11.6	11.6
Fuel tank capacity	approx. l	47	47
Cooling system incl. heating	l	7.5	7.5
Engine oil	l	4.2	4.2
Transmission oil incl. drivetrain	l	lifetime filling	lifetime filling
Unladen weight according to DIN/EU ¹⁾	kg	1350 / 1425	1395 / 1470
Payload according to DIN	kg	510	510
Permitted gross vehicle weight	kg	1860	1905
Permitted axle loads, front/rear	kg	960 / 930	1005 / 930
Permitted trailer load braked (12 %) / unbraked	kg	- / -	1000 / 500
Permitted roof load/permitted download	kg	75 / -	75 / 75
Luggage compartment capacity	l	350 - 1170	350 - 1170
Aerodynamic drag c_x / A / $c_x \times A$	- / m ² / m ²	0.35 / 2.36 / 0.83	0.35 / 2.36 / 0.83
Engine			
Type/no. of cylinders/valves		in-line / 4 / 4	in-line / 4 / 4
Engine control		MEV 1722	MEVD 1722
Capacity	cc	1598	1598
Bore/stroke	mm	77.0 / 85.8	77.0 / 85.8
Compression	:1	11.0	10.5
Fuel	RON	91-98	91-98
Output	kW/bhp	90 / 122	90 / 122
at engine speed	rpm	6000	6000
Torque	Nm	160	190
at engine speed	rpm	4250	4250
Electrical system			
Battery/installation	Ah / -	55 / engine compartment	55 / engine compartment
Alternator	A	120	120
Suspension			
Front wheel suspension		Single-joint McPherson spring strut axle with anti-dive control	
Rear wheel suspension		Multilink axle with trailing arms in aluminium lightweight construction	
Brakes, front		disc, vented	disc, vented
Diameter	mm	294 × 22	294 × 22
Rear brakes		disc	disc
Diameter	mm	280 × 10	280 × 10
Driving stability systems		Hydraulic 2-circuit brake system with anti-lock brakes (ABS), electronic brake force distribution (EBD) and Cornering Brake Control (CBC), Dynamic Stability Control (DSC) with brake assistant, hill start assistant, Dynamic Traction Control (DTC) and Electronic Differential Lock Control (EDLC). DSC control unit with integrated electronic management system for the all-wheel drive system MINI ALL4. Handbrake impacts mechanically on rear wheels	
Steering		Electrically supported steering (EPS); 2.4 revolutions from lock to lock	
Overall steering ratio	:1	14.1	14.1
Tyres		205/60 R16 92H	205/60 R16 92H
Rims		6.5J × 16 light alloy	6.5J × 16 light alloy
Transmission			
Transmission type		6-speed manual transmission	6-speed automatic
Gear ratio	I	:1	3.308
	II	:1	2.130
	III	:1	1.483
	IV	:1	1.139
	V	:1	0.949
	VI	:1	0.816
Reverse gear	:1	3.231	3.394
Final drive ratio	:1	4.353	3.683
Driving performance figures			
Power-to-weight ratio according to DIN	kg/kW	14.9	15.4
Power output per litre	kW/l	56.3	56.3
Acceleration	0-100 km/h	s	11.5
	0-1000 m	s	33.5
in 5th gear	80-120 km/h	s	14.6
Top speed	km/h	186	184



07/2014

Valid from
07/2014

Fuel consumption in EU cycle			
Urban	l/100 km	8.2	9.4
Extra-urban	l/100 km	5.8	5.7
Total	l/100 km	6.7	7.0
CO ₂	g/km	156	164
Other			
Emission rating		EU6	EU6
Insurance rating	3rd party/fully comprehensive/3rd party fire + theft	15 / 18 / 22	15 / 18 / 22
Ground clearance (empty)	mm	145	130

Technical specifications valid for ACEA markets / registration-related data only relevant to Germany in some cases (weights)

¹⁾ Weight of road-ready automobile (DIN) plus 75 kg for driver and luggage

²⁾ Details not yet available