



Technical specifications.

MINI Cooper SD Countryman,

MINI Cooper SD Countryman Automatic.

Body		MINI Cooper SD Countryman	MINI Cooper SD Countryman Automatic
Number of doors/seats		5 / 5	5 / 5
Length/width/height (empty)	mm	4109 / 1789 / 1561	4109 / 1789 / 1561
Wheelbase	mm	2596	2596
Track width, front/rear	mm	1529 / 1556	1529 / 1556
Turning circle	m	11.6	11.6
Fuel tank capacity	approx. l	47	47
Cooling system incl. heating	l	6.0	6.5
Engine oil	l	5.2	5.2
Transmission oil incl. drivetrain	l	lifetime filling	lifetime filling
Unladen weight according to DIN/EU ¹⁾	kg	1320 / 1395	1350 / 1425
Payload according to DIN	kg	510	510
Permitted gross vehicle weight	kg	1830	1860
Permitted axle loads, front/rear	kg	995 / 880	1025 / 880
Permitted trailer load braked (12 %) / unbraked	kg	800 / 500	1200 / 500
Permitted roof load/permitted download	kg	75 / 75	75 / 75
Luggage compartment capacity	l	350 – 1170	350 – 1170
Aerodynamic drag $c_x / A / c_x \times A$	– / m ² / m ²	0.35 / 2.36 / 0.83	0.35 / 2.36 / 0.83
Engine			
Type/no. of cylinders/valves		in-line / 4 / 4	in-line / 4 / 4
Engine control		DDE 701	DDE 701
Capacity	cc	1995	1995
Bore/stroke	mm	84.0 / 90.0	84.0 / 90.0
Compression	:1	16.5	16.5
Fuel	RON	Diesel	Diesel
Output	kW/bhp	105 / 143	105 / 143
at engine speed	rpm	4000	4000
Torque	Nm	305	305
at engine speed	rpm	1750 – 2700	1750 – 2700
Electrical system			
Battery/installation	Ah / –	70 / engine compartment	70 / engine compartment
Alternator	A	150	150
Suspension			
Front wheel suspension		Single-joint McPherson spring strut axle with anti-dive control	
Rear wheel suspension		Multilink axle with trailing arms in aluminium lightweight construction	
Brakes, front		disc, vented	disc, vented
Diameter	mm	307 × 24	307 × 24
Rear brakes		disc	disc
Diameter	mm	280 × 10	280 × 10
Driving stability systems		Hydraulic 2-circuit brake system with anti-lock brakes (ABS), electronic brake force distribution (EBD) and Cornering Brake Control (CBC), Dynamic Stability Control (DSC) with brake assistant, hill start assistant, Dynamic Traction Control (DTC) and Electronic Differential Lock Control (EDLC). Handbrake impacts mechanically on rear wheels	
Steering		Electrically supported steering (EPS); 2.4 revolutions from lock to lock	
Overall steering ratio	:1	14.1	14.1
Tyres		205/55 R17 91V	205/55 R17 91V
Rims		7J × 17 light alloy	7J × 17 light alloy
Transmission			
Transmission type		6-speed manual transmission	6-speed automatic transmission
Gear ratio	I	3.308	4.044
	II	1.870	2.371
	III	1.194	1.556
	IV	0.872	1.159
	V	0.721	0.852
	VI	0.596	0.672
Reverse gear	:1	3.231	3.193
Final drive ratio	:1	3.706	3.683
Driving performance figures			
Power-to-weight ratio according to DIN	kg/kW	12.6	12.8
Power output per litre	kW/l	52.6	52.6
Acceleration	0–100 km/h	s	9.4
	0–1000 m	s	30.6
in 5th gear	80–120 km/h	s	– / –
Top speed	km/h	200	197



04/2014

Valid from
07/2014

Fuel consumption in EU cycle			
Urban	l/100 km	5.1	7.2
Extra-urban	l/100 km	4.2	4.8
Total	l/100 km	4.5	5.7
CO ₂	g/km	119	149
Other			
Emission rating		EU6	EU6
Insurance rating	3rd party/fully comprehensive/3rd party fire + theft	16 / 20 / 23	16 / 20 / 23
Ground clearance (empty)	mm	150	150

Technical specifications valid for ACEA markets / registration-related data only relevant to Germany in some cases (weights)

¹⁾ Weight of road-ready automobile (DIN) plus 75 kg for driver and luggage

²⁾ Details not yet available