BMW Media information

06/2015

valid from 07/2015

Specifications. BMW X1 xDrive25d.



		BMW X1 xDrive25d			
Body					
No. of doors/seats		E / E			
Length/width/height 1) (unladen)	mm	5 / 5 4439 / 1821 / 1598			
Wheelbase	mm	2670			
Track, front/rear	mm	1561 / 1562			
Ground clearance	mm	183			
	mm				
Fording depth	mm	250			
Turning circle	m opprovi itr	11.4			
Tank capacity	approx. ltr	51			
Engine oil 2) Weight, unladen, to DIN/EU	ltr	5.0			
	kg	1575 / 1650			
Max. load to DIN	kg	595			
Max. permissible weight	kg	2170			
Max. axle load, front/rear	kg	1130 / 1075			
Max. trailer load,	kg				
braked (12%)/unbraked		2000 / 750			
Max. roof load/towbar download	kg 	75 / 80			
Luggage comp. capacity	ltr	505 – 1550			
Air resistance	C _d x A	0.29 x 2.46			
Engine					
Config./No. of cyls./valves		in-line / 4 / 4			
Engine technology		BMW TwinPower Turbo technology: multi-stage high- and low-pressure			
		turbocharger with variable inlet geometry,			
		common rail direct injection with solenoid injectors, maximum injection			
		pressure 2500 bar			
Effective capacity	cm ³	1995			
Stroke/bore	mm	90.0 / 84.0			
Compression ratio	:1	16.5			
Fuel		diesel			
Output	kW/hp	170 / 231			
at	rpm	4400			
Torque	Nm	450			
at	rpm	1500 – 3000			
Electrical System					
Battery/Installation	Ah/–	80 / luggage comp.			
Alternator	A/W	150 / 2100			
	7.000	10072100			
Driving Dynamics and Safety					
Suspension, front		Single-joint spring-strut axle in lightweight aluminium-steel construction			
Suspension, rear	Multi-arm axle in lightweight steel construction with separate spring and				
, , , , , , , , , , , , , , , , , , , ,		damper configuration			
Brakes, front		Single-piston floating-calliper disc brakes / vented			
Brakes, rear		Single-piston floating-calliper disc brakes / vented			
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC			
	(Cornering Brake Control), DBC (Dynamic Brake Control), Dry Braking				
		function, Fading Compensation, Start-Off Assistant, EDLC (Electrically			
		Controlled Differential Lock Control), Performance Control, cross-linking			
		with xDrive all-wheel-drive system, optional: Dynamic Damper Control			
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and			
carety equipment		front passenger, head airbags for front and rear seats, three-point inertia-			
		reel seatbelts on all seats with belt latch tensioner and belt force limiter at			
		the front seats, crash sensors, Tyre Defect Indicator			
Steering		Electric Power Steering (EPS)			
		with Servotronic function, optional: Variable Sport Steering			
Steering ratio, overall	:1	15.7			
Tyres, front/rear		225/55 R17 97W			
Rims, front/rear		7.5J x 17 light-alloy			

06/2015

valid from 07/2015

		BMW X1 xDrive25d
Transmission		
Type of gearbox		8-speed Steptronic transmission
Gear ratios I	:1	5.250
	I :1	3.029
	II :1	1.950
	V :1	1.457
	V :1	1.221
	VI :1	1.000
1	VII :1	0.809
1	VIII :1	0.673
	₹ :1	4.015
Final drive	:1	2.955
Performance		
Power-to-weight ratio ([DIN) kg/kW	9.3
Output per litre	kW/ltr	85.2
Acceleration 0-100) km/h s	6.6
in 5th gear 80–12	20 km/h s	-
Top speed	km/h	235
- is a large and		

BMW EfficientDynamics

BMW EfficientDynamics standard features

Brake Energy Regeneration with recuperation display, EPS (Electric Power Steering), Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with coasting function, BMW EfficientLightweight, optimised aerodynamic attributes, on-demand operation of ancillary units, mapcontrolled oil pump, detachable a/c compressor, final drive with optimised warm-up behaviour, efficiency- and weight-optimised all-wheel drive, tyres with reduced roll resistance

Fuel consumption EU cycle ³⁾					
With standard tyres	-				
Urban	ltr/100 km	5.8			
Extra-urban	ltr/100 km	4.6			
Combined	ltr/100 km	5.0			
CO ₂	g/km	132			
With rims 8J x 19 and ty	yres 225/45 R19 as well as winter tyres				
Urban	ltr/100 km	5.9			
Extra-urban	ltr/100 km	4.8			
Combined	ltr/100 km	5.2			
CO ₂	g/km	137			
Emission rating	-	EU6			

Specifications apply to ACEA markets; data relevant to homologation applicable in part only to Germany (weight)

 $^{^{1)}}$ Height with roof fin: 1612 millimetres $^{2)}$ Oil change $^{3)}$ Fuel consumption and CO_2 emissions depend on the selected tyre format