BMW Media Information

5/2017

Valid from 7/2017

## Specifications. BMW 5 Series Sedan.

540d xDrive



|                                  |                    | BMW 540d xDrive Sedan   |
|----------------------------------|--------------------|---|
| Body                             |                    |   |
| No. of doors/seats               |                    | 4/5   |
| Length/width/height (unladen)    | mm                 | 4936 / 1868 / 1479  |
| Wheelbase                        | mm                 | 2975  |
| Front/rear track                 | mm                 | 1605 / 1630   |
| Ground clearance                 | mm                 | 139   |
| Turning circle                   | m                  | 12.22   |
| Fuel capacity                    | approx. I          | 66  |
| Engine oil capacity 1)           |                    | 6.5   |
| Weight, unladen (DIN/EU)         | kg                 | 1750 / 1825   |
| Payload (DIN)                    | kg                 | 690   |
| Permitted total weight           | kg                 | 2440  |
| Permitted axle load, front/rear  | kg                 | 1200 / 1325   |
| Permitted trailer load (12%)     |                    |   |
| braked/unbraked                  | kg                 | 2000 / 750  |
| Permitted roof load/trailer down | iload kg           | 100 / 90  |
| Luggage compartment capacity     | y l                | 530   |
| Aerodynamic drag                 | c <sub>x</sub> x A | 0.25 x 2.35   |
| Engine                           |                    |   |
| Type/no. of cylinders/valves     |                    | in-line / 6 / 4   |
| Engine technology                |                    | BMW TwinPower Turbo technology: multi-stage charging,   |
|                                  |                    | high and low pressure turbocharger with variable-geometry,  |
|                                  |                    | Common Rail direct injection with piezo injectors   |
|                                  |                    | (max. injection pressure: 2500 bar)   |
| Effective capacity               | CC                 | 2993  |
| Stroke/bore                      | mm                 | 90.0 / 84.0   |
| Compression ratio                | :1                 | 16.5  |
| Fuel type                        |                    | Diesel  |
| Output                           | kW/hp              | 235 / 320   |
| at rpm                           | min <sup>-1</sup>  | 4400  |
| Torque                           | Nm                 | 680   |
| at rpm                           | min-1              | 1750 – 2250   |
| Electrical                       |                    |   |
| Battery charge/location          | Ah/–               | 90 / luggage compartment  |
| Driving Dynamics and Safet       | y                  |   |
| Front suspension                 |                    | Aluminium double track control arm axle with separate lower track arm level,  |
|                                  |                    | small steering roll radius, traverse force compensation, anti-dive  |
| Rear suspension                  |                    | Five-link axle in aluminium lightweight construction, double elastic bearig   |
| Front brakes                     |                    | Four-piston fixed-calliper disc brakes / vented   |
| Rear brakes                      |                    | Single-piston floating-calliper disc brakes / vented  |
| Driving stability systems        | Š                  | Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering Brake Control), DBC (Dynamic Brake Control), Dry Braking function, Fading Compensation, Start-Off Assistant, linked to xDrive all-wheel drive; Optional: Dynamic Damper Control, Adaptive Drive          |
| Safety equipment                 |                    | Standard: driver and front-seat passenger airbags, driver and front-seat passenger side airbags, head airbags front and rear, three-point automatic seatbelts for all seats, seatbelt tensioners and seatbelt force limiters in front seats, crash sensors, tyre pressure indicator |
| Steering                         |                    | Electromechanical rack-and-pinion power steering (EPS);<br>optional: Integral Active Steering   |
| Overall steering ratio           | :1                 | optional: integral Active Steering  16.3  |
| Front/rear tyres                 |                    | 225/55 R17 97Y  |
| Front/rear wheels                |                    |   |
| 1 TOTILITE AL WITEELS            |                    | 7,5J x 17 light-alloy   |

5/2017

Valid from 7/2017

## **Specifications. BMW 5 Series Sedan.**

|   |  |  | BMW 540d xDrive Sedan  |
|---|--|--|--|
|   |  |  |  |
| Transmission  |  |  |  |
| Type of gearbo  |  |  | 8-speed Steptronic   |
| Gear ratios   | I  | :1                                       | 5.000  |
|   | ll ll  | :1                                       | 3.200  |
|   | III  | :1                                       | 2.143  |
|   | IV   | :1                                       | 1.720  |
|   | V  | :1                                       | 1.313  |
|   | VI   | :1                                       | 1.000  |
|   | VII  | :1                                       | 0.823  |
|   | VIII   | :1                                       | 0.640  |
|   | R  | :1                                       | 3.478  |
| Differential ratio  | 0  | :1                                       | 2.563  |
| Performance   |  |  |  |
| Weight-to-pow   | er ratio   |  |  |
| (DIN unladen)   |  | kg/kW                                    | 7.4  |
| Specific power  | output   | kW/l                                     | 78.5   |
| Acceleration  | 0–100 km/h   | sec                                      | 4.7  |
| in 5th gear   | 80-120 km/h  | sec                                      | -  |
| Max. speed  |  | km/h                                     | 250  |
| Features includ   | ded as standard  |  | (EPS), Auto Start Stop function, gear shift indicator, ECO PRO mode with coasting function an Proactive Driving Assistant, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, differential and power divider with optimized-warm-up behaviour, tyres with reduced rolling resistance,  BMW Blue Performance Technology |
| Fuel consum   | ption (EU) <sup>2)</sup>   |  |  |
| with standard v   | vheels and tyres,  | also with 8                              | BJ x 18 wheels and 245/45 R18 tyres  |
| Urban   | -  | l/100 km                                 | 6.4  |
| Extra-urban   |  | l/100 km                                 | 4.6  |
| Combined  |  | I/100 km                                 | 5.2  |
| CO <sub>2</sub> emissions   |  | g/km                                     | 138  |
| With 8J x 18 w<br>with 8J x 19 wl<br>with 8J x 19 wl<br>with 8J x 20 wl | heels (front), 9J x<br>heels an 245/40 F<br>heels (front), 9J x<br>heels (front), 9J x | 18 (rear) a<br>R19 tyres.<br>19 (rear) a | and 245/45 R18 tyres (front), 275/40 R18 (rear),<br>and 245/40 R19 tyres (front), 275/35 R19 (rear),<br>and 245/35 R20 tyres (front), 275/30 R20 (rear)  |
| and with runfla   | t tyres  |  |  |
| Urban   |  | I/100 km                                 | 6.5  |
| Extra-urban   |  | I/100 km                                 | 4.8  |
| Combined  |  | I/100 km                                 | 5.4  |
| CO <sub>2</sub> emissions   |  | g/km                                     | 143  |
| Mith winter to  | ••   |  |  |

6.6

5.0

5.6 147

EU6

 $Specifications\ apply\ to\ ACEA\ markets;\ data\ relevant\ to\ homologation\ applicable\ in\ part\ only\ to\ Germany\ (weight)$ 

With winter tyres Urban

Extra-urban

Combined

CO<sub>2</sub> emissions

Emissions standard

I/100 km

I/100 km

I/100 km

g/km

 $<sup>^{1)}</sup>$  Height including roof aerial  $^{2)}$  Oil change volume  $^{3)}$  Fuel consumption and CO $_{2}$  emissions depend on the selected tyre format