

Specifications.

The new BMW 3 Series Sedan.

M340d xDrive.



BMW M340d xDrive Sedan		
Body		
No of doors/seats		4 / 5
Length/width/height (unladen)	mm	4713 / 1827 / 1440
Wheelbase	mm	2851
Track, front/rear	mm	1583 / 1567
Ground clearance	mm	130
Turning circle	m	12.0
Fuel tank capacity	approx. l	59
Engine oil ¹⁾	l	7.0
Weight, unladen, to DIN/EU	kg	1820 / 1895
Max load to DIN	kg	505
Max permissible weight	kg	2325
Max axle load, front/rear	kg	1155 / 1255
Max trailer load, braked (12%/unbraked)	kg	1800 / 750
Max roofload/max towbar download	kg	75 / 75
Luggage comp capacity	l	480
Air resistance	C _d x A	0.26 x 2.22
Power Unit		
Config/No of cyls/valves		In-line / 6 / 4
Engine technology		BMW TwinPower Turbo technology: multi-stage charging, high and low pressure turbocharger with variable-geometry, Common Rail direct injection with piezo injectors (max. injection pressure: 2700 bar)
Effective capacity	cc	2993
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel		Diesel
Max output	kW/hp	250 / 340
at	rpm	4400
Max torque	Nm	700
at	rpm	1750 – 2250
48 V mild hybrid technology		
Max output	kW/hp	8 / 11
Electrical System		
12 V battery/installation	Ah/-	80 / luggage compartment
48 V battery/installation	Ah/-	11 / engine compartment
Driving Dynamics and Safety		
Suspension, front		Double-joint spring-strut axle in lightweight aluminium-steel construction with M specific elastokinematics, hydraulically damped torque strut bearings
Suspension, rear		Five-link axle in lightweight aluminium-steel construction with M specific elastokinematics
Brakes, front		Four piston fixed-calliper disc brakes, vented
Brakes, rear		Single-piston floating-calliper disc brakes, vented
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering Brake Control), DBC (Dynamic Brake Control), Performance Control, Dry Braking function, Fading Compensation, Start-Off Assistant, xDrive all-wheel-drive system networked with DSC, M Sport differential; optional: Adaptive M suspension
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags front and rear, three-point inertia-reel seatbelts for all seats, front seats with belt stopper, belt latch tensioner and belt force limiter, crash-active front head restraints, crash sensors, tyre pressure indicator
Steering		Electric Power Steering (EPS), variable sport steering with Servotronic function
Steering ratio, overall	:1	13.6
Tyres, front/rear		225/45 R18 95Y XL/ 255/40 R18 99Y XL
Rims, front/rear		7.5J x 18 light-alloy/ 8.5J x 18 light-alloy

BMW M340d xDrive Sedan

Transmission

Type of transmission	Eight-speed Steptronic transmission		
Gear ratios	I	:1	5.500
	II	:1	3.520
	III	:1	2.200
	IV	:1	1.720
	V	:1	1.317
	VI	:1	1.000
	VII	:1	0.823
	VIII	:1	0.640
	R	:1	3.993
Final drive		:1	2.563

Performance

Power-to-weight ratio (DIN)	kg/kW	7.3
Output per litre	kW/l	83.5
Acceleration 0–100 km/h	s	4.6
Top speed	km/h	250

BMW EfficientDynamics

BMW EfficientDynamics standard features	Mild hybrid technology with 48 volt starter generator, Brake Energy Regeneration with recuperation display, Auto Start Stop function, ECO PRO and COMFORT mode with coasting function, Proactive Driving Assistant. Optimum Shift Indicator, Electric Power Steering (EPS), BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, efficiency-optimised all-wheel drive, differential with optimised warm-up behaviour, tyres with reduced rolling resistance, BMW Blue Performance technology including SCR catalytic converter
---	--

Fuel Consumption ECE

Urban	l/100 km	7.7 – 7.3
Extra-urban	l/100 km	4.5 – 4.2
Combined	l/100 km	5.7 – 5.3
CO ₂	g/km	149 – 139
Emission rating		Euro 6d

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

¹⁾ Oil change

The values for fuel consumption, CO₂ emission and energy consumption shown were determined in the standardized test cycle according to the European Regulation (EC) 715/2007 in the version applicable at the time of type approval. The figures refer to a vehicle with basic configuration in Germany and the range shown considers optional equipment and the different size of wheels and tires available on the selected model and may vary during the configuration.

The values are already based on the test cycle according to the new WLTP regulation and are translated back into NEDC-equivalent values in order to allow a comparison between vehicles. With respect to these vehicles, for vehicle related taxes or other duties based (at least inter alia) on CO₂-emissions the CO₂ values may differ to the values stated here.