

Specifications.

BMW X6.

X6 xDrive30d.



BMW X6 xDrive30d		
Body		
No of doors/seats		5 / 5
Length/width/height (unladen)	mm	4935 / 2004 / 1696
Wheelbase	mm	2975
Track, front/rear	mm	1678 / 1688
Turning circle	m	12.6
Fuel tank capacity	approx. l	80
Engine oil ¹⁾	l	7.0
Weight, unladen, to DIN/EU	kg	2185 / 2260
Max load to DIN	kg	755
Max permissible weight	kg	2940
Max axle load, front/rear	kg	1360 / 1635
Max trailer load, braked (12%)/unbraked	kg	3500 / 750
Max roofload/max towbar download	kg	100 / 140
Luggage comp capacity	l	580 – 1530
Air resistance	c _d x A	0.32 x 2.83
Power Unit		
Config/No of cyls/valves		In-line / 6 / 4
Engine technology		BMW TwinPower Turbo technology: multi-stage turbocharging, low-pressure turbocharger with variable inlet geometry, common-rail direct injection with piezo injectors (max. injection pressure: 2700 bar)
Effective capacity	cc	2993
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel		Diesel
Max output	kW/hp	210 / 286
at	rpm	4000
Max torque	Nm	650
at	rpm	1500 – 2500
48V mild hybrid technology output	kW/hp	8 / 11
Electrical System		
12V battery/installation	Ah/–	90 / luggage compartment
48V battery/installation	Ah/–	11 / engine compartment
Driving Dynamics and Safety		
Suspension, front		Double-wishbone axle in aluminium construction; optional: air suspension with automatic self-levelling
Suspension, rear		Five-link axle in lightweight steel construction; optional: air suspension with automatic self-levelling
Brakes, front		Single-piston fixed-calliper disc brakes, vented
Brakes, rear		Single-piston floating-calliper disc brakes, vented
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering Brake Control), DBC (Dynamic Brake Control), Dry Braking function, Fading Compensation, Start-Off Assistant, DSC networked with xDrive all-wheel-drive system, ADB-X (Active Differential Brake), HDC (Hill Descent Control), Adaptive suspension; optional: active roll stabilisation, electronically controlled rear differential lock
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia-reel seatbelts on all seats with belt stopper, belt latch tensioner and belt force limiter in the front, crash sensors, tyre pressure indicator
Steering		Electric Power Steering (EPS); optional: Integral Active Steering
Steering ratio, overall	:1	18.7
Tyres, front/rear		265/50 R19 110W XL
Rims, front/rear		9J x 19 light-alloy

BMW X6 xDrive30d			
Transmission			
Type of transmission		Eight-speed Steptronic transmission	
Gear ratios	I	:1	5.500
	II	:1	3.520
	III	:1	2.200
	IV	:1	1.720
	V	:1	1.317
	VI	:1	1.000
	VII	:1	0.823
	VIII	:1	0.640
	R	:1	3.993
Final drive		:1	2.929
Performance			
Power-to-weight ratio (DIN)	kg/kW		10.4
Output per litre	kW/l		70.2
Acceleration 0–100 km/h	s		6.1
Top speed	km/h		235
Off-road characteristics			
Angle of approach/departure	°	25.1 / 21.7	
Breakover angle	°	17.9	
Ground clearance when unladen	mm	216	
Fording depth (at 7 km/h)	mm	500	
BMW EfficientDynamics			
BMW EfficientDynamics standard features	Mild hybrid technology with 48V starter-generator, Brake Energy Regeneration with recuperation display, Auto Start Stop function, ECO PRO and COMFORT mode with coasting function, Proactive Driving Assistant, Optimum Shift Indicator, Electric Power Steering, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, efficiency-optimised all-wheel drive, differential with optimised warm-up behaviour, tyres with reduced rolling resistance, BMW Blue Performance technology with SCR catalytic converter		
Fuel Consumption ECE			
Urban	l/100 km	7.2 – 6.7	
Extra-urban	l/100 km	5.6 – 5.1	
Combined	l/100 km	6.2 – 5.7	
CO ₂	g/km	162 – 149	
Emission rating		Euro 6d	

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

¹⁾ Oil change

The values for fuel consumption, CO₂ emission and energy consumption shown were determined in the standardized test cycle according to the European Regulation (EC) 715/2007 in the version applicable at the time of type approval. The figures refer to a vehicle with basic configuration in Germany and the range shown considers optional equipment and the different size of wheels and tires available on the selected model and may vary during the configuration.

The values are already based on the test cycle according to the new WLTP regulation and are translated back into NEDC-equivalent values in order to allow a comparison between vehicles. With respect to these vehicles, for vehicle related taxes or other duties based (at least inter alia) on CO₂-emissions the CO₂ values may differ to the values stated here.