BMW Media Information 11/2020 Page 1

Specifications. BMW 2 Series Coupe.218i.



		BMW 218i Coupe
Body		
No. of doors/seats		2/4
Length/width/height 1) (unladen)	mm	4432 / 1774 / 1418
Wheelbase	mm	2690
Track, front/rear	mm	1521 / 1556
Ground clearance	mm	140
Turning circle	m	10.9
Tank capacity	approx. ltr	52
Engine oil 2)	ltr	5.25
Weight, unladen, to DIN/EU	kg	1415 / 1490 (1435 / 1510)
Max. load to DIN	kg	515 (475)
Max. permissible weight	kg	1930 (1910)
Max. axle load, front/rear	kg	920 / 1075
Max. trailer load,	kg	3237 1070
braked (12%)/unbraked	'\9	1500 / 745 (750)
Max. roof load/towbar download	kg	75/75
Luggage comp. capacity	ltr	390
Air resistance	C _d x A	0.29 x 2.14
7 11 10010101100	OU X 7 Y	OLEO X ETT
Engine		
Config./No. of cyls./valves		in-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology: turbocharger,
0		High Precision Injection, VALVETRONIC fully variable valve timing,
		Double-VANOS variable camshaft timing
Effective capacity	cm ³	1998
Stroke/bore	mm	94.6 / 82.0
Compression ratio	:1	11.0
Fuel		min RON 91
Output	kW/hp	100 / 136
at	rpm	4400 – 6000
Torque	Nm	220
at	rpm	1350 – 4300
Floatsiaal Contains		
Electrical System	Ah/-	00/1
Battery/Installation	An-	80 / luggage comp.
Driving Dynamics and Safety		
Suspension, front		Aluminium double-joint spring strut axle
Suspension, rear		Five-link axle in lightweight steel construction with double elastic bearing
Brakes, front		Single-piston floating-calliper disc brakes
Brakes, rear		Single-piston floating-calliper disc brakes
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control),
3		CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying
		function, fading compensation, start-off assistant; optional: M Sport
		suspension, adaptive suspension
Safety equipment	(Standard: airbags for driver and front passenger, side airbags for driver and
,		front passenger, head airbags for front and rear seats, three-point inertia-
		reel seatbelts on all seats with belt latch tensioner and belt force limiter at
		the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electromechanical rack-and-pinion power steering (EPS)
		with Servotronic function; optional: Variable Sport Steering
Steering ratio, overall	:1	15.0
Tyres, front/rear		205/55 R16 91W
Rims, front/rear		7J x 16 light-alloy

			BMW 218i Coupe
			•
Transmission	•		
Type of gearbo	X		6-speed manual (8-speed Steptronic transmission)
Gear ratios	l	:1	4.002 (5.000)
	II	:1	2.130 (3.200)
	III	:1	1.395 (2.143)
	IV	:1	1.000 (1.720)
	V	:1	0.780 (1.314)
	VI	:1	0.668 (1.000)
	VII	:1	- (0.822)
	VIII	:1	- (0.640)
	R	:1	3.647 (3.456)
Final drive		:1	2.813 (3.077)
Performance			
Power-to-weig	ht ratio (DIN)	kg/kW	14.2 (14.4)
Output per litre)	kW/l	50.0
Acceleration	0-100 km/h	S	8.8 (8.9)
in 5 th gear	80-120 km/h	S	11.2 (–)
Top speed		km/h	210 (210)
BMW Efficien	ntDynamics		
BMW EfficientI	Dynamics		Brake Energy Regeneration with recuperation display, EPS (Electric Power
standard featur	res		Steering), Auto Start Stop function, Optimum Shift Indicator, ECO PRO
			mode with coasting function (automatic), BMW EfficientLightweight,
			optimised aerodynamic attributes, on-demand operation of ancillary units,
			map-controlled oil pump, detachable a/c compressor, differential with
			optimized-warm-up behaviour, tyres with reduced rolling resistance
	ption EU cycle	1. (4.00.1	0.0 0.4 (7.4 7.0)
Urban		ltr/100 km	9.2 – 9.1 (7.4 – 7.3)
Extra-urban		ltr/100 km	5.7 – 5.5 (5.3 – 5.2)
Combined		Itr/100 km	7.0 – 6.8 (6.1 – 6.0)
CO ₂ Emission ratino	,	g/km	160 – 157 (140 – 137) Euro 6d
	4		⊑ui0 ou

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight) Figures in brackets are for vehicles with automatic transmission

The values for fuel consumption, CO_2 emission and energy consumption shown were determined in the standardized test cycle according to the European Regulation (EC) 715/2007 in the version applicable at the time of type approval. The figures refer to a vehicle with basic configuration in Germany and the range shown considers optional equipment and the different size of wheels and tires available on the selected model and may vary during the configuration.

¹⁾ Height including roof aerial ²⁾ Oil change volume

BMW 2 Series Coupe. 220i.

11/2020
Page 3

		BMW 220i Coupe
		·
Body		
No. of doors/seats		2/4
Length/width/height 1) (unladen)	mm	4432 / 1774 / 1418
Wheelbase	mm	2690
Track, front/rear	mm	1521 / 1556
Ground clearance	mm	140
Turning circle	m	10.9
Tank capacity	approx. ltr	52
Engine oil 2)	ltr	5.25
Weight, unladen, to DIN/EU	kg	1440 / 1515
Max. load to DIN	kg	470
Max. permissible weight	kg	1910
Max. axle load, front/rear	kg	920 / 1075
Max. trailer load,	kg	
braked (12%)/unbraked		1500 / 750
Max. roof load/towbar download	kg	75 / 75
Luggage comp. capacity	ltr	390
Air resistance	c _d x A	0.28 x 2.14
Engine		
Config./No. of cyls./valves		in-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology: twin scroll turbocharger, High Precision Injection, VALVETRONIC fully variable valve timing, Double-VANOS variable camshaft timing
Effective capacity	cm ³	1998
Stroke/bore	mm	94.6 / 82.0
Compression ratio	:1	11.0
Fuel		min RON 91
Output	kW/hp	135 / 184
at	rpm	5000 – 6500
Torque	Nm	270
at	rpm	1350 – 4600
at	тріті	1030 - 4000
Electrical System		
Battery/Installation	Ah/-	80 / luggage comp.
Datterymistaliation	7-1111	oo naggage comp.
Driving Dynamics and Safety		
Suspension, front		Aluminium double-joint spring strut axle
Suspension, rear		Five-link axle in lightweight steel construction with double elastic bearing
Brakes, front		Single-piston floating-calliper disc brakes
Brakes, rear		Single-piston floating-calliper disc brakes
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control),
		CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, start-off assistant; optional: M Sport suspension, adaptive suspension
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and
carety equipment		front passenger, head airbags for front and rear seats, three-point inertia- reel seatbelts on all seats with belt latch tensioner and belt force limiter at the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electromechanical rack-and-pinion power steering (EPS) with Servotronic function; optional: Variable Sport Steering
Steering ratio, overall	:1	15.0
Tyres, front/rear		205/55 R16 91W
Rims, front/rear		7J x 16 light-alloy

			BMW 220i Coupe
Transmission			
Type of gearbox			8-speed Steptronic transmission
Gear ratios	I	:1	5.000
	II	:1	3.200
	III	:1	2.143
	IV	:1	1.720
	V	:1	1.314
	VI	:1	1.000
	VII	:1	0.822
	VIII	:1	0.640
	R	:1	3.456
Final drive		:1	2.813
Performance			
Power-to-weight ratio (C	DIN)	kg/kW	10.7
Output per litre		kW/l	67.6
Acceleration 0–100	km/h	S	7.2
Top speed		km/h	230

BMW EfficientDynamics

BMW EfficientDynamics standard features

Brake Energy Regeneration with recuperation display, EPS (Electric Power Steering), Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with coasting function, BMW EfficientLightweight, optimised aerodynamic attributes, on-demand operation of ancillary units, mapcontrolled oil pump, detachable a/c compressor, differential with optimizedwarm-up behaviour, tyres with reduced rolling resistance

Fuel consumption El	J cycle		
Urban	ltr/100 km	7.5 – 7.4	
Extra-urban	ltr/100 km	5.2 – 5.0	
Combined	ltr/100 km	6.0 – 5.9	
CO ₂	g/km	139 – 136	
Emission rating		Euro 6d	

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

The values for fuel consumption, CO_2 emission and energy consumption shown were determined in the standardized test cycle according to the European Regulation (EC) 715/2007 in the version applicable at the time of type approval. The figures refer to a vehicle with basic configuration in Germany and the range shown considers optional equipment and the different size of wheels and tires available on the selected model and may vary during the configuration.

¹⁾ Height including roof aerial ²⁾ Oil change volume

11/2020 Page 5

BMW 2 Series Coupe. 230i.

		BMW 230i Coupe
		Divive 2501 Coupe
Body		
No. of doors/seats		2/4
Length/width/height 1) (unladen)	mm	4432 / 1774 / 1418
Wheelbase	mm	2690
Track, front/rear	mm	1521 / 1556
Ground clearance	mm	140
Turning circle	m	10.9
Tank capacity	approx. Itr	52
Engine oil 2)	ltr	5.25
Weight, unladen, to DIN/EU	kg	1465 / 1540
Max. load to DIN	kg	470
Max. permissible weight	kg	1935
Max. axle load, front/rear	kg	920 / 1075
Max. trailer load,	kg	
braked (12%)/unbraked		1500 / 750
Max. roof load/towbar download	kg	75 / 75
Luggage comp. capacity	ltr	390
Air resistance	c _d x A	0.29 x 2.14
Engine		
Engine Config./No. of cyls./valves		in-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology: twin scroll turbocharger,
Engine technology		High Precision Injection, VALVETRONIC fully variable valve timing, Double-VANOS variable camshaft timing
Effective capacity	cm ³	1998
Stroke/bore	mm	94.6 / 82.0
Compression ratio	:1	10.2
Fuel		min RON 91
Output	kW/hp	185 / 252
at	rpm	5200 - 6500
Torque	Nm	350
at	rpm	1450 – 4800
Electrical System		
Battery/Installation	Ah/–	80 / luggage comp.
Driving Dynamics and Safaty		
Driving Dynamics and Safety Suspension, front		Aluminium double-joint spring strut axle
Suspension, rear		Five-link axle in lightweight steel construction with double elastic bearing
Brakes, front		Single-piston floating-calliper disc brakes
Brakes, rear		Single-piston floating-calliper disc brakes
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control),
Driving stability systems		CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, start-off assistant; optional: M Sport suspension, adaptive suspension
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and
y4		front passenger, head airbags for front and rear seats, three-point inertia- reel seatbelts on all seats with belt latch tensioner and belt force limiter at the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electromechanical rack-and-pinion power steering (EPS) with Servotronic function; optional: Variable Sport Steering
Steering ratio, overall	:1	15.0
Tyres, front/rear		205/50 R17 89Y
Rims, front/rear		7J x 17 light-alloy

			BMW 230i Coupe
Transmission	n		
Type of gearbo	OX		8-speed Steptronic Sport transmission
Gear ratios		:1	5.000
	II	:1	3.200
	III	:1	2.143
	IV	:1	1.720
	V	:1	1.314
	VI	:1	1.000
	VII	:1	0.822
	VIII	:1	0.640
	R	:1	3.456
Final drive		:1	2.813
Performance	!		
Power-to-weig	ht ratio (DIN)	kg/kW	7.9
Output per litre	Э	kW/l	92.6
Acceleration	0–100 km/h	S	5.6
Top speed		km/h	250
BMW Efficier	ntDynamics		
BMW Efficient	Dynamics	Е	Brake Energy Regeneration with recuperation display, EPS (Electric Power
standard featu	res		Steering), Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with coasting function, BMW EfficientLightweight, optimised aerodynamic attributes, on-demand operation of ancillary units, map-

controlled oil pump, detachable a/c compressor, differential with optimizedwarm-up behaviour, tyres with reduced rolling resistance Fuel consumption EU cycle ltr/100 km 7.6 ltr/100 km 5.2

Urban Extra-urban Combined Itr/100 km 6.1 CO₂ 140 g/km **Emission rating** Euro 6d

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

The values for fuel consumption, CO_2 emission and energy consumption shown were determined in the standardized test cycle according to the European Regulation (EC) 715/2007 in the version applicable at the time of type approval. The figures refer to a vehicle with basic configuration in Germany and the range shown considers optional equipment and the different size of wheels and tires available on the selected model and may vary during the configuration.

¹⁾ Height including roof aerial ²⁾ Oil change volume

BMW 2 Series Coupe. M240i.

		BMW M240i Coupe
Body		2/4
No. of doors/seats Length/width/height 1) (unladen)	mm	4454 / 1774 / 1408
Wheelbase		2690
Track, front/rear	mm mm	1516 / 1534
Ground clearance	mm	130
Turning circle	m	10.9
Tank capacity	approx. ltr	52
Engine oil 2)	ltr	6.5
Weight, unladen, to DIN/EU	kg	1525 / 1600
Max. load to DIN	kg	470
Max. permissible weight	kg	1995
Max. axle load, front/rear	kg	975 / 1075
Max. trailer load,	kg	3737 1073
braked (12%)/unbraked	Ng	-1-
Max. roof load/towbar download	kg	 75 <i>I</i> –
Luggage comp. capacity	ltr	390
Air resistance	C _d x A	0.32 x 2.14
Engine Config./No. of cyls./valves		in-line / 6 / 4
Engine technology		BMW TwinPower Turbo technology: twin scroll turbocharger, High Precision Injection, VALVETRONIC fully variable valve timing,
		Double-VANOS variable camshaft timing
Effective capacity	cm ³	2998
Stroke/bore	mm	94.6 / 82.0
Compression ratio	:1	11.0
Fuel	.1	min RON 91
Output	kW/hp	250 / 340
at	rpm	5500 – 6500
Torque	Nm	500
at	rpm	1550 – 4500
	трпп	1000 1000
Electrical System		
Battery/Installation	Ah/–	80 / luggage comp.
Driving Dynamics and Safety		
Suspension, front		Aluminium double-joint spring strut axle with M-specific elastokinematics
Suspension, rear		Five-link axle in lightweight steel construction with double elastic bearing
Brakes, front		Four-piston fixed-calliper disc brakes
Brakes, rear		Two-piston fixed-calliper disc brakes
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control),
3 3 3		CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying
		function, fading compensation, start-off assistant, M Sport suspension;
		optional: adaptive suspension
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and
		front passenger, head airbags for front and rear seats, three-point inertia-
		reel seatbelts on all seats with belt latch tensioner and belt force limiter at
		the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electromechanical rack-and-pinion power steering (EPS);
Steering ratio, overall	:1	Variable Sport Steering 14.5
Tyres, front/rear	.1	225/40 ZR18 88Y/
i yres, ironureai		245/35 ZR 18 92Y XL
Rims, front/rear		7.5J x 18 light-alloy/
», ·· -··		8J x 18 light-alloy

-			BMW M240i Coupe
Transmission	1		
Type of gearbo	X		8-speed Steptronic Sport transmission
Gear ratios		:1	5.000
	II	:1	3.200
	III	:1	2.143
	IV	:1	1.720
	V	:1	1.314
	VI	:1	1.000
	VII	:1	0.822
	VIII	:1	0.640
	R	:1	3.456
Final drive		:1	2.813
Performance			
Power-to-weigh	ht ratio (DIN)	kg/kW	6.1
Output per litre	!	kW/l	83.4
Acceleration	0-100 km/h	S	4.6
Top speed		km/h	250
BMW Efficien	tDynamics		
BMW Efficient[Dynamics	E	Brake Energy Regeneration with recuperation display, EPS (Electric Power
standard feature	es		Steering), Auto Start Stop function, Optimum Shift Indicator, ECO PRO
			mode with coasting function, BMW EfficientLightweight, optimised
			aerodynamic attributes, on-demand operation of ancillary units, map-
			controlled oil pump, differential with optimized-warm-up behaviour
Fuel consump	otion EU cycle		
Urban		ltr/100 km	9.6
Extra-urban		ltr/100 km	6.0
Combined		ltr/100 km	7.3
CO ₂		g/km	168
Emission rating			Euro 6d

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

The values for fuel consumption, CO_2 emission and energy consumption shown were determined in the standardized test cycle according to the European Regulation (EC) 715/2007 in the version applicable at the time of type approval. The figures refer to a vehicle with basic configuration in Germany and the range shown considers optional equipment and the different size of wheels and tires available on the selected model and may vary during the configuration.

¹⁾ Height including roof aerial ²⁾ Oil change volume