BMW Media Information

03/2021 Page 1

Specifications. BMW 8 Series Gran Coupe. 840i.



		BMW 840i Gran Coupe	
Body			
No. of doors/seats		4/5	
Length/width/height (unladen)	mm	5074 / 1932 / 1401	
Wheelbase	mm	3023	
Track, front/rear	mm	1627 / 1671	
Ground clearance	mm	121	
Turning circle	m	12.3	
Tank capacity	approx. ltr	68	
Engine oil 1)	Itr	6.5	
Weight, unladen, to DIN/EU	kg	1815 / 1890	
Max. load to DIN	kg	620	
Max. permissible weight	kg	2435	
Max. axle load, front/rear	kg	1170 / 1360	
Max. trailer load,	Ng Ng	117071300	
braked (12%)/unbraked	ka	- <i>I</i> -	
Max. roof load/towbar download	kg		
	kg Itr	440	
Luggage comp. capacity Air resistance		0.29 x 2.31	
Air resistance	c _d x A	0.29 X 2.31	
Engine			
Config./No. of cyls./valves		in-line / 6 / 4	
Engine technology		BMW TwinPower Turbo technology: twin scroll turbocharger, High Precision Injection, VALVETRONIC fully variable valve timing, Double-VANOS variable camshaft timing	
Effective capacity	cm ³	2998	
Stroke/bore	mm	94.6 / 82.0	
Compression ratio	:1	11.0	
Fuel	•••	min RON 91	
Output	kW/hp	245 / 333	
at	rpm	5500 – 6250	
Torque	Nm	500	
at	rpm	1700 – 4000	
Electrical System	• • • • • • • • • • • • • • • • • • • •	20.00	
Battery/Installation	Ah/–	90 / luggage comp.	
Driving Dynamics and Safety			
Suspension, front		Double-wishbone axle in aluminium construction with separate lower track	
		arm and specific elastokinematics	
Suspension, rear		Five-link axle in aluminium/steel lightweight construction with dual elastic bearing and specific elastokinematics	
Brakes, front		Four-piston fixed-calliper disc brakes / vented	
Brakes, rear		Single-piston floating-calliper disc brakes / vented	
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control),	
Driving stability systems		CBC Cornering Brake Control, DBC Dynamic Brake Control, Dry Braking	
		function, fading compensation, start-off assistant, Adaptive Suspension,	
		M Sport differential; optional: active roll stabilisation	
Safety equipment	Ç	Standard: airbags for driver and front passenger, side airbags for driver and	
carety equipment		front passenger, head airbags for front and rear seats, three-point inertia-	
	reel seatbelts on all seats with belt stopper, belt latch tensioner and belt		
		force limiter at the front seats, crash sensors, Tyre Pressure Indicator	
Steering		Electromechanical rack-and-pinion power steering (EPS)	
C.C.C.III.Ig		with Servotronic function; optional: Integral Active Steering	
Steering ratio, overall	:1	16.9	
Tyres, front/rear		245/45 R18 100Y XL/	
- 1		275/40 R18 103Y XL	
		·	
Rims, front/rear		8J x 18 light-alloy /	

			BMW 840i Gran Coupe
Transmission			
Type of gearbox			8-speed Steptronic
Gear ratios		:1	5,250
	II	:1	3.360
	III	:1	2.172
	IV	:1	1.720
	V	:1	1.316
	VI	:1	1.000
	VII	:1	0.822
	VIII	:1	0.640
	R	:1	3.712
Final drive		:1	2.929
Performance			
Power-to-weight ra	atio (DIN)	kg/kW	7.4
Output per litre	, ,	kW/l	81.7
Acceleration 0	–100 km/h	S	5.4
Top speed		km/h	250
BMW EfficientDy	namics		
BMW EfficientDyna	amics		Brake Energy Regeneration with recuperation display, EPS (Electric Power
standard features			Steering), Auto Start Stop function, Optimum Shift Indicator,
			ECO PRO and COMFORT mode with coasting function, Proactive Driving
			Assistant, BMW EfficientLightweight, optimised aerodynamic attributes,
			active air flap control, on-demand operation of ancillary units, map-
			controlled oil pump, differential with optimized-warm-up behavior
Fuel consumptio	n EU cycle	Itr/100 km	0.7. 0.4
Urban (NEDC)	\		9.7 – 9.4
Extra-urban (NEDC) Combined (NEDC)		ltr/100 km	6.1 – 5.9 7.4 – 7.2
Combined (NEDC)		Itr/100 km	8.7 – 8.2
CO ₂ (NEDC)		g/km	8.7 - 8.2 171 - 166
		g/km	1/1 - 100

199 – 186

Euro 6d

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

g/km

CO₂ (WLTP)

¹⁾ Oil change volume

BMW 8 Series Gran Coupe. 840i xDrive.

03/20)21
Page	3
	_

		BMW 840i xDrive Gran Coupe
Pody		
Body No. of doors/seats		4/5
Length/width/height (unladen)	mm	5074 / 1932 / 1401
Wheelbase	mm	3023
Track, front/rear		1627 / 1671
Ground clearance	mm	121
Turning circle	mm	12.6
	m opprovi itr	68
Tank capacity Engine oil 1)	approx. ltr	6.5
	ltr.	
Weight, unladen, to DIN/EU	kg	1875 / 1950
Max. load to DIN	kg	605
Max. permissible weight	kg	2480
Max. axle load, front/rear	kg	1220 / 1355
Max. trailer load,		
braked (12%)/unbraked	kg	-/-
Max. roof load/towbar download	kg	75 / –
Luggage comp. capacity	ltr	440
Air resistance	c _d x A	0.29 x 2.31
Engine		
Config./No. of cyls./valves		in-line / 6 / 4
Engine technology		BMW TwinPower Turbo technology: twin scroll turbocharger,
3 0,		High Precision Injection, VALVETRONIC fully variable valve timing,
		Double-VANOS variable camshaft timing
Effective capacity	cm ³	2998
Stroke/bore	mm	94.6 / 82.0
Compression ratio	:1	11.0
Fuel		min RON 91
Output	kW/hp	245 / 333
at	rpm	5500 - 6250
Torque	Nm	500
at	rpm	1700 – 4000
Electrical System		
Battery/Installation	Ah/–	90 / luggage comp.
D		
Driving Dynamics and Safety		Devide with a second in the second se
Suspension, front		Double-wishbone axle in aluminium construction with separate lower track arm and specific elastokinematics
Suspension, rear		Five-link axle in aluminium/steel lightweight construction with dual elastic bearing and specific elastokinematics
Brakes, front		Four-piston fixed-calliper disc brakes / vented
Brakes, rear		Single-piston floating-calliper disc brakes / vented
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC
		(Cornering Brake Control), DBC (Dynamic Brake Control), Dry Braking
		function, fading compensation, Start-Off Assistant, DSC linked with xDrive
		all-wheel drive, Adaptive Suspension; optional: M Sport differential, active
		roll stabilisation
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and
		front passenger, head airbags for front and rear seats, three-point inertia-
		reel seatbelts on all seats with belt stopper, belt latch tensioner and belt
		force limiter at the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electromechanical rack-and-pinion power steering (EPS)
		with Servotronic function, Integral Active Steering
Steering ratio, overall	:1	16.4
Tyres, front/rear		245/45 R18 100Y XL/
		275/40 R18 103Y XL
Rims, front/rear		8J x 18 light-alloy /
		9J x 18 light-alloy

		BMW 840i xDrive Gran Coupe
Transmission		
Type of gearbox		8-speed Steptronic
Gear ratios I	:1	5.250
	II :1	3.360
	III :1	2.172
	IV :1	1.720
	V :1	1.316
	VI :1	1.000
	VII :1	0.822
	VIII :1	0.640
	R :1	3.712
Final drive	:1	2.929
Performance		
Power-to-weight ratio (DIN)	kg/kW	7.7
Output per litre	kW/l	81.7
Acceleration 0–100 km/l	n s	5.1
Top speed	km/h	250

BMW EfficientDynamics

BMW EfficientDynamics standard features

Brake Energy Regeneration with recuperation display, EPS (Electric Power Steering), Auto Start Stop function, Optimum Shift Indicator, ECO PRO and COMFORT mode with coasting function, Proactive Driving Assistant, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, automatic rear spoiler, on-demand operation of ancillary units, map-controlled oil pump, efficiency-optimised all-wheel drive, differential with optimized-warm-up behaviour

Fuel consumption EU cy	/cle		
Urban (NEDC)	ltr/100 km	10.0 – 9.6	
Extra-urban (NEDC)	ltr/100 km	6.6 – 6.5	
Combined (NEDC)	ltr/100 km	7.8 – 7.6	
Combined (WLTP)	ltr/100 km	9.1 – 8.6	
CO ₂ (NEDC)	g/km	180 – 175	
CO ₂ (WLTP)	g/km	209 – 197	
Emission rating		Euro 6d	

 $Specifications\ apply\ to\ ACEA\ markets/data\ relevant\ to\ homologation\ applies\ in\ part\ only\ to\ Germany\ (weight)$

¹⁾ Oil change volume

BMW 8 Series Gran Coupe. M850i xDrive.

		BMW M850i xDrive Gran Coupe
Body No. of doors/seats		4/5
Length/width/height (unladen)	mm	5082 / 1932 / 1407
Wheelbase	mm	3023
Track, front/rear	mm mm	1627 / 1671
Ground clearance	mm	128
Turning circle	m	12.6
Tank capacity	approx. ltr	68
Engine oil 1)	ltr	10.5
Weight, unladen, to DIN/EU	kg	2010 / 2085
Max. load to DIN	kg	590
Max. permissible weight	kg	2600
Max. axle load, front/rear		1300 / 1390
Max. trailer load,	kg	13007 1390
braked (12%)/unbraked	ka	-1-
Max. roof load/towbar download	kg kg	
		440
Luggage comp. capacity Air resistance	ltr c _d x A	0.32 x 2.31
Air resistance	Cd X A	0.32 X 2.3 I
Engine		
Config./No. of cyls./valves		V/8/4
Engine technology		BMW TwinPower Turbo technology: two twin scroll turbochargers, High Precision Injection, VALVETRONIC fully variable valve timing, Double-VANOS variable camshaft timing
Effective capacity	cm ³	4395
Stroke/bore	mm	88,3 / 89,0
	:1	10.5
Compression ratio Fuel		
	Id///bp	min RON 91 390 / 530
Output	kW/hp	
at	rpm	5500 – 6000
Torque at	Nm rpm	750 1800 – 4600
Electrical System		
Battery/Installation	Ah/–	90 / luggage comp.
Driving Dynamics and Safety		
Suspension, front	Г	Double-wishbone axle in aluminium construction with separate lower track
		arm and specific elastokinematics
Suspension, rear		Five-link axle in aluminium/steel lightweight construction with dual elastic
		bearing and specific elastokinematics
Brakes, front		Four-piston fixed-calliper disc brakes / vented
Brakes, rear		Single-piston floating-calliper disc brakes / vented
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC
		(Cornering Brake Control), DBC (Dynamic Brake Control), Dry Braking
	f	unction, fading compensation, Start-Off Assistant, DSC linked with xDrive
	al	I-wheel drive, Adaptive M Suspension, M Sport differential; optional: active
		roll stabilisation
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and
	1	front passenger, head airbags for front and rear seats, three-point inertia-
		reel seatbelts on all seats with belt stopper, belt latch tensioner and belt
		force limiter at the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electromechanical rack-and-pinion power steering (EPS)
		with Servotronic function, Integral Active Steering
Steering ratio, overall	:1	16.4
Tyres, front/rear		245/35 R20 95Y XL/
		275/30 R20 97Y XL
Rims, front/rear		8J x 20 light-alloy /
		9J x 20 light-alloy

		BMW M850i xDrive Gran Coupe
 Transmission		
Type of gearbox		8-speed Steptronic
Gear ratios I	:1	5.500
II	:1	3.520
III	:1	2.200
IV	:1	1.720
V	:1	1.317
VI	:1	1.000
VII	:1	0.823
VIII	:1	0.640
R	:1	3.993
Final drive	:1	2.813
Performance		
Power-to-weight ratio (DIN)	kg/kW	5.2
Output per litre	kW/l	88.7
Acceleration 0–100 km/h	S	3.9
Top speed	km/h	250
BMW EfficientDynamics		
DAMA/ Efficient Damaria	D.J.E.	December 21 - 21 - 22 - 23 - 25 - 25 - 25 - 25 - 25 - 25

BMW EfficientDynamics standard features

Brake Energy Regeneration with recuperation display, EPS (Electric Power Steering), Auto Start Stop function, Optimum Shift Indicator, ECO PRO and COMFORT mode with coasting function, Proactive Driving Assistant, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, automatic rear spoiler, on-demand operation of ancillary units, map-controlled oil pump, efficiency-optimised all-wheel drive, differential with optimized-warm-up behaviour

Fuel consumption EU cy	/cle		
Urban (NEDC)	ltr/100 km	14.3 – 14.1	
Extra-urban (NEDC)	ltr/100 km	7.8 – 7.7	
Combined (NEDC)	ltr/100 km	10.2 – 10.1	
Combined (WLTP)	ltr/100 km	11.0 – 10.9	
CO ₂ (NEDC)	g/km	234 – 232	
CO ₂ (WLTP)	g/km	252 – 248	
Emission rating		Euro 6d	

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

¹⁾ Oil change volume

BMW 8 Series Gran Coupe. 840d xDrive.

		BMW 840d xDrive Gran Coupe
Body		
No. of doors/seats		4/5
Length/width/height (unladen)	mm	5074 / 1932 / 1401
Wheelbase	mm	3023
Track, front/rear	mm	1627 / 1671
Ground clearance	mm	121
Turning circle	m	12.6
Tank capacity	approx. ltr	66
Engine oil 1)	ltr	7.0
Weight, unladen, to DIN/EU	kg	1995 / 2070
Max. load to DIN	kg	605
Max. permissible weight	kg	2600
Max. axle load, front/rear	kg	1275 / 1425
Max. trailer load.	9	127071120
braked (12%)/unbraked	kg	-/-
Max. roof load/towbar download	kg	75/-
Luggage comp. capacity	ltr	440
Air resistance	C _d x A	<u> </u>
, iii Teolota Teo	Ou A 7 1	OLEO A Ello I
Engine		
Config./No. of cyls./valves		in-line / 6 / 4
Engine technology		BMW TwinPower Turbo technology: multi-stage charging,
		high and low pressure turbocharger with variable inlet geometry, common
		rail direct fuel injection with piezo injectors
		(max. injection pressure: 2700 bar)
Effective capacity	cm ³	2993
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel		Diesel
Output	kW/hp	250 / 340
at	rpm	4400
Torque	Nm	700
at	rpm	1750 – 2250
48V mild hybrid technology		
output	kW/hp	8/11
Electrical System	A1./	00.11
12V battery/installation	Ah/-	90 / luggage comp.
48V battery/installation	Ah/–	11 / engine comp.
Driving Dynamics and Safety		
Suspension, front		Double-wishbone axle in aluminium construction with separate lower track
Casponsion, none		arm and specific elastokinematics
Suspension, rear		Five-link axle in aluminium/steel lightweight construction with dual elastic
, , , ,		bearing and specific elastokinematics
Brakes, front		Four-piston fixed-calliper disc brakes / vented
Brakes, rear		Single-piston floating-calliper disc brakes / vented
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC
g ctatum, cyctams		(Cornering Brake Control), DBC (Dynamic Brake Control), Dry Braking
		function, fading compensation, Start-Off Assistant, DSC linked with xDrive
		all-wheel drive, Adaptive Suspension; optional: M Sport differential, active
		roll stabilisation
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and
		front passenger, head airbags for front and rear seats, three-point inertia-
		reel seatbelts on all seats with belt stopper, belt latch tensioner and belt
		force limiter at the front seats, crash sensors, Tyre Pressure Indicator
Steering		Electromechanical rack-and-pinion power steering (EPS)
J		with Servotronic function, Integral Active Steering
Steering ratio, overall	:1	16.4
Tyres, front/rear		245/45 R18 100Y XL/
- /		275/40 R18 103Y XL
Rims, front/rear		8J x 18 light-alloy /
,		9.1 x 18 light-alloy

9J x 18 light-alloy

			BMW 840d xDrive Gran Coupe
			BMW 6400 XDTIVE GIAII Coupe
Transmission			
Type of gearbox			8-speed Steptronic
Gear ratios	I	:1	5.500
	II	:1	3.520
	III	:1	2.200
	IV	:1	1.720
	V	:1	1.317
	VI	:1	1.000
	VII	:1	0.823
	VIII	:1	0.640
	R	:1	3.993
Final drive		:1	2.647
Performance			
Power-to-weight	t ratio (DIN)	kg/kW	8.0
Output per litre		kW/l	83.5
Acceleration	0–100 km/h	S	5.0
Top speed		km/h	250

BMW EfficientDynamics

BMW EfficientDynamics standard features

Mild hybrid technology with 48V starter-generator, Brake Energy Regeneration with recuperation display, Auto Start Stop function, ECO PRO and COMFORT mode with coasting function, Proactive Driving Assistant, Optimum Shift Indicator, Electric Power Steering, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, efficiency-optimised all-wheel drive, differential with optimised warm-up behaviour, BMW Blue Performance technology with SCR catalytic converter

Fuel consumption EU cy	/cle		
Urban (NEDC)	ltr/100 km	7.4 – 7.1	
Extra-urban (NEDC)	ltr/100 km	5.0 – 4.7	
Combined (NEDC)	ltr/100 km	5.9 – 5.6	
Combined (WLTP)	ltr/100 km	6.8 – 6.4	
CO ₂ (NEDC)	g/km	155 – 148	
CO ₂ (WLTP)	g/km	179 – 176	
Emission rating		Euro 6d	

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

¹⁾ Oil change volume