BMW Media Information

12/2010

Valid from 3/2011

Specifications. The new BMW 6 Series Convertible. 640i, 650i

BMW 640i Convertible



BMW 650i Convertible

		Divite 0401 Convertible	Divivi dodi Galivertibie
Body			
No. of doors/seats		2/4	2/4
Length/width/height (unlad	lon) m	4894 / 1894 / 1365	4894 / 1894 / 1365
Wheelbase	len) m m	2855	2855
Track, front/rear	m	1600 / 1657	1600 / 1657
Ground clearance	m	123	123
Turning circle	m	11.7	11.7
Tank capacity	ca. I	70	70
Cooling system incl heating		9.3	11.4
Engine oil ¹⁾	<u> </u>	6.5	8.5
Weight, unladen, to DIN/El	J kg	1840 / 1915	1940 / 2015
Max load to DIN	kg kg	450	450
Max permissible weight	kg	2290	2390
Max axle load, front/rear	kg	1100 / 1290	1180 / 1310
Max trailer load,	kg	-/-	-/-
braked (12%)/unbraked	kg	-7-	-,-
Max roof load/towbar dowr	nload kg	-/-	
Luggage comp capacity	IIOau ky	300-350	300-350
Air drag	c _X x A	0.31 x 2.23	0.32 x 2.23
All drug	- OX X /-	0.01 X 2.20	0.02 X 2.20
Engine			
Configuration/No of cyls/va	lves	inline / 6 / 4	V90/8/4
Engine technology		BMW TwinPower Turbo,	BMW TwinPower Turbo,
0 0,		direct injection,	direct injection
		fully variable valve control	
		(VALVETRONIC)	
Effective capacity	CC	2979	4395
Bore/stroke	mm	89.6 / 84.0	88.3 / 89.0
Compression ratio	:1	10.2	10.0
Fuel grade		min RON 91	min RON 91
Output	kW/hp	235 / 320	300 / 407
at	rpm	5800-6000	5500-6400
Torque	Nm	450	600
<u>at</u>	rpm	1300-4500	1750-4500
Flactoical acostana			
Electrical system	A I. /	001	105#
Battery/Installation	Ah/-	90/luggage comp	105/luggage comp
Alternator	A/W	210 / 2940	210 / 2940
Driving dynamics and s	afoty		
Suspension, front	шесу	Double track control arm with sena	rate lower track arm level, aluminium,
Caspension, none			oll radius, anti-dive
Suspension, rear		Integral-V multi-arm axle, aluminium, with steering function, anti-squat and anti-dive, double acoustic separation	
Brakes, front			alliper disc brakes in frame structure
Diameter	mm	348 x 30 / vented	374 x 36 / vented
Brakes, rear			swing-calliper disc brakes
Diameter	mm	345 x 24 / vented	345 x 24 / vented
Driving stability systems			d DTC (Dynamic Traction Control),
	C	CBC (Cornering Brake Control), DBC (Dy	namic Brake Control), Dry Braking function, Assistant; optional: Adaptive Drive
Safety equipment	1	Standard: airbags for driver and front passenger, side airbags with combined head airbags for driver and front passenger, three-point inertia-reel seatbelts on all seats with belt latch tensioner and belt force limiter integrated in the front seats, crash-activated head restraints at the front, roll-over protection system, crash sensors, Tyre Defect Indicator	
Steering			g (EPS) with Servotronic; al Active Steering
Steering ratio, overall	:1	17.1	17.1
Tyres, front/rear		225/55 R17 97Y RSC	245/45 R18 96Y RSC
Rims, front/rear		8J x 17 LM	8J x 18 LM

BMW Media Information

12/2010

Valid from 3/2011

Specifications. The new BMW 6 Series Convertible. 640i, 650i

			BMW 640i Convertible	BMW 650i Convertible	
BMW Connec	ctedDrive				
Comfort		Optional: BMW Assist incl Enquiry Service, remote-control functions and V-Info (Traffic Info plus), BMW TeleServices, integration of mobile devices			
Infotainment	Optional: internet access, BMW Online incl Park Info, National Info, Google Local Search, News, Realtime Weather, BMW Routes, Office functions, Bluetooth Audio Streaming and Online Update Music Tracks				
Safety		Optional: Adaptive Headlights with cornering lights, variable light distribution and adaptive headlight range control, High Beam Assistant, Park Distance Control, rear-view camera, Surround View incl Top View and Side View, BMW Night Vision wit pedestrian recognition, Head-Up Display, Parking Assistant, Lane Change Warning, Lane Departure Warning, Speed Limit Info, Automatic/Advanced Emergency Call			
Transmission	1				
Type of gearbo	X		Eight-speed automatic	with Steptronic	
Gear ratios	I	:1	4.714	4.714	
	II	:1	3.143	3.143	
	III	:1	2.106	2.106	
	IV	:1	1.667	1.667	
	V	:1	1.285	1.285	
	VI	:1	1.000	1.000	
	VII	:1	0.839	0.839	
	VIII	:1	0.667	0.667	
R	R	:1	3.295	3.317	
Final drive		:1	3.232	3.077	
Performance					
Power-to-weig	ht ratio I	kg/kW	7.8	6.5	
Output per litre)	kW/l	78.9	68.3	
Acceleration	0–100 km/h	S	5.7	5.0	
	0–1000 m	S	25.2	23.8	
in 4th gear	80-120 km/h	S	-	-	
Top speed		km/h	250	250	
BMW					
BMW EfficientDynamics standard features			Brake Energy Regeneration with recuperation display, Auto Start-Stop function (BMW 640i), intelligent lightweight construction, on-demand operation of ancillary units, air flap control (BMW 640i), Electric Power Steering (EPS), detachable a/c compressor, tyres with reduced rolling resistance		
Fuel consum	ntion Ell				
Urban	•	00km	10.9	15.5	
Extra-urban		00km	6.2	7.9	
Combined		00km	7.9	10.7	
COmbined CO ₂	1/ 1	g/km	185	249	
		g/NIII	EU5		
Emission rating	7			EU5	

Specifications apply to ACEA markets; data relevant to homologation applicable in part only to Germany (weight)

¹⁾ Oil change