## Specifications BMW 5 Series Sedan. 530d, 535d

## 6/2013

Valid from 7/2013



|   |                | BMW 530d  | BMW 535d  |  |
|---|----------------|---|---|--|
| Body  |                |   |   |  |
| No of doors/seats                           |                | 4/5   | 4/  |  |
| Length/width/height <sup>1)</sup> (unladen) | mm             | 4907 / 1860 / 1464  | 4907 / 1860 / 1464  |  |
| Wheelbase                                   | mm             | 2968  | 2968  |  |
| Track, front/rear                           | mm             | 1600 / 1627   | 1600 / 162  |  |
| Ground clearance                            | mm             | 141   | 14  |  |
| Turning circle                              | m              | 12.0  | 12.0  |  |
| Tank capacity                               | app ltr        | 70  | 7(  |  |
| Cooling system incl heater                  | app Iti<br>Itr | 8.0   | 8.  |  |
| Engine oil <sup>2)</sup>                    | ltr            | 7.2   | 7.2   |  |
| Weight, unladen, to DIN/EU                  |                | 1710 / 1785   | 1735 / 1810   |  |
| Max load to DIN                             | kg<br>kg       | 610   | 61  |  |
| Max permissible                             | kg             | 2320  | 234   |  |
|   |                | 1100 / 1290   | 1100 / 1310   |  |
| Max axle load, front/rear                   | kg             | 2000 / 750  | 2000/750  |  |
| Max trailer load (12%),                     | kg             | 20007750  | 20007750  |  |
| braked/unbraked                             |                | 100/00  | 100.100   |  |
| Max roofload/max towbar downloa             |                | 100/90  | 100 / 90  |  |
| Luggage comp capacity                       | ltr            | 520   | 520   |  |
| Air resistance                              | Cd x A         | 0.26 x 2.35   | 0.26 x 2.3  |  |
|   |                |   |   |  |
| Engine                                      |                |   |   |  |
| Config/No of cyls/valves                    |                | Straight-six / 4  | Straight-six / 4  |  |
| Engine technology                           |                | BMW TwinPower Turbo   | BMW TwinPower Turbo   |  |
|   |                | technology with variable-   | technology with multi-stage   |  |
|   |                | geometry turbocharger,  | variable-geometry   |  |
|   |                | Common Rail direct<br>injection with solenoid   | high-pressure<br>turbocharger, Common Rai   |  |
|   |                | valve injectors (max.   | direct injection with piezo   |  |
|   |                | injection pressure:   | injectors (max. injection   |  |
|   |                | 1800 bar)   | pressure: 2000 bar  |  |
| Capacity, effective                         | CC             | 2993  |   |  |
| Stroke / bore                               | mm             | 90.0/84.0   | 90.0 / 84.0   |  |
| Compression ratio                           | :1             | 16.5  | 16.5  |  |
| Fuel grade                                  |                | Diesel  | Diese   |  |
| Max output                                  | kW/hp          | 190 / 258   | 230/313   |  |
| at  | rpm            | 4000  | 4400  |  |
|   | Nm             | 540   | 630   |  |
| Max torque                                  |                | 1500 - 3000   | 1500 – 2500   |  |
| at  | rpm            | 1300 - 3000   | 1500 - 2500   |  |
| Electrical System                           |                |   |   |  |
| Battery/installation                        | Ah/-           | 90 / luggage comp   | 90 / luggage comp   |  |
| Alternator                                  | A/W            | 180 / 2520  | 220/3080  |  |
|   |                |   |   |  |
| Driving Dynamics and Safety                 |                |   |   |  |
| Suspension, front                           |                |   | axle with separate lower track arm level, aluminium,  |  |
|   |                |   | Il steering roll radius, anti-dive  |  |
| Suspension, rear                            |                | 5   | , aluminium, with steering function, anti-squat and   |  |
|   |                |   | live, double acoustic separation  |  |
| Brakes, front                               |                |   | m floating-calliper disc brakes in frame structure  |  |
| Diameter                                    | mm             | 348 x 30 / inner-vented   | 348 x 36 / inner-vented   |  |
| Brakes, rear                                |                | Single-piston   | aluminium floating-calliper disc brakes   |  |
| Diameter                                    | mm             | 330 x 20 / inner-vented   | 345 x 24 / inner-vented   |  |
| Driving stability systems                   |                |   | nd DTC Dynamic Traction Control, CBC Cornering  |  |
|   |                | Compensation, Start-C   | namic Brake Control, Dry Braking function, Fading<br>Off Assistant; optional: Dynamic Damper Control,<br>Adaptive Drive |  |
| Safety equipment                            |                | Standard: airbags for driver and front passenger, side airbags for driver<br>and front passenger, head airbags for front and rear seats, three-point<br>inertia-reel belts on all seats with belt stopper, belt tightener and belt force<br>limiter at the front, crash-activated headrests at the front, crash sensors,<br>Tyre Defect Indicator |   |  |
| Steering                                    |                |   | wer Steering (EPS) with Servotronic;<br>ional: Integral Active Steering   |  |
| Steering transmission, overall              | :1             | 17.1  | 17.1  |  |
| Tyres, front/rear                           |                | 225/55 R17 97W  | 225/55 R17 97W  |  |
| i ji ooj il ollal oal                       |                |   |   |  |

Information

6/2013

Valid from

7/2013

sec

km/h

|                             |            | BMW 530d |                            | BMW 535d     |
|-----------------------------|------------|----------|----------------------------|--------------|
| Transmissio                 | on         |          |                            |              |
| Type of gearbox             |            |          | Eight-speed automatic with | n Steptronic |
| Gear ratios                 |            | :1       | 4.714                      | 4.714        |
|                             | I          | :1       | 3.143                      | 3.143        |
|                             |            | :1       | 2.106                      | 2.106        |
|                             | IV         | :1       | 1.667                      | 1.667        |
|                             | V          | :1       | 1.285                      | 1.285        |
|                             | VI         | :1       | 1.000                      | 1.000        |
|                             | VII        | :1       | 0.839                      | 0.839        |
|                             | VIII       | :1       | 0.667                      | 0.667        |
|                             | R          | :1       | 3.317                      | 3.317        |
| Final drive                 |            | :1       | 2.471                      | 2.647        |
| Performanc                  | e          |          |                            |              |
| Power-to-weight ratio (DIN) |            | kg/kW    | 9.0                        | 7.5          |
| Output per litre            |            | kW       | 63.5                       | 76.8         |
| Acceleration                | 0–100 km/h | sec      | 5.8                        | 5.3          |
|                             | 0–1000 m   | sec      | 25.9                       | 24.5         |

(-)

250 (250)

## **BMW EfficientDynamics**

80–120 km/h

BMW EfficientDynamics,

in 4th gear

Top speed

standard features

Brake Energy Regeneration with recuperation display, Auto Start Stop function, ECO PRO mode with coasting function, intelligent lightweight construction, on-demand operation of ancillary units, air flap control, Electric Power Steering (EPS), detachable a/c compressor, tyres with reduced roll resistance, BMW BluePerformance technology

(-)

250

148

EU6

## Fuel Consumption EU<sup>3)</sup>

| i dei oonsumption    | LU                                 |  |     |
|----------------------|------------------------------------|--|-----|
| With standard wheels | s and tyres: 8J x 17 wheels, 22    | 5/55 R17 tyres                             |     |
| Urban                | ltr/100 km                         | 6.0  | 6.2 |
| Extra-urban          | ltr/100 km                         | 4.6  | 4.7 |
| Combined             | ltr/100 km                         | 5.1  | 5.3 |
| CO <sub>2</sub>      | g/km                               | 134  | 138 |
| With 8J x 18 wheels  | and 245/45 R18 tyres and with      | winter tyres                               |     |
| Urban                | ltr/100 km                         | 6.2  | 6.5 |
| Extra-urban          | ltr/100 km                         | 4.7  | 4.9 |
| Combined             | ltr/100 km                         | 5.3  | 5.4 |
| CO <sub>2</sub>      | g/km                               | 139  | 143 |
| With 8J x 18 wheels  | at front, 9J x 18 at rear and 24   | 5/45 R18 tyres at front, 275/40 R18 at rea | r   |
| With 8.5J x 19 wheel | ls at front, 9J x 19 at rear and 2 | 45/40 R19 tyres at front, 275/35 R19 at re | ear |
| With 8.5J x 20 wheel | ls at front, 9J x 20 at rear and 2 | 45/35 R20 tyres at front, 275/30 R20 at re | ear |
| Urban                | ltr/100 km                         | 6.5  | 6.7 |
| Extra-urban          | ltr/100 km                         | 4.9  | 5.1 |
| Combined             | ltr/100 km                         | 5.5  | 5,6 |
|                      |                                    |  |     |

144

EU6

Emission rating

Specifications applicable to ACEA markets. data relevant to homologation applicable in part only to Germany (weight)

 $\overline{CO_2}$ 

Height with roof aerial: 1475 mm
Oil change
Fuel consumption and CO<sub>2</sub> emissions depend on the selected tyre format

g/km