Specifications BMW 5 Series Sedan. 530d xDrive, 535d xDrive

6/2013

BMW Media Information

Valid from 7/2013

		BMW 530d xDrive	BMW 535d xDrive	
Body				
No of doors/seats		4/5	4/	
Length/width/height ¹⁾ (unladen)	mm	4907 / 1860 / 1464	4907 / 1860 / 146	
Wheelbase	mm	2968	296	
Track, front/rear	mm	1600 / 1627	1600 / 162	
Ground clearance	mm	141	14	
Turning circle	m	12.1	12.	
Tank capacity	app ltr	70	70	
Cooling system incl heater	ltr	8.0	8.0	
Engine oil ²⁾	ltr	7.2	7.	
Weight, unladen, to DIN/EU	kg	1810 / 1885	1840 / 191	
Max load to DIN	kg	600	60	
Max permissible	kg	2410	244	
Max axle load, front/rear	kg	1190/1325	1200 / 133	
Max trailer load (12%),	kg	2000/750	2000/75	
braked/unbraked		100/00	100.100	
Max roofload/max towbar downloa		100/90	100/9	
Luggage comp capacity	ltr	520	520	
Air resistance	Cd x A	0.26 x 2.35	0.26 x 2.3	
Engine				
Config/No of cyls/valves		Straight-six / 4	Straight-six /	
Engine technology		BMW TwinPower Turbo	BMW TwinPower Turbo	
		technology with variable-	technology with variable	
		geometry turbocharger,	geometry, high-pressur	
		Common Rail direct injection with solenoid	multi-stage turbocharging Common Rail direc	
		valve injectors (max.	injection with piez	
		injection pressure:	injectors (max. injectio	
		1800 bar)	pressure: 2000 ba	
Capacity, effective	CC	2993	2993	
Stroke / bore	mm	90.0/84.0	90.0 / 84.0	
Compression ratio	:1	16.5	16.5	
Fuel grade		Diesel	Diese	
Max output	kW/hp	190 / 258	230/31	
at	rpm	4000	4400	
Max torque	Nm	560	63	
at	rpm	1500 – 3000	1500 – 250	
Electrical System				
	Ah/-	90 / luggage comp	90 / luggage com	
Battery/installation Alternator	An/- A/W	220 / 3080		
Allemator	AVVV	22073080	22073080	
Driving Dynamics and Safety				
Suspension, front			axle with separate lower track arm level, aluminium, all steering roll radius, anti-dive	
Suspension, rear			rm axle, aluminium, anti-squat and anti-dive, double acoustic separation	
Brakes, front			Im floating-calliper disc brakes in frame structure	
Diameter	mm		348 x 30 / inner-vented 348 x 36 / inner-vented	
Brakes, rear			aluminium floating-calliper disc brakes	
Diameter	mm		330 x 20 / inner-vented 345 x 24 / inner-vented	
Driving stability systems			nd Dynamic Traction Control (DTC), Cornering Brake	
		Control (CBC), Dynamic Compensation, Start-Off	Brake Control (DBC), Dry Braking function, Fading Assistant, linked to xDrive all-wheel-drive system in agement (ICM); optional: Dynamic Damper Control, Adaptive Drive	
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia-reel belts on all seats with belt stopper, belt tightener and belt force limiter at the front, crash-activated headrests at the front, crash sensors, Tyre Defect Indicator		
Steering		Hydraulic rack-a	nd-pinion power steering with Servotronic	
Steering transmission, overall	:1	17.1	17.1	
<u> </u>		225/55 R17 97W	225/55 R17 97V	
Tyres, front/rear		223/33 RT/ 9/W	223/33 RT/ 3/ V	



BMW Media

Information

6/2013

Valid from 7/2013

			BMW 530d xDrive	BMW 535d xDrive
Transmission				
Type of gearbox			Eight-speed automatic with Steptronic	
Gear ratios I II III IV V V VI VII VIII	I	:1	4.714	4.714
	11	:1	3.143	3.143
	Ш	:1	2.106	2.106
	IV	:1	1.667	1.667
	V	:1	1.285	1.285
	VI	:1	1.000	1.000
	VII	:1	0.839	0.839
	VIII	:1	0.667	0.667
	R	:1	3.317	3.317
Final drive		:1	2.471	2.647
Performance				
Power-to-weight ratio (DIN)		kg/kW	9.5	8.0
Output per litre		kW	63.5	76.8
Acceleration C)–100 km/h	sec	5.7	5.1
	0–1000 m	sec	26.1	24.6
in 4th gear 80)–120 km/h	sec	-	-
Top speed		km/h	250	250

BMW EfficientDynamics

BMW EfficientDynamics,

standard features

Brake Energy Regeneration with recuperation display, Auto Start Stop function, ECO PRO mode with coasting function, intelligent lightweight construction, on-demand operation of ancillary units, air flap control, detachable a/c compressor, efficiency-optimised rear differential and power divider, tyres with reduced roll resistance, BMW BluePerformance technology

EU6

Fuel Consumption EU³⁾

Fuel Consumption	LU		
With standard wheels	s and tyres: 8J x 17 wheels, 22	5/55 R17 tyres	
Urban	ltr/100 km	6.4	6.8
Extra-urban	ltr/100 km	4.9	4.9
Combined	ltr/100 km	5.4	5.6
CO ₂	g/km	142	147
With 8J x 18 wheels	and 245/45 R18 tyres and with	winter tyres	
Urban	ltr/100 km	6.6	7.0
Extra-urban	ltr/100 km	5.0	5.1
Combined	ltr/100 km	5.6	5.8
CO ₂	g/km	147	152
With 8J x 18 wheels	at front, 9J x 18 at rear and 24	5/45 R18 tyres at front, 275/40 R18 at rea	ır
With 8.5J x 19 wheel	s at front, 9J x 19 at rear and 2	45/40 R19 tyres at front, 275/35 R19 at r	ear
With 8.5J x 20 wheel	s at front, 9J x 20 at the rear ar	nd 245/35 R20 tyres at front, 275/30 R20	at the rear
Urban	ltr/100 km	6.8	7.2
Extra-urban	ltr/100 km	5.2	5.2
Combined	ltr/100 km	5.8	6.0
CO ₂	g/km	152	157
			FUE

EU6

Emission rating

Specifications applicable to ACEA markets. data relevant to homologation applicable in part only to Germany (weight)

¹⁾ Height with roof aerial: 1475 mm
²⁾ Oil change
³⁾ Fuel consumption and CO₂ emissions depend on the selected tyre format