# The new MINI 3-door. Contents.



The new MINI.	
Profile	2
All new, all MINI:	
the new MINI.	6
Technical specifications	21
Power and torque diagrams	31
Exterior and interior dimensions	36

# The new MINI. Profile.



- New edition of the premium small car segment original; new MINI with hallmark emotional design, further optimised balance between driving fun and fuel consumption, innovative networking technology and clever functionality; significant advances in the areas of spatial comfort, safety, equipment, quality of material and finish as well as sporty flair and ride comfort as the result of consistently and extensively refined product substance; new model generation now more than ever before the benchmark for driving fun, premium quality and individual flair within its competitive environment.
- Exterior design refined on an evolutionary basis with hallmark styling, proportions and body structure; characteristic design features such as hexagonal radiator grille, headlamps and rear light clusters with wide chrome surround, turn indicator element and peripheral body surround in black reinterpreted and given additional emphasis due to the surface design in each specific area; high-end details underscore the sophisticated nature of the new model; five exterior paint finishes, roof in contrasting colour available as an option at no extra charge; MINI Cooper S and MINI Cooper D on request and without extra charge with roof and exterior mirror caps in contrasting colour.
- Newly designed headlamps: LED headlamps including daytime driving lights with integrated direction indicators, adaptive light distribution, and optionally available LED cornering lights and LED fog lamps; rear lights also optionally available in LED technology, optional lighting package with LED interior lights and orange-coloured ambient lighting.
- Vehicle length increased by 98 millimetres, width by 44 millimetres, height by 7 millimetres, also longer wheelbase (+ 28 millimetres) and larger track width (front + 42 millimetres, rear + 34 millimetres) as compared to the predecessor model (differential figures relate to MINI Cooper); optimised spatial comfort on all four seats; new seat design with larger adjustment range at front and longer seat surface at rear (+ 23 millimetres); more shoulder room and foot space as well as increased comfort for rear passengers; luggage compartment volume increased by 51 litres to 211 litres; rear backrest foldable with 60:40 split; optional storage package including luggage compartment floor which can be locked into place at varying points.
- New generation of engines with MINI TwinPower Turbo Technology;
   TWO model variants available as of market launch: MINI Cooper S with
   141 kW/192 bhp 4-cylinder petrol engine and 3-door and 5-door MINI

Cooper D with 3-cylinder diesel engine (85 kW/116 bhp); 6-speed automatic transmission **as standard with the** sports automatic transmission, also newly developed; extensive MINIMALISM technology including automatic engine start/stop function likewise in conjunction with automatic transmission and optional GREEN mode; improved driving performance figures and reduced fuel consumption; average fuel consumption 27 per cent lower; lowest fuel consumption and CO<sub>2</sub> levels in the MINI Cooper D: **21.15** km/l **125** g/km (as per rule **115** of Central Motor Vehicle Rules, **1989**)

- Intensification of the typical MINI go-kart feeling with extensively revised suspension technology, reduced weight and increased rigidity; new single-joint spring strut front axle with aluminium swivel bearing and also axle supports and wishbones made of high-strength steel; new multilink rear axle also in optimised lightweight construction and space-saving geometry; refined electromechanical power steering now with Servotronic as standard; Dynamic Stability Control (DSC) as standard including Dynamic Traction Control (DTC) and Electronic Differential Lock Control (EDLC), in the MINI Cooper S also including Performance Control; new spring and damper set-up with triple-path support bearings; Dynamic Damper Control optionally available for the first time in MINI; refined brake system, adapted to increased driving performance; fitted as standard with 16" light alloy wheels, with optionally available 17" light alloy wheels.
- Variable vehicle set-up using the new Driving Modes option by means
  of rotary switch at the base of the gearshift or selector lever; in addition
  to the standard setting MID mode, the modes SPORT and GREEN can be
  activated; choice of mode influences the characteristic curve of the
  accelerator and steering, as well as the shift times of the automatic
  transmission and the Dynamic Damper Control where these features are
  fitted; GREEN mode in conjunction with automatic transmission enables
  coasting with decoupled drivetrain.
- New display and operating concept: instrument cluster on the steering column showing road speed and engine speed, colour display for vehicle status details and fuel level; central instrument with new display elements and coloured lighting configuration including LED ring for visual feedback in response to numerous operating functions, 4-line TFT display as standard or optional colour display up to 8.8 inches in size; operation of navigation, entertainment, telephone and vehicle functions using MINI Controller in centre console with the relevant feedback provided on the on-board computer; start/stop button at the centre of the toggle switch bar on the centre console, can be activated without key insertion; power window lifts in the door trim panels; operating panel for lights in the dashboard.

- Body structure weight-optimised and crash-optimised; standard safety features including front and side airbags, side curtain airbags, 3-point automatic seat belts on all seats, with belt tensioners and belt force limiters at front, ISOFIX children's seat mounting at rear, Run Flat Indicator and vehicle weight lower than in predecessor models and competitors in the segment in virtually all variants of the new MINI despite extended range of fittings; increased acoustic and vibrational comfort: optimised aerodynamic properties as appropriate to each specific model including active cooling air flaps, underbody trim panel and air ducting elements in the upper section of the C columns; best aerodynamic figures within the competitive environment: Cd value reduced to 0.28 or 0.31 (MINI Cooper S).
- New MINI with significantly extended range of innovative driver assistance systems: MINI Head-Up-Display, parking assistant, rear-view camera high beam assistant and road sign detection.
- Newly structured MINI Connected in-car infotainment program with additional functions and the opportunity for ongoing expansion due to apps allowing integration in the car via smartphone; increased driving fun with typical MINI functions such as Mission Control, Dynamic Music, Driving Excitement and MINIMALISM Analyser; online connection also allows the use of social networks such as Facebook, Twitter, foursquare and Glympse.
- Extensive standard fittings and high-end options to increase comfort, premium characteristics and individual flair; these include: rain sensor with automatic driving light control, heated windscreen, Park Distance Control, electrically operated glass roof, electrically heated and folding exterior mirrors, interior and exterior mirrors with automatic anti-dazzle function, seat heating, 2-zone automatic air conditioning, bonnet stripes, seat upholsteries, interior surfaces and Colour Lines; Professional navigation system, MINI Radio Visual Boost, Harman Kardon hi-fi speaker system.

#### Engine variants:

**MINI Cooper S:** 4-cylinder petrol engine with MINI TwinPower Turbo Technology (turbo charging, direct injection, fully variable valve control, variable camshaft control),

capacity: 1998 cc, output: 141 kW/192 bhp at 4700 – 6000 rpm,

max. torque: 280 Nm at 1 250 - 4750 rpm

(300 Nm with overboost),

acceleration (0-100 km/h): 6.8 seconds (automatic: 6.7 seconds),

top speed: 235 km/h (233 km/h),

average fuel consumption\*: 5.7 - 5.8 litres (5.2 - 5.4 litres)/100

kilometres.

CO<sub>2</sub> emissions\*: 133 – 136 g/km (122 – 125 g/km), exhaust emission

page 5

standard: EU6.

**MINI Cooper D:** 3-cylinder diesel engine with MINI TwinPower Turbo Technology (turbocharger with variable turbine geometry, common rail direct injection),

capacity: 1496 cc,

output: 85 kW/116 bhp at 4000 rpm, max. torque: 270 Nm at 1750 rpm,

acceleration (0-100 km/h): 9.2 seconds (automatic: 9.2 seconds),

top speed: 200 km/h (204 km/h),

average fuel consumption\*: 21.15 km/l

CO<sub>2</sub> emissions\*: 125 g/km exhaust emission standard: EU6.

#### • Exterior dimensions:

Length: 3821 millimetres (MINI Cooper S: 3850 millimetres)

Width: 1727 millimetres)
Height: 1414 millimetres)
Wheelbase: 2495 millimetres

<sup>\*</sup> Fuel consumption depends on the selected tyre format.

# All new, all MINI: the new MINI.



The new MINI carries forward its predecessor's aspiration to remaining the leading original of the premium small car segment, underpinning its outstanding position with significant advancements in all areas relating to driving fun, quality and individual flair. The evolutionary refinement of its design signals the more mature character of the new model, reflected in a significant optimisation of such aspects as space, safety, fittings, materials and finish quality as well as sportiness and ride comfort. The enhancement of product substance embodied in the new edition of the MINI derives directly from the BMW Group's outstanding development expertise and takes on a more extensive form than ever before in the history of the brand. A new generation of engines increases driving fun and efficiency, and there is a wider selection of innovative driver assistance systems as well as MINI Connected infotainment facilities.

Three entirely newly developed power units featuring MINI TwinPower Turbo Technology are available to choose from at the market launch of the new MINI in spring 2014. The 4-cylinder petrol engine of the MINI Cooper S mobilises 141 kW/192 bhp. The new MINI Cooper D is powered by a 85 kW/116 bhp 3-cylinder diesel engine. The model program will be extended soon after the market launch with the addition of two entry-level variants. Along with a 6-speed automatic transmission that is optionally available for all engine variants. The increased engine efficiency, extensive MINIMALISM technology, optimised weight and enhanced aerodynamic properties go together to produce a reduction in fuel consumption figures of up to 27 per cent as compared to predecessor models. All model variants of the new MINI also meet the EU6 exhaust emission standard.

Classic MINI proportions, the characteristic three-way separation of body corpus, all-round greenhouse and roof together with a new take on hallmark design features define the exterior of the new model, which has grown by some ten centimetres in length. Its interior offers extended spatial comfort on all four seats as well as a luggage compartment volume expanded by 51 litres to a total of 211 litres.

A new display and operating concept combines the typical brand-style look and feel of the cockpit with optimised functionality. Road speed and engine speed along with other key driving-related information is shown in the newly designed instrument cluster on the steering column. The characteristic central instrument with an optional colour display of up to 8.8 inches in size provides feedback on operations performed using the MINI Controller in the centre console as well as giving visual feedback on driving condition and on numerous functions activated by the driver.

The new MINI Driving Modes allow an individual set-up involving not just the characteristic curve of the accelerator and steering but also engine acoustics, and in the MINI Cooper S - where the relevant features are fitted - ambient lighting, the displays in the central instrument, the shift times of the automatic transmission and the characteristics of Dynamic Damper Control, the latter system being optionally available for the first time. The modes SPORT and GREEN can be activated in addition to the standard MID mode. In conjunction with an automatic transmission, the efficiency-oriented GREEN mode also features a coasting function with decoupled drivetrain.

The range of optional driver assistance systems has been significantly expanded. For the first time there is an extendible Head-Up Display above the steering column available for the new MINI-high beam assistant and also a parking assistant and a rear view camera.

Unique within the competitive environment, the MINI in-car infotainment program likewise moves into a whole new dimension.

### Exterior design: unmistakable proportions, striking lines, high-end highlights.

The new MINI sets out to continue the global success story of the first ever premium automobile in the small car segment. At the same time it carries forward the tradition of the classic MINI that stretches back over more than 50 years. Its design reflects these historical roots as well as an evolutionary refinement of the modern vehicle concept. The hallmark brand proportions have been preserved thanks to precisely defined expansion of the exterior dimensions. These also help give the new MINI a compact and powerful appearance which symbolise its agile character, geared consistently towards inspiring driving fun.

The body of the new MINI 3-door is 3821 millimetres long, 1727 millimetres wide and 1414 millimetres high. This makes it 98 millimetres longer, 44 millimetres wider and 7 millimetres higher than its predecessor. The wheelbase has been extended by 28 millimetres to 2495 millimetres, while the track width has been enlarged at the front by 42 millimetres and at the rear by 34 millimetres to a total of 1501 millimetres in each case. Cornering agility and ride comfort benefit from these new dimensions as do the amount of space available to occupants and the luggage compartment volume. The extended adjustment range of the front seats, a seat surface lengthened by 23 millimetres and a perceptible increase in shoulder room provide more foot space and freedom of movement as well as optimised entry comfort for rear passengers. Luggage compartment volume has been increased by 51 litres to 211 litres.

Like its proportions, the car's hallmark brand styling and the three-way separation of body structure that is so typical of MINI both contribute to its unmistakable appearance. The corpus, greenhouse and roof on top are clearly separated from one another in visual terms. The glass surface with the dark body columns forms a harmonious cover extending across the entire automobile. From the side view, the window graphic tapering off to the rear creates a dynamic wedge shape which is suggestive of the forward thrust characterising the new MINI.

The wide track and short overhangs emphasise the vehicle's corpus more strikingly than ever before as it sits powerfully on top of the wheels. The athletic stature of the new MINI is additionally underscored by the visual link between the front and rear wheel arches. This is created by means of a striking sill line along with a character line running above and virtually parallel to it in the side view. The two lines feature a dynamic downward curve at both front and rear, thereby directing attention to the two large wheel arches.

Traditional design features such as the hexagonal contour of the radiator grille, the side indicator surrounds known as side scuttles, the circular headlights, the upright rear light clusters and the black periphery around the bottom edge of the body are reinterpreted. Selected design features are given a particularly high-end emphasis by means of a novel surface design in their specific environment. The contours of the headlamps, rear light clusters and wheel arches are highlighted by means of precise edging. The visual effect of the side scuttle elements and the additional headlights in the front apron is enhanced by means of striking lines on the adjacent surfaces in each case.

MINI Cooper D can be recognised by radiator grille ribs and a tailgate handle in white aluminium and a high-gloss black bumper strip as well as chrome trim element for the exhaust tailpipe. The exterior mirror caps are finished in body colour as standard in these models.

The MINI Cooper S draws its model-specific sporty flair from such features as a radiator grille with honeycomb pattern, a bumper strip in anthracite, an additional opening in the bonnet, brake air ducts integrated in the lower air inlets and a separate rear apron with exhaust tailpipes arranged at the centre. In addition to the side scuttle elements, the radiator grille of this model variant now also bears an "S" logo with chrome surround.

### Unique in the segment: LED headlamps, adaptive light distribution, LED turning light.

Detailed design revision has been applied to both the classic circular headlamps, featuring a wide chrome ring surround, and the likewise circular additional headlamps integrated in the front apron. The light sources of the headlamps are clearly structured, with the arched turn

indicators arranged in the lower section. In the standard version, the daytime driving light and the side light is produced inside the additional headlights, while fog lamps can also be included here as an optional extra.

The new MINI is the first car in its segment to offer the option of LED headlamps. The bright white LED units provide the light source for both low and high beam. They are also surrounded by an LED daylight driving light ring, the lower section of which reaches down to the white turn indicators. Another option is the LED headlamps with adaptive light distribution that ensures optimum illumination of the road surface and roadside - depending on situation and route profile - and also includes an LED turning light. The optional fog lamps are likewise available in halogen or LED, according to preference. In conjunction with the LED headlamps, the rear light clusters also come as LED units.

For the market launch of the new MINI, the selection of exterior body finishes has been extended to include five new colours. The roof and exterior mirror caps can be finished in a contrasting colour - white or black - as an option and at no extra cost. Roof rails are also available for the new MINI for the first time. Other ways of adding a touch of individual style include white or black bonnet stripes and Chrome Line for the exterior.

### Interior design: hallmark MINI style, new display and operating concept.

Precise lines, high-end colour and material combinations and modern functionality highlight the orientation of the new MINI towards driving fun and a premium interior ambience. The horizontal structure of the cockpit and the circular or elliptical contours of key features such as air outlets, instruments and door trim elements are classic design components which take on a more sophisticated and especially high-quality form in the new MINI. A new display and operating concept provides the ideal basis for safe, intuitive and convenient control of the driver assistance, infotainment and comfort systems, which have been significantly expanded in terms of the functions available.

One of the most important new features is the instrument cluster on the steering column. Road speed, engine speed and fuel level are displayed on vertically arranged circular instruments. The speedometer scale includes a colour panel for Check Control messages, vehicle status displays and visual indicators relating to driver assistance systems currently activated.

Key insertion as previously required is no longer necessary in the cockpit of the new MINI. As soon as the key is inside the car, the engine of the new MINI can be started by pressing the toggle-type start/stop button located in the middle of the centre console, which lights up red. Above the toggle switch there are three circular control switches for heating and air conditioning. The operating switches for the headlamps and fog lamps have

also been repositioned and are now located on the instrument cluster next to the steering wheel. The electrically controlled power window lifts in the new MINI are integrated in the door trim panels.

## Central instrument with new functions and impressive lighting configuration.

With its new indicator elements and extended functionality, the hallmark MINI central instrument intensifies interaction between driver and car. Depending on the car's fittings, the centre of its interior surface serves as a 4-line TFT display or else a colour screen up to 8.8 inches in size which shows operating feedback for vehicle functions, air conditioning, infotainment and communication, navigation maps and route directions as well as the special graphics for MINI Connected Services. The selection and control of these functions is facilitated by a new controller in the centre console which comes in conjunction with the Radio MINI Visual Boost or the MINI navigation system or the Professional navigation system. Rotary, pressure and shift movements as well as one-touch and bookmark buttons allow for intuitive, safe and convenient operation based on the principles of the BMW iDrive system - a ground-breaking force throughout the entire automotive sector.

The innovative display and operating concept is supported by a lighting design in the area of the central instrument which is unique to MINI. LED units around the outer edge of the circular instrument - optionally available in six colours - can respond to the current situation on the road and to specific operating steps, according to driver preference. For example, the hand movements of the road speed and engine speed display in the instrument cluster are underpinned by parallel light impulses at the edge of the central instrument. When Park Distance Control is activated, the remaining distance to obstacles is shown by means of a ring of light which is illuminated in green, yellow or red - supplementing the graphic display. A change in the desired interior temperature is confirmed by LED units which light up in blue or red. Route guidance information provided by the navigation system is also visually supported by the illuminated ring: the closer the car gets to the turn-off point, the smaller the lit-up area at the edge of the central instrument.

### Typical MINI diversity of colours and materials for maximum individual flair.

Increased interior space and a wide range of clever details make for further advancements in the area of functionality. The rear backrest with a 60:40 split is not only foldable, its tilt angle can be adjusted too. Numerous cupholders and storage facilities make it easy to take drinks and travel utensils along in the car, and there is an additional storage compartment behind the decorative strip on the passenger side. A storage package is also optionally available that includes a double load compartment floor,

additional lashing eyes and nets for the luggage compartment, along with map pouches for the backrests of the front seats.

Seats in a fabric/leather combination and leather finish are offered as an alternative to the standard fabric version. The MINI Cooper S is fitted with sports seats as standard: these are available as optional extras for all other variants. A model-specific selection of upholstery colours, interior surfaces, Colour Lines and other design features - including Chrome Line for the interior and the lighting package with LED interior lights and orange-coloured ambient lighting - offers a wide range of possibilities for interior customisation.

#### New engines with MINI TwinPower Turbo Technology.

The launch of the new MINI sees a change of generation in the area of engines. For the first time both 3-cylinder and 4-cylinder engines are used, all featuring MINI TwinPower Turbo Technology. In all petrol engines this includes turbocharging, direct fuel injection and variable camshaft control on the intake and exhaust side (double VANOS). In the engines of the MINI Cooper S models there is also fully variable valve control in the form of VALVETRONIC, as patented by the BMW Group. The diesel engines of the MINI Cooper D have a turbocharging system with variable turbine geometry and the latest generation of common rail direct injection with fuel injection pressure increased as compared to the predecessor engines so as to achieve high-precision fuel metering and clean combustion. The result: a further boost to driving fun along with increased efficiency and adherence to the EU6 exhaust emission standard. All model variants of the new MINI have improved engine and driving performance figures while their fuel consumption and emission levels have been reduced as compared to the predecessor models by as much as 27 per cent.

For highly spirited power delivery, the new MINI Cooper S is powered by a 2.0-litre 4-cylinder engine with a peak output of 141 kW/192 bhp which goes on stream between 4700 and 6000 rpm, delivering its maximum torque of 280 Newton metres at 1250 rpm. Torque can even briefly be increased to 300 Newton metres by means of an overboost function. As a result, acceleration from zero to 100 km/h takes just 6.7 seconds, while the top speed is 233 km/h.

The new MINI Cooper D also lines up for the start with increased power and a reduced level of fuel consumption as compared to its predecessor. It has a 1.5-litre 3-cylinder diesel engine which mobilises its peak output of 85 kW/116 bhp at 4000 rpm. The maximum torque of 270 Newton metres goes on stream at 1750 rpm, enabling acceleration from zero to 100 km/h in 9.2 seconds with both manual and automatic transmission. The top speed is 205 (204) km/h. The new MINI Cooper D also achieves a new optimum in terms of fuel consumption, with an average of 21.15 km/l. Its

**level of CO₂ emissions is 125 grams** per kilometre (98 to 99 g/km; EU test cycle figures, dependent on tyre format selected).

#### New automatic transmission with optimised efficiency.

The automatic transmission, also newly developed, make an additional contribution to improved efficiency. The 6-speed automatic transmission available for all variants of the new MINI which offers improved efficiency, enhanced shift comfort and increased shift dynamics. These advancements have been achieved by means of such elements as a more efficient transmission control system, a more direct connection and optimised hydraulics. The new MINI also combines automatic transmission with the automatic engine start/stop function for the first time, preventing unnecessary fuel consumption caused by idling at junctions or in congested traffic. An additional option for the new MINI Cooper S is the 6-speed sports automatic transmission which enables even shorter shift times and can be operated in manual mode using shift paddles at the steering wheel.

In conjunction with the MINI navigation system, the automatic transmission is also able to take account of the route profile in controlling gear shifts. Based on navigation data, the appropriate drive position is selected to match the imminent situation on the road, e.g. directly prior to junctions or on corners. This prevents unnecessary upshifts between two bends in quick succession, for example.

The MINIMALISM technology which comes as standard includes not only the automatic engine start/stop function and extensive measures to optimise weight and aerodynamic drag in the new MINI but also a shift point display function for automobiles with manual transmission, brake energy recuperation and needs-oriented control of the fuel pump, coolant pump and other ancillary units. The electromechanical power steering is equally as energy-efficiency as the map-controlled oil pumps in all engines. An optimised preheating process reduces the energy required to start the diesel engines by around 50 per cent.

Depending on the model variant, a significant optimisation of aerodynamic properties is achieved by such measures as active cooling air flaps, extensive underbody trim and air ducting elements in the upper section of the C columns. With a drag coefficient (Cd value) of 0.28 or 0.31 (MINI Cooper S), the new MINI is the segment leader in terms of aerodynamics, too.

#### MINI Driving Modes: sporty flair and efficiency and turn of a switch.

The new MINI Driving Modes option provides an excellent basis for fuel efficient motoring. A rotary switch at the base of the gear or selector lever is used to activate either the standard MID mode, the SPORT or the GREEN mode. In addition to the characteristic curve of the accelerator and steering and engine acoustics, the MINI Driving Modes also influence the ambient

lighting, the displays in the central instrument, the shift characteristics of the automatic transmission and the Dynamic Damper Control configuration in the MINI Cooper S - in so far as these features are fitted. The choice is between a set-up which is either very sporty, comfortable and well-balanced or else geared towards fuel efficiency.

In GREEN mode - supporting a relaxed and more fuel-efficient driving style - the energy used by electrically powered comfort functions such as air conditioning and exterior mirror heating is reduced. In cars fitted with automatic transmission it is also possible to use the coasting function. The drivetrain is decoupled at speeds of between 50 and 160 km/h as soon as the driver removes their foot from the accelerator pedal. The new MINI then rolls at idling engine speed at a minimum rate of minimal fuel consumption.

#### Optimised suspension technology: less weight, more go-kart feeling.

The refinement of suspension technology in the new MINI keeps to the well-established design principle of the single-joint spring strut axle at front along with a multilink rear axle that is unique within the competitive environment, as well as featuring extensive optimisation of all components in terms of material selection and geometry. All improvements are aimed at intensifying the experience of the agile MINI handling properties, commonly known as the go-kart feeling. The set-up of the wheel suspension, body mounting, vehicle suspension, damping, steering and brakes takes account of the increased level of engine power and the typical MINI concept consisting of front-wheel drive, transversely mounted engine at the front, low centre of gravity, short overhangs, wide track and rigid, weight-optimised body structure.

In order to reduce weight and increase component rigidity, the new front axle is fitted with aluminium swivel bearings as well as axle supports and wishbones made of high-strength steel. The modified front axle kinematics supports the agile turn-in response and precise steering sensation of the new MINI. The share of high-strength steel used in the rear axle has also been increased. Tube-shaped stabilisers at the front and rear axle likewise contribute to weight reduction. There is also an innovative axle bearing which benefits both ride comfort and agility.

#### Premiere for Dynamic Damper Control in the new MINI.

The newly configured suspension and damping systems have been reduced in weight. The dampers are decoupled at the front and rear axle by means of triple-path support bearings. Another new addition to the MINI equipment program is Dynamic Damper Control. Two characteristic lines are available for damper set-up, allowing activation of either a more comfort-oriented response or a direct, sporty response to road bumps, depending on the given situation. The compression and rebound stage are adjusted by means of electrical control of the EDC valves.

The electromechanical power steering has also been subjected to extensive further development. So-called torque steer compensation prevents self-steering tendencies caused by differing degrees of torque at the drive wheels. Steering precision has also been optimised for sudden avoidance swerves and when taking bends in very sporty style. Standard features also include the speed-related steering assistance system Servotronic.

In addition to the anti-lock system ABS, electronic brake force distribution EBD, Cornering Brake Control (CBC) and the brake assistant, the driving stability control system DSC (Dynamic Stability Control) in the new MINI also includes a drive-off assistant, a brake dry function, Fading Brake Support and DTC mode (Dynamic Traction Control), which permits controlled slip at the drive wheels so as to facilitate driving off on loose sand or deep snow. When the driving stability system is deactivated (DSC Off mode), there is an electronic locking function for the front axle differential which selectively and appropriately brakes a spinning drive wheel on tight corners, redirecting the drive torque to the other wheel. This system, known as Electronic Differential Lock Control (EDLC), thereby promotes the car's forward momentum without negatively influencing self-steering response. The new MINI Cooper S also features the Performance Control system, which counteracts any tendency to understeer prior to reaching the threshold level so as to support an agile yet neutral driving response on bends.

The new **MINI Cooper D and** MINI Cooper S are fitted with 16-inch light alloy wheels as standard. Other light alloy wheels up to a size of 17 inches are available as part of the program of options and accessories.

## Less weight, more safety and greater agility due to intelligent lightweight construction.

Further development in the body area was focused on optimising structure, which impacts positively on both the driving properties and the crash response of the new MINI. Intelligent lightweight construction means that weight reduction in the new MINI is combined with an increase in rigidity, thereby promoting both agility and occupant protection. In spite of its extended range of fittings, virtually all variants of the new MINI are lighter than their respective predecessor models. They also weight less than their competitors in the segment.

Highly resilient bearing structures, deformation zones in optimum design and an extremely stable passenger cell provide an excellent basis for keeping impact energy away from passengers and ensuring maximum occupant protection. The safety concept of the new MINI is geared towards achieving maximum scores on all the relevant crash tests worldwide.

page 15

### Comprehensive safety technology including pedestrian protection.

The standard safety fittings of the new MINI comprise front and side airbags as well as curtain airbags for the front and rear seats. All seats are fitted with 3-point seat belts with belt tensioners and belt force limiters at the front and ISOFIX child seat mountings provided at the rear.

There are also impact absorbers, precisely defined deformation elements and a partially active bonnet, all of which are elements that minimise the risk of injury to pedestrians. In the event of a collision with a pedestrian, which is registered by special sensors, a pyrotechnical trigger mechanism raises the engine compartment lid. This creates additional deformation space and significantly reduces the risk of injury when impacting against very hard parts of the engine.

#### Innovative driver assistance systems increase convenience and safety.

Further evidence of the technological progress ushered in with the new edition of the MINI is to be found in the program of driver assistance systems - available for the first time in a model of the British brand. New features include the MINI Head-Up-Display which shows information relevant to the driver on an extendible monitor in the upper section of the dashboard between the windscreen and steering wheel. The MINI Head-Up Display promotes concentration on the road by displaying information directly in the driver's line of sight. It can then be read quickly and conveniently without averting one's eyes from the road. The information that can be shown in the MINI Head-Up Display includes speed in figures, navigation directions in the form of arrow graphics and junction sketches, visual signals for collision warning. Check Control messages and entertainment program details such as radio channels and track titles. The graphics on the high-resolution screen are clearly visible in all light conditions.

A rear view camera and parking assistant are also available for the new MINI. The video images supplied by the rear view camera underneath the tailgate handle are shown on the on-board computer in the central instrument as an aid when manoeuvring and reverse parking.

#### High-end features for comfort, functionality and individual style.

The standard features of the new MINI include electrically adjustable exterior mirrors, door sill cover strips with model-specific inscription, Colour Line in Carbon Black and the MINI Radio including AUX-In and USB interface: these can be supplemented with a range of high-quality options in the areas of comfort, functionality and individual flair so as to adapt the car to one's own personal style. There is also a 2-zone automatic air conditioning system, seat heating for driver and front passenger, a panorama glass roof, a visibility package including windscreen heating, rain sensor and automatic light control, the Harman Kardon hi-fi speaker system

and a sports leather steering wheel (as standard in the MINI Cooper S) including optional multifunction buttons and cruise control.

Other options include **Front** Park Distance Control, electrically heatable and folding exterior mirrors, and both interior and exterior mirrors with automatic anti-dazzle function. For customisation of the exterior and interior in hallmark brand style, options also include a rear spoiler in John Cooper Works design as well as various decorative trim styles for roof and exterior mirrors, bonnet stripes, seat upholsteries, interior surfaces and Colour Lines.

## MINI Connected: premiere for Emergency Call; apps now also available for Android smartphones.

The option MINI connected or MINI Connected XL is also available in conjunction with the Radio MINI Visual Boost and the MINI navigation system. It offers extensive integration of smartphones in the car, allowing the use of internet-based services in the areas of infotainment, communication and driver experience. These are provided via apps whose functional diversity is being continuously expanded.

The MINI Connected program provided through smartphone apps includes vehicle-related functions such as Mission Control, Dynamic Music, Driving Excitement and MINIMALISM Analyser as well as online-based services such as a web radio function, the use of social networks such as Facebook, Twitter, foursquare and Glympse. With the colour display in the central instrument, all functions can be operated in typical MINI style - and more comfortably, intuitively and safely than ever before.

**Technical specifications** 

### MINI Cooper S.

Padu.		MINI Comos C Automotic
Body Number of doors/seats		MINI Cooper S Automatic 3 / 4
Length/width/height (empty)	mm	3850 / 1727 / 1414
Wheelbase	mm mm	2595
Track width, front/rear	mm	1485 / 1485
Turning circle	m	10.8
Fuel tank capacity	approx. I	44
Cooling system incl. heating	approx.1	6.1
Engine oil	i	5.0
Transmission oil incl. drivetrain	1	lifetime filling
Unladen weight according to DIN/EU 1)	kg	1175 / 1250
Payload according to DIN	kg	450
Permitted gross vehicle weight	kg	1655
Permitted axle loads, front/rear	kg	930 / 765
Permitted trailer load		
braked (12 %) / unbraked	ļ.a	.=!=
Permitted roof load/permitted download	kĝ	60 / -
Luggage compartment capacity	1 21 2	211
Aerodynamic drag c <sub>x</sub> / A / c <sub>x</sub> × A	- / m <sup>2</sup> / m <sup>2</sup>	0.31 / 2.09 / 0.65
Engine		in line / 4 / 4
Type/no. of cylinders/valves		in-line / 4 / 4
Engine control		MEVD 17.2.3 1998
Capacity Bore/stroke	CC	
Compression	mm :1	82.0 / 94.6 11.0
Fuel Output	RON kW/bhp	91–98 141 / 192
at engine speed	rpm	4700 - 6000
Torque (with overboost)	Nm	280 (300)
at engine speed	rpm	1250 - 4750
Electrical system		
Battery/installation	Ah / -	80 / engine compartment
Alternator	A	150
Suspension		
Front wheel suspension		
Rear wheel suspension		
Brakes, front		disc, vented
rear brakes		disc
Driving stability systems		
Steering		
Overall steering ratio	:1	14.2
Tyres		195/55 R16 87W
Rims		6.5J × 16 light alloy
Transmissions		
Transmission type	.1	6-speed automatic transmission
Gear ratio I	:1	4.459
III	:1 :1	2.508 1.555
IV	:1	
V V	:1	1.142 0.851
VI	:1	0.631
Reverse gear	:1	3.185
Final drive ratio	:1	3.502
Driving performance figures	.1	3.302
Power-to-weight ratio according to DIN	kg/kW	8.3
Power output per litre	kW/l	70.6
Acceleration 0-100 km/h	S .	6.7
0–1000 m	S	2)
in 4th/5th gear 80-120 km/h	S	-1-
Top speed	km/h	233
• •		233

01/2014 page 20

Fuel consumption in EU cycle 3)		
Urban	l/100 km	6.8 - 6.9
Extra-urban	l/100 km	4.4 - 4.5
Total	l/100 km	5.2 - 5.4
CO <sub>2</sub>	g/km	122 - 125
Other		
Emission rating		EU6
Insurance rating in Germany	3rd party/fully	2)
Ground clearance (empty)	mm	124

Technical specifications valid for ACEA markets / authorisation data only relevant to Germany in some cases (weights)

 $<sup>^{1)}</sup>$  Weight of road-ready automobile (DIN) plus 75 kg for driver and luggage  $^{2)}$  Details not yet available  $^{3)}$  Dependent on tyre format selected

### MINI Cooper D, MINI Cooper D Automatic.

Body		MINI Cooper D	MINI Cooper D Automatic
Number of doors/seats		3 / 4	3 / 4
Length/width/height (empty)	mm	3821 / 1727 / 1414	3821 / 1727 / 1414
Wheelbase	mm	2495	2495
Track width, front/rear	mm	1501 / 1501	1501 / 1501
Turning circle	m	10.8	10.8
Fuel tank capacity	approx. l	44	44
Cooling system incl. heating		6.6	6.6
Engine oil	i	4.7	4.7
Transmission oil incl. drivetrain	<u> </u>	lifetime filling	lifetime filling
Unladen weight according to DIN/EU 1)	kg	1135 / 1210	1150 / 1225
Payload according to DIN	kg	450	450
Permitted gross vehicle weight	kg	1615	1630
Permitted axle loads, front/rear	kg	910 / 755	925 / 755
Permitted date loads, front/real	, kg	910 / 733	923   733
braked (12 %) / unbraked			
Permitted roof load/permitted download	kg	60 / -	60 / -
Luggage compartment capacity		211	211
Aerodynamic drag c <sub>x</sub> / A / c <sub>x</sub> × A	- / m <sup>2</sup> / m <sup>2</sup>	0.28 / 2.07 / 0.58	0.28 / 2.07 / 0.58
Engine	, ,	0.20 / 2.07 / 0.30	0.20 / 2.07 / 0.50
Type/no. of cylinders/valves		in-line / 3 / 4	in-line / 3 / 4
Engine control		DDE 7.01	DDE 7.01
Capacity	CC	1496	1496
Bore/stroke	mm	84.0 / 90.0	84.0 / 90.0
Compression		16.5	16.5
Fuel	RON	Diesel	Diesel
Output	kW/bhp	85 / 116	85 / 116
at engine speed	rpm	4000	4000
Torque	Nm	270	270
at engine speed	rpm	1750	1750
Electrical system			
Battery/installation	Ah / –	80 / engine compartment	80 / engine compartment
Alternator	Α	150	150
Suspension			
Front wheel suspension	Si	ingle-joint McPherson spring strut axle	
			anti-dive control
Rear wheel suspension			vith weight-optimised trailing arms
Brakes, front		disc, vented	disc, vented
rear brakes		disc	disc
Driving stability systems  Hydraulic 2-circuit brake system with anti-lock brakes (ABS), electronic			
Driving stability systems			
Driving stability systems		n (EBD) and Cornering Brake Control (C	BC), Dynamic Stability Control (DSC)
Driving stability systems		n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadin	BC), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction
Driving stability systems		n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadin Control (DTC) and Electro	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction nic Differential Lock Control (EDLC).
		n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadin Control (DTC) and Electror Handbrake in	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction nic Differential Lock Control (EDLC). spacts mechanically on rear wheels
Steering	with brake assistant, hill s	n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadin Control (DTC) and Electro Handbrake in Electrically assisted	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction ic Differential Lock Control (EDLC). pacts mechanically on rear wheels I EPS unit with Servotronic function
Steering Overall steering ratio		n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadin Control (DTC) and Electro Handbrake in Electrically assisted 14.2	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction ic Differential Lock Control (EDLC). pacts mechanically on rear wheels I EPS unit with Servotronic function 14.2
Steering Overall steering ratio Tyres	with brake assistant, hill s	n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadin Control (DTC) and Electron Handbrake in Electrically assisted 14.2 175/65 R15 84H	BC), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction ic Differential Lock Control (EDLC). upacts mechanically on rear wheels I EPS unit with Servotronic function 14.2 175/65 R15 84H
Steering Overall steering ratio Tyres Rims	with brake assistant, hill s	n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadin Control (DTC) and Electro Handbrake in Electrically assisted 14.2	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction ic Differential Lock Control (EDLC). pacts mechanically on rear wheels I EPS unit with Servotronic function 14.2
Steering Overall steering ratio Tyres Rims Transmissions	with brake assistant, hill s	n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadin Control (DTC) and Electron Handbrake in Electrically assisted 14.2 175/65 R15 84H 5.5J × 15 light alloy	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction ic Differential Lock Control (EDLC). pacts mechanically on rear wheels I EPS unit with Servotronic function 14.2 175/65 R15 84H 5.5J × 15 light alloy
Steering Overall steering ratio Tyres Rims Transmissions Transmission type	with brake assistant, hill s	n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadir Control (DTC) and Electron Handbrake in Electrically assisted 14.2 175/65 R15 84H 5.5J × 15 light alloy	BC), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction itc Differential Lock Control (EDLC). upacts mechanically on rear wheels I EPS unit with Servotronic function 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed automatic transmission
Steering Overall steering ratio Tyres Rims Transmissions Transmission type Gear ratio	with brake assistant, hill s	n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadiri Control (DTC) and Electron Handbrake in Electrically assisted 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed manual transmission 3.923	BC), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction itc Differential Lock Control (EDLC). upacts mechanically on rear wheels if EPS unit with Servotronic function 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed automatic transmission 4.459
Steering Overall steering ratio Tyres Rims Transmissions Transmission type Gear ratio I	with brake assistant, hill s	n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadian Control (DTC) and Electro Handbrake in Electrically assisted 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed manual transmission 3.923 2.136	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction ic Differential Lock Control (EDLC). pacts mechanically on rear wheels I EPS unit with Servotronic function  14.2  175/65 R15 84H  5.5J × 15 light alloy  6-speed automatic transmission  4.459  2.508
Steering Overall steering ratio Tyres Rims Transmissions Transmission type Gear ratio  II  III	with brake assistant, hill s	n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadin Control (DTC) and Electro Handbrake in Electrically assisted 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed manual transmission 3.923 2.136 1.393	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction ic Differential Lock Control (EDLC). pacts mechanically on rear wheels I EPS unit with Servotronic function 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed automatic transmission 4.459 2.508 1.555
Steering Overall steering ratio Tyres Rims Transmissions Transmission type Gear ratio  II  III  IV	with brake assistant, hill s	n (EBD) and Cornering Brake Control (Ctart assistant, brake dry function, Fadin Control (DTC) and Electron Handbrake in Electrically assisted 14.2 175/65 R15 84H 5.5J × 15 light alloy  6-speed manual transmission 3.923 2.136 1.393 1.088	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction it Differential Lock Control (EDLC). pacts mechanically on rear wheels I EPS unit with Servotronic function 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed automatic transmission 4.459 2.508 1.555 1.142
Steering Overall steering ratio Tyres Rims Transmissions Transmission type Gear ratio II III IV V	with brake assistant, hill s	n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadin Control (DTC) and Electro Handbrake in Electrically assisted 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed manual transmission 3.923 2.136 1.393 1.088 0.892	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction it Differential Lock Control (EDLC). pacts mechanically on rear wheels EPS unit with Servotronic function 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed automatic transmission 4.459 2.508 1.555 1.142 0.851
Steering Overall steering ratio Tyres Rims Transmissions Transmission type Gear ratio II III IV V VI	### with brake assistant, hill s  ### :1  ### :1  ### :1  ### :1  ### :1  ### :1  ### :1  ### :1	n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadin Control (DTC) and Electro Handbrake in Electrically assisted 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed manual transmission 3.923 2.136 1.393 1.088 0.892 0.756	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction ic Differential Lock Control (EDLC). pacts mechanically on rear wheels EPS unit with Servotronic function 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed automatic transmission 4.459 2.508 1.555 1.142 0.851 0.672
Steering Overall steering ratio Tyres Rims Transmissions Transmission type Gear ratio II III IV V VI Reverse gear	### with brake assistant, hill s  ### :1  ### :1  ### :1  ### :1  ### :1  ### :1  ### :1  ### :1  ### :1	n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadin Control (DTC) and Electro Handbrake in Electrically assisted 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed manual transmission 3.923 2.136 1.393 1.088 0.892 0.756 3.538	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction ic Differential Lock Control (EDLC). pacts mechanically on rear wheels EPS unit with Servotronic function 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed automatic transmission 4.459 2.508 1.555 1.142 0.851 0.672 3.185
Steering Overall steering ratio Tyres Rims Transmissions Transmission type Gear ratio II III III IV V VI Reverse gear Final drive ratio	### with brake assistant, hill s  ### :1  ### :1  ### :1  ### :1  ### :1  ### :1  ### :1  ### :1	n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadin Control (DTC) and Electro Handbrake in Electrically assisted 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed manual transmission 3.923 2.136 1.393 1.088 0.892 0.756	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction ic Differential Lock Control (EDLC). pacts mechanically on rear wheels EPS unit with Servotronic function 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed automatic transmission 4.459 2.508 1.555 1.142 0.851 0.672
Steering Overall steering ratio Tyres Rims Transmissions Transmission type Gear ratio  II  III  IV  V  VI  Reverse gear Final drive ratio Driving performance figures	### with brake assistant, hill s  ### :1  ###	n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadin Control (DTC) and Electro Handbrake in Electrically assisted 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed manual transmission 3.923 2.136 1.393 1.088 0.892 0.756 3.538	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction ic Differential Lock Control (EDLC). pacts mechanically on rear wheels EPS unit with Servotronic function 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed automatic transmission 4.459 2.508 1.555 1.142 0.851 0.672 3.185
Steering Overall steering ratio Tyres Rims Transmissions Transmission type Gear ratio II III III IV V VI Reverse gear Final drive ratio	### with brake assistant, hill s  ### :1  ### :1  ### :1  ### :1  ### :1  ### :1  ### :1  ### :1  ### :1	n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadin Control (DTC) and Electro Handbrake in Electrically assisted 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed manual transmission 3.923 2.136 1.393 1.088 0.892 0.756 3.538	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction ic Differential Lock Control (EDLC). pacts mechanically on rear wheels EPS unit with Servotronic function 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed automatic transmission 4.459 2.508 1.555 1.142 0.851 0.672 3.185
Steering Overall steering ratio Tyres Rims Transmissions Transmission type Gear ratio  II  III  IV  V  VI  Reverse gear Final drive ratio Driving performance figures Power-to-weight ratio according to DIN	### with brake assistant, hill s  ### :1  ###	n (EBD) and Cornering Brake Control (Cl tart assistant, brake dry function, Fadin Control (DTC) and Electro Handbrake in Electrically assisted 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed manual transmission 3.923 2.136 1.393 1.088 0.892 0.756 3.538 3.389	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction itc Differential Lock Control (EDLC). pacts mechanically on rear wheels I EPS unit with Servotronic function 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed automatic transmission 4.459 2.508 1.555 1.142 0.851 0.672 3.185
Steering Overall steering ratio Tyres Rims Transmissions Transmission type Gear ratio  II  III  IV  V  VI  Reverse gear Final drive ratio Driving performance figures	### with brake assistant, hill s  ### :1  ###	n (EBD) and Cornering Brake Control (Ctart assistant, brake dry function, Fadian Control (DTC) and Electron Handbrake in Electrically assisted 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed manual transmission 3.923 2.136 1.393 1.088 0.892 0.756 3.538 3.389	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction in Differential Lock Control (EDLC). pacts mechanically on rear wheels I EPS unit with Servotronic function  14.2  175/65 R15 84H  5.5J × 15 light alloy  6-speed automatic transmission  4.459  2.508  1.555  1.142  0.851  0.672  3.185  3.234
Steering Overall steering ratio Tyres Rims Transmissions Transmission type Gear ratio  II  III  IV  V  VI  Reverse gear Final drive ratio Driving performance figures Power-to-weight ratio according to DIN Power output per litre	### with brake assistant, hill s  ### :1  ###	n (EBD) and Cornering Brake Control (Ctart assistant, brake dry function, Fadin Control (DTC) and Electro Handbrake in Electrically assisted 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed manual transmission 3.923 2.136 1.393 1.088 0.892 0.756 3.538 3.389	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction in: Differential Lock Control (EDLC). pacts mechanically on rear wheels I EPS unit with Servotronic function  14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed automatic transmission 4.459 2.508 1.555 1.142 0.851 0.672 3.185 3.234
Steering Overall steering ratio Tyres Rims Transmissions Transmission type Gear ratio  II  III  IV  V  VI  Reverse gear Final drive ratio  Driving performance figures Power-to-weight ratio according to DIN Power output per litre Acceleration 0-100 km/h	:1 :1:1:1:1:1:1:1:1:1:1:1:1:1:1:1:1:1:1	n (EBD) and Cornering Brake Control (Ctart assistant, brake dry function, Fadin Control (DTC) and Electron Handbrake in Electrically assisted 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed manual transmission 3.923 2.136 1.393 1.088 0.892 0.756 3.538 3.389	3C), Dynamic Stability Control (DSC) g Brake Support, Dynamic Traction in Differential Lock Control (EDLC). pacts mechanically on rear wheels I EPS unit with Servotronic function 14.2 175/65 R15 84H 5.5J × 15 light alloy 6-speed automatic transmission 4.459 2.508 1.555 1.142 0.851 0.672 3.185 3.234 13.5 56.8 9.2

01/2014 page 22

Fuel consumption in EU cycle <sup>3)</sup>				
Urban	l/100 km	4.3 – 4.4	4.2 - 4.3	
Extra-urban	l/100 km	3.1 – 3.2	3.5 - 3.5	
Total	l/100 km	3.5 – 3.6	3.7 - 3.8	
CO <sub>2</sub>	g/km	92 – 95	98 - 99	
Other				
Emission rating		EU6	EU6	
Insurance rating in Germany	3rd party/fully	2)	2)	
Ground clearance (empty)	mm	124	124	


Technical specifications valid for ACEA markets / authorisation data only relevant to Germany in some cases (weights)

 $<sup>^{1)}</sup>$  Weight of road-ready automobile (DIN) plus 75 kg for driver and luggage  $^{2)}$  Details not yet available  $^{3)}$  Dependent on tyre format selected


Power and torque diagrams.



#### MINI Cooper S.



### MINI Cooper D.



### **Exterior and interior dimensions.**



