

# Specifications. BMW 4 Series Coupe. 425d



BMW 425d Coupe		
<b>Body</b>		
No. of doors/seats		2 / 4
Length/width/height <sup>1)</sup> (unladen)	mm	4638 / 1825 / 1377
Wheelbase	mm	2810
Front/rear track	mm	1545 / 1594
Ground clearance	mm	130
Turning circle	m	11.3
Fuel capacity	approx. l	57
Cooling and heating system reservoir capacity	l	<sup>4)</sup>
Engine oil capacity <sup>2)</sup>	l	5.2
Weight, unladen (DIN/EU)	kg	1490 / 1565 (1505 / 1580)
Payload (DIN)	kg	520
Permitted total weight	kg	2010 (2025)
Permitted axle load, front/rear	kg	935 / 1120
Permitted trailer load (12%) braked/unbraked	kg	1800 / 750
Permitted roof load/trailer download	kg	75 / 75
Luggage compartment capacity	l	445
Aerodynamic drag	c <sub>c</sub> x A	0.28 x 2.16
<b>Engine</b>		
Type/no. of cylinders/valves		in-line / 4 / 4
Engine technology	BMW TwinPower Turbo technology with two turbochargers, high pressure charger with variable inlet geometry, Common Rail direct injection with piezo injectors (max. injection pressure: 2000 bar)	
Effective capacity	cc	1995
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel type		Diesel
Output	kW/hp	160 / 218
at rpm	min <sup>-1</sup>	4000
Torque	Nm	450
at rpm	min <sup>-1</sup>	1500
<b>Electrical</b>		
Battery charge/location	Ah/–	90 / luggage compartment
Alternator current/output	AW	<sup>4)</sup>
<b>Driving Dynamics and Safety</b>		
Front suspension	Aluminium double-joint spring-strut axle with displaced camber, small positive steering roll radius, compensation of lateral forces, anti-dive	
Rear suspension	Five-link axle in lightweight steel construction	
Front brakes	Single-piston floating-calliper disc brakes, inner-vented	
Rear brakes	Single-piston floating-calliper disc brakes, inner-vented	
Driving stability systems	Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, start-off assist	
Safety equipment	Standard: driver and front-seat passenger airbags, driver and front-seat passenger side airbags, front and rear head airbags, three-point automatic seatbelts for all seats, seatbelt tensioners and seatbelt force limiters in front seats, crash sensors, tyre defect indicator	
Steering	Electromechanical rack-and-pinion power steering (EPS) with Servotronic function; optional: Variable Sport Steering	
Overall steering ratio	:1	15.0
Front/rear tyres		225/50 R17 94W
Front/rear wheels		7,5J x 17 light-alloy

## Specifications. BMW 4 Series Coupe.

BMW 425d Coupe			
Transmission			
Type of gearbox		6-speed manual (optional: 8-speed automatic with Steptronic)	
Gear ratios	I	:1	4.110 (4.714)
	II	:1	2.248 (3.143)
	III	:1	1.403 (2.106)
	IV	:1	1.000 (1.667)
	V	:1	0.802 (1.285)
	VI	:1	0.659 (1.000)
	VII	:1	– (0.839)
	VIII	:1	– (0.667)
	R	:1	3.727 (3.295)
Differential ratio		:1	3.462 (2.813)
Performance			
Weight-to-power ratio (DIN unladen)		kg/kW	9.3 (9.4)
Specific power output		kW/l	80.2
Acceleration	0–100 km/h	sec.	6.7 (6.5)
	0–1,000 m	sec.	4)
in 4th/5th gear	80–120 km/h	sec.	4) / 6.8 (– / –)
Max. speed		km/h	247 (247)
BMW EfficientDynamics			
BMW EfficientDynamics Features included as standard		Brake Energy Regeneration with recuperation display, electric power steering (EPS), Auto Start Stop function, Optimum Gearshift Indicator (manual gearbox), ECO PRO mode with coasting function, intelligent lightweight construction, optimised aerodynamic attributes, on-demand operation of ancillary units, differential with optimized-warm-up behaviour, tyres with reduced rolling resistance	
Fuel consumption (EU) 3)			
With standard wheels and tyres			
Urban	l/100 km		6.1 (5.7)
Extra-urban	l/100 km		4.3 (4.1)
Total	l/100 km		5.0 (4.7)
CO <sub>2</sub> emissions	g/km		131 (124)
With 8J x 18" rims and 225/45 R18 tyres and winter tyres, With 8J x 18" front rims, 8.5J x 18" rear rims, 225/45 R18 front tyres and 255/40 R18 rear tyres, With 8J x 19" front rims, 8.5J x 19" rear rims, 225/40 R19 front tyres and 255/35 R19 rear tyres			
Urban	l/100 km		6.3 (5.9)
Extra-urban	l/100 km		4.4 (4.3)
Combined	l/100 km		5.1 (4.9)
CO <sub>2</sub> emissions	g/km		135 (128)
Emissions standard			EU6

Technical data valid for ACEA countries/Some permitted weights valid only for Germany  
Figures in brackets apply to automatic transmission

<sup>1)</sup> Height including roof aerial

<sup>2)</sup> Oil change volume

<sup>3)</sup> Fuel consumption and CO<sub>2</sub> emissions depend on the selected tyre format

<sup>4)</sup> Data not yet available