BMW Media Information 10/2017 Page 1

Specifications. The new BMW X2. sDrive20i.



	BMW X2 sDrive20i			
Body				
No of doors/seats		5/5		
Length/width/height (unladen)	mm	4360 / 1824 / 1526		
Wheelbase	mm	2670		
Track, front/rear	mm	1563 / 1562		
Ground clearance	mm	182		
Turning circle	m	11.3		
Fuel tank capacity	approx. I	51		
Engine oil ¹⁾	прргод. Т	5.25		
Weight, unladen, to DIN/EU	kg	1460 / 1535		
Max load to DIN	kg	595		
Max permissible weight	kg	2055		
Max axle load, front/rear	kg	1055 / 1030		
Max trailer load,	kg	1800 / 750		
braked (12%)/unbraked	'\9			
Max roofload/max towbar	kg	75 / 80		
download	ı.g			
Luggage comp capacity	1	470 –1355		
Air resistance	Cd x A	0.29 x 2.37		
, iii roolotarioo	- Cunn	OLEO A ELOY		
Power Unit				
Config/No of cyls/valves		In-line/4/4		
Engine technology		BMW TwinPower Turbo technology: TwinScroll turbocharger, High Precision Direct Injection, VALVETRONIC fully variable valve control, Double-VANOS		
		variable camshaft timing		
Effective capacity	CC	1998 94.6 / 82.0		
Stroke/bore	mm			
Compression ratio	:1	11.0		
Fuel	1.1.4.///	min. RON 91		
Max output	kW/hp	141 / 192		
at	rpm	5000 – 6000 280		
Max torque	Nm			
at	rpm	1350 – 4600		
Electrical System				
Battery/installation	Ah/-	70 / Luggage compartment		
Driving Dynamics and Safet	·			
Suspension, front	,	Single-joint spring-strut axle in lightweight aluminium-steel construction		
Suspension, rear		Multi-arm axle in lightweight steel construction with separate spring and		
Brakes, front		damper configuration Single-piston floating-calliper disc brakes, vented		
Brakes, rear				
Driving stability systems		Single-piston floating-calliper disc brakes, vented Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), DBC (Dynamic Brake Control), brake drying function, Fading Compensation, Start-Off Assistant, EDLC (Electronic Differential Lock Control), Performance		
Safety equipment		Control, trailer stability control; optional: Dynamic Damper Control Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia-reel seatbelts on all seats (belt latch tensioner and belt force limiter at the front		
Steering		seats), crash sensors, tyre defect indicator Electric Power Steering (EPS) with Servotronic function; optional: M Servotronic		
Steering ratio, overall	:1	15.9		
Tyres, front/rear		225/55 R17 97W 225/55 R17 97W		
Rims, front/rear		7.5J x 17 light-alloy /		
inino, iluliureai		7.53 x 17 light-alloy 7 7.5J x 17 light-alloy		

		BMW X2 sDrive20i
Transmission		
Type of transmission		7-speed Steptronic dual-clutch transmission
Gear ratios	l :1	4.154
	Ⅱ :1	2.45
	III :1	1.393
	IV :1	0.975
	V :1	0.755
	VI :1	0.675
	VII :1	0.547
	VIII :1	
	R :1	3.357
Final drive	:1	3.789
Performance		
Power-to-weight ratio	kg/kW	10.4
Output per litre	kW/l	70.6
Acceleration 0–100 km	/h s	7.7
In 5th gear 80–120 km/h	S	
Top speed	km/h	227
BMW EfficientDynamics		
BMW EfficientDynamics standard features		Electric Power Steering, Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with coasting function, BMW EfficientLightweight, optimised aerodynamic attributes, map-regulated oil pump, tyres with reduced rolling resistance
Fuel Consumption ECE ²⁾		
Urban	l/100 km	7.2 – 6.8
Extra-urban	l/100 km	5.1 – 4.8
Combined	l/100 km	5.9 – 5.5
CO ₂	g/km	134 – 126
Emission rating		EU6

Specifications apply to ACEA markets/data relevant to homologation apply in part only to Germany (weight)

 $^{^{1)}\}mbox{Oil change}$ $^{2)}\mbox{Fuel consumption and CO}_{2}\mbox{ emissions depend on the selected tyre format$

The new BMW X2. xDrive20d, xDrive25d.

		BMW X2 xDrive20d	BMW X2 xDrive25d		
Body					
No of doors/seats		5/5	5/5		
Length/width/height (unladen)	mm	4360 / 1824 / 1526	4360 / 1824 / 1526		
Wheelbase	mm	2760	2760		
Track, front/rear	mm	1563 / 1562	1563 / 1562		
Ground clearance	mm	182	182		
Turning circle	m	11.3	11.3		
Fuel tank capacity	approx. I	51	51		
Engine oil ¹⁾	І	6.3	5.0		
Weight, unladen, to DIN/EU	kg	1600/1675	1585/1660		
Max load to DIN	kg	590	595		
Max permissible weight	kg	2190	2180		
Max axle load, front/rear	kg	1120/1100	1125/1085		
Max trailer load,	kg	2000 / 750	2000 / 750		
braked (12%)/unbraked	Νg	20001700	2000.700		
Max roofload/max towbar	kg	75 / 80	75 / 80		
download	Νg	767.66			
Luggage comp capacity	1	470 – 1355	470 – 1355		
Air resistance	Cd x A	0.28 x 2.37	0.29 x 2.37		
All registarioe	OUAH	0.20 x 2.07	0.E3 X E.01		
Power Unit					
Config/No of cyls/valves		In-line/4/4	In-line/4/4		
Engine technology	BMW TwinPower Turbo technology: turbocharger with variable inlet geometry,				
	common-rail direct injection				
Effective capacity	CC	1995	1995		
Stroke/bore	mm	90.0 / 84.0	90.0 / 84.0		
Compression ratio	:1	16.5	16.5		
Fuel		Diesel	Diesel		
Max output	kW/hp	140 / 190	170 / 231		
at	rpm	4000	4400		
Max torque	Nm	400	450		
at	rpm	1750 – 2500	1500 – 3000		
Electrical System					
Battery/installation	Ah/-	70 / Luggage compartment	70 / Luggage compartment		
Driving Dynamics and Safet Suspension, front		Single-joint spring-strut axle in lightweight	aluminium-steel construction		
Suspension, none	`	Single joint spring structure in lightweight	didifficial steel construction		
Suspension, rear	Multi-arm axle in lightweight steel construction with separate spring and				
	damper configuration				
Brakes, front		Single-piston floating-calliper d			
Brakes, rear		Single-piston floating-calliper d			
Driving stability systems	Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), DBC				
	(Dynamic Brake Control), brake drying function, Fading Compensation, Start- Off Assistant, EDLC (Electronic Differential Lock Control), Performance				
	Control, trailer stability control, HDC (Hill Descent Control), networked with				
	O.	xDrive all-wheel-drive system; optional:			
Safety equipment	Standard: airbags for driver and front passenger, side airbags for driver and				
23.23, 242,6	front passenger, head airbags for front and rear seats, three-point inertia-reel				
	seatbelts on all seats (belt latch tensioner and belt force limiter at the front				
		seats), crash sensors, tyre d			
Steering		Electric Power Steering (EPS) with			
		optional: M Servot			
Steering ratio, overall	:1	15.9	15.9		
Tyres, front/rear		225/55 R17 97W	225/55 R17 97W		
Rims, front/rear		7.5J x 17 light-alloy	7.5J x 17 light-alloy		


			BMW X2 xDrive20d	BMW X2 xDrive25d
Transmission				
Type of transmission			8-speed Steptronic	8-speed Steptronic
Gear ratios	I	:1	5.519	5.25
	II	:1	3.184	3.029
	III	:1	2.05	1.95
	IV	:1	1.492	1.457
	V	:1	1.235	1.221
	VI	:1	1.000	1.000
	VII	:1	0.801	0.809
	VIII	:1	0.673	0.673
	R	:1	4.221	4.015
Final drive		:1	2.851	2.955
Performance				
Power-to-weight ratio	kç	g/kW	11.4	9.3
Output per litre		kW/l	70.2	85.2
Acceleration 0–10	00 km/h	S	7.7	6.7
In 5th gear 80–12	0 km/h	S		
Top speed		km/h	221	237
BMW EfficientDyna	mics			
BMW EfficientDynamics standard features			Electric Power Steering, Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with coasting function, BMW EfficientLightweight, optimised aerodynamic attributes, map-regulated oil pump, tyres with reduced rolling resistance, efficiency- and weight-optimised all-wheel drive, BMW BluePerformance technology	
Fuel Consumption E	ECE ²⁾			
Urban	1/100) km	5.4 – 5.2	5.9 – 5.7
Extra-urban	1/100) km	4.5 – 4.3	4.9 – 4.7
Combined) km	4.8 – 4.6	5.3 – 5.1
CO ₂	(g/km	126 – 121	139 – 133
Emission rating	,	-	EU6	EU6

Specifications apply to ACEA markets/data relevant to homologation apply in part only to Germany (weight) $^{1)}$ Oil change $^{2)}$ Fuel consumption and CO_2 emissions depend on the selected tyre format


BMW Media Information 10/2017 Page 5

Output and torque diagrams. The new BMW X2. sDrive20i.






The new BMW X2. sDrive20d.



The new BMW X2. sDrive25d.

10/2017 Page 7



BMW Media Information 10/2017 Page 8

Exterior and interior dimensions. The new BMW X2.



