**BMW** Media Information

9/2012

Valid from 11/2012

## Specifications. BMW 1 Series 3 Door Hatch.

114d



		BMW 114d
Body		
Number of doors/seats		3 / 4 (5)
Length/Width/Height 1) (unladen)	mm	4324 / 1765 / 1421
Wheelbase	mm	2690
Track front/rear	mm	1535 / 1569
Ground clearance	mm	140
Turning circle	m	10.9
	approx. I	52
Cooling system incl. heating	І І	7.0
Engine oil 2)	<u>.</u>	5.2
Weight, unladen, to DIN/EU	kg	1305 / 1380
Max. load to DIN	kg	530
Max. perm. weight, overall	kg	1835
Max perm axle load front/rear	kg	875 / 1055
Max perm trailer load (12%)	kg	-1-
braked/unbraked		•
Perm roof load/trail download	kg	751-
Luggage capacity	I	360 – 1200
Air resistance	c <sub>X</sub> x A	0.30 x 2.14
Engine		
Configuration/No. of cyls./valves		R/4/4
Engine technology		BMW TwinPower Turbo technology: turbocharger with variable intake geometry, Common Rail direct injection with solenoid injectors, max. injection pressure: 1600 bar
Capacity	CC	1598
Stroke/bore	mm	83.6 / 78.0
Compression ratio	:1	16.5
Fuel grade		Diese
Max output	kW/hp	70 / 95
at	rpm	4000
Max torque	Nm	235
at	rpm	1500 – 2750
Electrical system		
Battery/installation	Ah/–	90 / luggage comp
Alternator	A/W	175 / 2450
Driving dynamics and safety		
		Develop inite against standard subministra
Suspension, front		Double-ioint spring-strut axie, aiuminium
Suspension, front Suspension, rear		Double-joint spring-strut axle, aluminium  Five-link rear axle, light steel, with double elastic bearings
Suspension, rear		Five-link rear axle, light steel, with double elastic bearings
	mm	Five-link rear axle, light steel, with double elastic bearings One-piston floating-calliper
Suspension, rear Brakes, front Diameter	mm	Five-link rear axle, light steel, with double elastic bearings One-piston floating-calliper
Suspension, rear Brakes, front Diameter Brakes, rear		Five-link rear axle, light steel, with double elastic bearings One-piston floating-calliper
Suspension, rear Brakes, front Diameter	mm	Five-link rear axle, light steel, with double elastic bearings One-piston floating-calliper
Suspension, rear Brakes, front Diameter Brakes, rear Diameter Diameter Driving stability systems		Five-link rear axle, light steel, with double elastic bearings One-piston floating-calliper  3) / vented One-piston floating-calliper  Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC (Cornering Brake Control), DBC (Dynamic Brake Control), Dry
Suspension, rear Brakes, front Diameter Brakes, rear Diameter		Five-link rear axle, light steel, with double elastic bearings  One-piston floating-calliper  One-piston floating-calliper  One-piston floating-calliper  Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC (Cornering Brake Control), DBC (Dynamic Brake Control), Dry Braking function, Fading Compensation, Start-Off Assistant Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia-reel seatbelts on all seats with belt latch tensioner and belt force limiter integrated in the front seats, crash sensors,
Suspension, rear Brakes, front Diameter Brakes, rear Diameter Driving stability systems  Safety features  Steering	mm	Five-link rear axle, light steel, with double elastic bearings  One-piston floating-calliper  One-piston floating-calliper  Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC (Cornering Brake Control), DBC (Dynamic Brake Control), Dry Braking function, Fading Compensation, Start-Off Assistant  Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia-reel seatbelts on all seats with belt latch tensioner and belt force limiter integrated in the front seats, crash sensors, Tyre Defect Indicator  Electric Power Steering (EPS), optional: Servotronic, variable sports steering
Suspension, rear Brakes, front Diameter Brakes, rear Diameter Driving stability systems  Safety features		Five-link rear axle, light steel, with double elastic bearings  One-piston floating-calliper  One-piston floating-calliper  Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC (Cornering Brake Control), DBC (Dynamic Brake Control), Dry Braking function, Fading Compensation, Start-Off Assistant Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia-reel seatbelts on all seats with belt latch tensioner and belt force limiter integrated in the front seats, crash sensors, Tyre Defect Indicator  Electric Power Steering (EPS),

9/2012

Valid from 11/2012

## Specifications. BMW 1 Series 3 Door Hatch.

BMW Connecte	dDrive			
Comfort			Optional: BMW Assist incl. Enquiry Service, remote-contro functions, Real Time Traffic Information, BMW TeleServices, integration of mobile devices	l
Infotainment			Optional: Internet access, BMW Online incl. Park Info, National Info, Google Local Search, News, Real-Time Weather BMW Routes, Office functions, Bluetooth Audio Streaming, Online Update Music Tracks, Apps	.,
Safety			Optional: Adaptive Headlights with cornering lights, variable ht distribution and adaptive headlight range control, High Beam Assis istance Control, rear-view camera, Active Cruise Control with braking Parking Assistant, Lane Departure Warning with rear-end collision w Speed Limit Info incl. No Passing Info, Automatic/Advanced Emerger	function, arning,
Transmission				
Type			Six-speed manual transmission	
Gear ratios	ı		Cix opoda mandar transmission	4.002
- Courtailos	<u> </u>	:1		2.109
		:1		1.380
	IV	:1		1.000
	V	:1		0.781
	V			0.761
	R			3.647
Final drive	K			
rinai unve		:1		2.929
Performance				
Power-to-weight	ratio (DIN)	kg/kW		18.6
Output per litre	,	kW/l		43.8
	0–100 km/h	S		12.2
	0–1000 m	S		33.5
	)–120 km/h	S		10.8 / 15.2
Top speed	, 120 1411111	km/h		185
BMW EfficientD	<u>-                                      </u>			
BMW EfficientDy measures as stan			Brake Energy Regeneration, Electric Power Steering (EPS), Auto Start Stop function, gear shift indicator (manual transmission), E mode, intelligent lightweight construction, on-demand operation of units, map-controlled oil pump, final drive with optimised warm-up b tyres with reduced rolling resistance	ECO PRO ancillary
	4)			
Fuel consumpti				
With standard wh				
		l/100 km		4.9
With standard wh				4.9
With standard wh Urban		l/100 km		
With standard wh Urban Extra-urban Composite CO <sub>2</sub>	eels and tyres	l/100 km l/100 km l/100 km g/km		3.7
With standard wh Urban Extra-urban Composite CO <sub>2</sub> With 7J x 16 whe With 7.5J x 17 wh With 7.5J x 17 wh	eels and tyres els and 205/5 neels and 225 neels at front,	I/100 km I/100 km I/100 km g/km 5 R16 tyre /45 R17 ty 8J x 17 at	s, with 7J x 17 wheels and 205/50 R 17 tyres and with winter tyres, res, the rear and 225/45 R17 tyres at front, 245/40 R17 at the rear, the rear and 225/40 R18 tyres at front, 245/35 R18 at the rear	3.7 4.1
With standard wh Urban Extra-urban Composite CO <sub>2</sub> With 7J x 16 whe With 7.5J x 17 wh With 7.5J x 17 wh	eels and tyres els and 205/5 neels and 225 neels at front,	I/100 km I/100 km I/100 km g/km 5 R16 tyre /45 R17 ty 8J x 17 at	res, the rear and 225/45 R17 tyres at front, 245/40 R17 at the rear,	3.7 4.1
With standard wh Urban Extra-urban Composite CO <sub>2</sub> With 7J x 16 whe With 7.5J x 17 wh With 7.5J x 17 wh With 7.5J x 18 wh	eels and tyres els and 205/5 neels and 225 neels at front,	I/100 km I/100 km I/100 km g/km 5 R16 tyre I/45 R17 ty 8J x 17 at 8J x 18 at I/100 km	res, the rear and 225/45 R17 tyres at front, 245/40 R17 at the rear,	3.7 4.1 109 5.0
With standard wh Urban Extra-urban Composite CO <sub>2</sub> With 7J x 16 whe With 7.5J x 17 wh With 7.5J x 18 wh With 7.5J x 18 wh Urban Extra-urban	eels and tyres els and 205/5 neels and 225 neels at front,	I/100 km I/100 km I/100 km g/km 5 R16 tyre /45 R17 ty 8J x 17 at 8J x 18 at I/100 km	res, the rear and 225/45 R17 tyres at front, 245/40 R17 at the rear,	3.7 4.1 109 5.0 3.8
With standard wh Urban Extra-urban Composite CO <sub>2</sub> With 7J x 16 whe With 7.5J x 17 wh With 7.5J x 18 wh Urban	eels and tyres els and 205/5 neels and 225 neels at front,	I/100 km I/100 km I/100 km g/km 5 R16 tyre I/45 R17 ty 8J x 17 at 8J x 18 at I/100 km	res, the rear and 225/45 R17 tyres at front, 245/40 R17 at the rear,	3.7 4.1 109

Technical data valid for ACEA markets/part of data relevant to homologation only apply to Germany (weights)

 $<sup>^{1)}</sup>$  Height including roof fin: 1440 mm  $^{2}$  Oil change quantity  $^{3)}$  Information not yet available  $^{4}$  Fuel consumption and  $\mathrm{CO}_2$  emissions depend on the selected tyre format