BMW Media Information

6/2012

valid from 7/2012

Specifications.

BMW 730d. BMW 740d.



		BMW 730d	BMW 740d	
Body				
No of doors/seats		4/5	4/5	
Length/width/height (unladen)	mm	5079 / 1902 / 1471	5079 / 1902 / 147	
Wheelbase	mm	3070	3070	
Track, front/rear	mm	1611 / 1650	1611 / 1650	
Ground clearance	mm	152	152	
Turning circle	m	12.2	12,2	
Tank capacity	app ltr	80	80	
Cooling system incl heater	ltr	8.8	8.8	
Engine oil ¹⁾	ltr	7.2	7.2	
Weight, unladen, to DIN/EU	kg	1840 / 1915	1865 / 1940	
Max load to DIN	kg	640	650	
Max permissible	kg	2505	2515	
Max axle load, front/rear	kg	1180 / 1405	1200 / 1410	
Max trailer load (12%),	kg	2100 / 750	2100 / 750	
braked/unbraked		21007750		
Max roofload/max towbardownl	kg	100 / 100	100 / 100	
Luggage comp capacity	ltr	500	500	
Air drag	Cd x A	0.28 x 2.42	0.28 x 2.42	
Power Unit				
Config/No of cyls/valves		In-line six / 4	In-line six / 4	
Engine technology	Turbo	ocharger with variable intake	BMW TwinPower Turbo	
		metry, common-rail direct	(Variable Twin Turbo), common-	
		njection with piezo injectors	rail direct fuel injection with	
	(max injection pressure:	piezo injectors (max injection	
Constitute of the state of		1800 bar)	pressure: 2000 bar)	
Capacity, effective	CC	2993	2993	
Stroke / bore	mm	90.0 / 84.0	90.0 / 84.0	
Compression ratio Fuel	:1	16.5	16.5	
	IAM/ba	Diesel	Diese	
Max output	kW/hp	190 / 258	230 / 313	
at Advitage of	rpm	4000	4300	
Max torque	Nm	560	630	
<u>at</u>	rpm	1500	1500	
Electrical System				
Battery/location	Ah/–	90 / luggage comp	90 / luggage comp	
Alternator	AW	180 / 2520	180 / 2520	
Driving Dynamics and Safety				
Suspension, front	Double-track control arm axle with separate lower track arm level in aluminium, small			
	steering roll radius, anti-dive			
Suspension, rear	Integral-V multi-arm axle in aluminium with steering function, anti-squat and anti-dive,			
	double acoustic separation, air suspension with automatic height adjustment			
Dualiza front	(air suspension with self-levelling standard on long-wheelbase version)			
Brakes, front	Single-piston swing-calliper disc brakes / vented			
Brakes, rear	calliper disc brakes / vented			
Driving stability systems	Standard: DSC incl ABS and DTC Dynamic Traction Control, CBC Cornering Brake Control, DBC Dynamic Brake Control, Dry Braking, Fading Compensation, Start-Off			
	Assistant, Dynamic Damping Control; optional: Dynamic Drive anti-roll stability			
0.6.		mar	nagement	
Safety equipment			nger, side airbags for driver and front passenger,	
			ets at the front, three-point inertia-reel seat belts front, crash sensors, Tyres Defect Indicator	
		<u> </u>	· · · · · · · · · · · · · · · · · · ·	
Steering	Elec		ed-related steering assistance (Servotronic) and itimised pump	
Steering transmission, overall	:1	17.1	17.1	
Tyres, front/rear		245/55 R17 102W RSC	245/50 R18 100Y RSC	
Rims, front/rear		8J x 17 light-alloy	8J x 18 light-alloy	

BMW

Media Information

6/2012

valid from 7/2012



			BMW 730d	BMW 740d			
BMW Connect	edDrive						
Convenience	edDiive	Optional: BMW Assist including Enquiry Service, remote-control function and RTTI Real Time Traffic Information, BMW TeleServices, integration of mobile devices, Rear Seat Entertainment, Comfort Access with contactless opening of the tailgate					
Infotainment		Optional: internet access, BMW Online including features such as Park Info, 3D City Mode, National Info, Google Local Search, News, Realtime Weather, Office functions, Speech to Text, BMW Routes, Online Update Music Tracks					
Safety		Optional: Adaptive Headlights with Cornering Lights, LED High-Beam Assistant, Park Distance Control, Side View, Top View, rear-view camera, BMW Parking Assistant, BMW Night Vision with pedestrian detection + Dynamic Light Spots, Head-Up Display, Active Cruise Control premium with Stop & Go and emergency brake assist, Lane Change Warning, Lane Departure Warning, Speed Limit Info with No Passing Info, Active Protection with Attentiveness assistant, Automatic/Advanced Emergency Call					
Transmission							
Type of transmis	ssion		Eight-speed automatic transmission w	ith Steptronic function			
Gear ratios	I	:1	4.714	4.714			
	II	:1	3.143	3.143			
	III	:1	2.208	2.208			
	IV	:1	1.667	1.667			
	V	:1	1.285	1.285			
	VI	:1	1.000	1.000			
	VII	:1	0.839	0.839			
	VIII	:1	0.667	0.667			
	Reverse	:1	3.317	3.317			
Final drive		:1	2.563	2.647			
Performance							
Power-to-weight	t ratio	kg/kW	9.7	8.7			
Output per litre		kW/hp	63.5	76.8			
Acceleration	0–100 km/h	sec	6.1	5.5			
Star	nding start km	sec	26.3	25.2			
Top speed		km/h	250	250			
BMW Efficient							
BMW EfficientDy features	ynamics standard	Vario	o Start-Stop function, ECO PRO mode, Brake Ene serve steering assistance pump, intelligent lightwe demand fuel pump, on-demand coolant pump, fin nagement, tyres with reduced rolling resistance, al Dynamic Drive with on-demand	eight technology, air flap control, on- nal drive with optimised thermal oc compressor detachable, optional			
Fuel Consump	EU Cycle						
Urban	,	ltr/100 km	6.8	6.9			
Extra-urban		ltr/100 km	4.8	4,8			
Combined		ltr/100 km	5.6	5.7			
CO ₂		g/km	148	149			
		5	EU5	EU5			

Specifications applicable to ACEA markets / homologation data applicable in part only to Germany (weight)

BMW

Media Information

6/2012

valid from 7/2012

