BMW Media Information

BMW 730Ld.



6/2012

valid from 7/2012

		BMW 730Ld	
		Siller 700Eu	
Body			
No of doors/seats		4/5	
Length/width/height (unladen)	mm	5219 / 1902 / 1481	
Wheelbase	mm	3210	
Track, front/rear	mm	1611 / 1650	
Ground clearance	mm	152	
Turning circle	m	12.7	
Tank capacity	app ltr	80	
Cooling system incl heater	Itr	8.8	
Engine oil ¹⁾	ltr	7.2	
Weight, unladen, to DIN/EU	kg	1875 / 1950	
Max load to DIN	kg	640	
Max permissible	kg	2535	
Max axle load, front/rear	kg	1190 / 1410	
Max trailer load (12%),	kg	113071110	
braked/unbraked	Ng	2100 / 750	
Max roofload/max towbardownl	kg	100 / 100	
Luggage comp capacity	ltr	500	
Air drag	Cd x A	0.28 x 2.42	
Power Unit			
Config/No of cyls/valves		In-line six / 4	
Engine technology	Turbo	charger with variable intake	
Engine technology		metry, common-rail direct	
		njection with piezo injectors	
	(m	nax, pressure: 1800 bar)	
Capacity, effective	CC	2993	
Stroke / bore	mm	90.0 / 84.0	
Compression ratio	:1	16.5	
Fuel		Diesel	
Max output	kW/hp	190 / 258	
at	rpm	4000	
Max torque	Nm	560	
at	rpm	1500	
Electrical System			
Battery/location	Ah/-	105 / / luggage comp	
Alternator	A/W	180 / 2520	
Aitemator	AVV	10072320	
Driving Dynamics and Safety			
Suspension, front	Double-track control arm axle with separate lower track arm level in aluminium constructior small steering roll radius, anti-dive		
Suspension, rear	Integral-V multi-arm axle in aluminium with steering function, anti-squat and anti-dive, double acoustic separation, air suspension with automatic height adjustment		
Brakes, front	Single-piston swing-calliper disc brakes / vented		
Brakes, rear	Single-piston swing-calliper disc brakes / vented		
Drivingstabilitysystems	Standard: DSC incl ABS and DTC Dynamic Traction Control, CBC Cornering Brake Control, DBC Dynamic Brake Control, Dry Braking, Fading Compensation, Start-Off Assistant, Dynamic Damping Control, optional: Dynamic Drive anti-roll stability management		
Safetyequipment	Standard: airbags for driver and front passenger, side airbags for driver and front passenge head airbags front and rear, active headrests at the front, three-point inertia-reel seat belts on all seats, belt latch tensioners at the front, crash sensors, Tyre Defect Indicator		
Steering	Elect		vith speed-related steering assistance (Servotronic) and CO ₂ -optimised pump
Steering transmission, overall	:1	17.1	
Tyres, front/rear		245/55 R17 102W RSC	
Rims, front/rear		8J x 17 light-alloy	·

BMW

Media Information

6/2012

valid from 7/2012



BMW 730Ld					
BMW Connected	Drive				
Convenience		Optional: BMW Assist including Enquiry Service, remote-control function and RTTI Real Time Traffic Information, BMW TeleServices, integration of mobile devices, Rear Seat Entertainment, Comfort Access with contactless opening of the tailgate			
Infotainment		Optional: internet access, BMW Online including features such as Park Info, 3D City Mod National Info, Google Local Search, News, Realtime Weather, Office functions, Speech to Text, BMW Routes, Online Update Music Tracks			
Safety		Optional: Adaptive Headlights with Cornering Lights, LED High-Beam Assistant, Park Distance Control, Side View, Top View, rear-view camera, BMW Parking Assistant, BMW Night Vision with pedestrian detection + Dynamic Light Spots, Head-Up Display, Active Cruise Control premium with Stop & Go and emergency brake assist, Lane Change Warning, Lane Departure Warning, Speed Limit Info with No Passing Info, Active Protectio with Attentiveness assistant, Automatic/Advanced Emergency Call			
Transmission					
Type oftransmission			Eight-speed automatic transmission with Steptronic function		
Gear ratios	<u> </u>	:			
	II	:1			
	III	:1			
	IV	:1			
	V	:1			
	VI	:1	***		
VII VIII Reverse		:1	0.839		
		:1			
	Reverse	:1	3.317		
Final drive		:1	2.563		
Performance					
Power-to-weight ra	tio	kg/kW	9.9		
Output per litre		kW/hp	63.5		
Acceleration 0-	100 km/h	sec	6.2		
Standing start km		sec	26.4		
Top speed		km/h	250		
BMW EfficientDy	namics				
BMW EfficientDyna features			Auto Start-Stop function, ECO PRO mode, Brake Energy Regeneration, coasting mode, Varioserve steering assistance pump, intelligent lightweight technology, air flap control, ondemand fuel pump, on-demand coolant pump, final drive with optimised thermal management, tyres with reduced rolling resistance, a/c compressor detachable, optional Dynamic Drive with on-demand pump control		
Fuel Consump El	I Cycle				
Urban	Joycie	ltr/100 km	6.8		
Extra-urban		ltr/100 km	4.8		
Combined		ltr/100 km	5.6		
CO ₂		g/km	148		
Emission rating		g/NIII	EU5		
			LUJ		

Specifications applicable to ACEA markets / homologation data applicable in part only to Germany (weight)