BMW Media Information

6/2012

Valid from

7/2012

Specifications BMW 3 Series Sedan. 320d xDrive



		BMW 320d xDrive
Body		415
No of doors / seats		4/5
Length/width/height (unladen)	mm	4624 / 1811 / 1434
Wheelbase	mm	2810
Track, front/rear	mm	1543 / 1582
Ground clearance		145
Turning circle	m	11,7
Tank capacity		57
Cooling system incl heater	ltr	7,0 (7,0)
Engine oil ¹⁾	ltr	5,2
Weight, unladen, to DIN/EU	kg	1510 / 1520 (1585 / 1595)
Max load to DIN	ka	540
	kg	
Max permissible	kg	2050 (2060)
Max axle load, front / rear	kg	980 / 1145
Max trailer load (12%), braked / unbraked	kg	1600 / 750
Max roofload / max download	kg	75 / 75
Luggage comp	ltr	480
Air drag	cd x A	0,28 x 2,20
Power Unit		
Configuration/No of cyls/valves		In-line / 4 / 4
,		
Engine technology		BMW TwinPower Turbo technology with variable- geometry turbocharger, Common Rail direct injection with piezo injectors (max. injection pressure: 1800 bar)
Capacity, effective	CC	1995
Stroke / bore	mm	90,0 / 84,0
Compression ratio	:1	16,5
Fuel		Diesel
Max output	kW/hp	135 / 184
at	rpm	4000
Max torque	Nm/lb-ft	380
at	rpm	1750 – 2750
Electrical System	A1./	00.11
Battery / installation	Ah/–	90 / Luggage compartment
ternator	A/W	180 / 2520
Driving Dynamics and Safet	· · · · · · · · · · · · · · · · · · ·	
Suspension, front	· y	Double-joint spring strut axle in aluminium with displaced castor, small positive steering roll radius, compensation of lateral forces, anti-dive
Companies and		
Suspension, rear		Five-arm axle in lightweight steel
Brakes, front		Single-piston swing-calliper disc brakes / vented
Brakes, rear		Single-piston swing-calliper disc brakes / vented
Driving stability systems		Standard: xDrive all-wheel-drive system, DSC incl ABS and DTC Dynamic Traction Control, CBC Cornering Brake Control, DBC Brake Assistant, Dry Braking, Fading Compensation.
Safety		Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags front and rear, three-point inertia-reel belts on all seats, with belt retainer, belt latch tensioner and belt force limiter at the front, crash-activated headrests at the front, crash sensors, Tyre Defect Indicator
Steering		Electric Power Steering (EPS), optional: Servotronic Function,
		Variable Sport Steering
Steering ratio, overall	:1	15,2
Tyres, front/rear Wheels, front/rear		205/60 R16 92V 7J x 16 Light Alloy

BMW Media Information

6/2012

Valid from

7/2012

Specifications BMW 3 Series Sedan. 320d xDrive

		DMM 2204
		BMW 320d xDrive
PMW Connected Drive		
Comfort		Optional: BMW Assist including information service, remote functions, Real- rime Traffic Information, BMW TeleServices, mobile device integration
Infotainment	C	Optional: access to the internet, BMW Online incl Parkinfo, National Info, Google directory search, news, realtime weather, BMW Routes, office functions, Bluetooth audio streaming and music title update online, apps
Safety	a c F C	Optional: Adaptive Headlights with turning lights, variable light distribution and daptive headlight range adjustment, high beam assistance, park distance ontrol, rear view camera, Surround View incl. Side View and Top View, BMW lead-Up Display, cruise control with brake function, Parking Assistant, Lane Chance Warning, Lane Departure Warning with Collision Warning, speed limit and no passing information, Active Protection, extended emergency call
Transmission		
Type of transmission		Six-speed manual (optional: eight-speed-automatic)
Gear ratios	:1	4,110 (4,714)
	:1	2,248 (3,143)
	:1	1,403 (2,106)
IV	:1	1,000 (1,667)
V	:1	0,802 (1,285)
VI	:1	0,659 (1,000)
VII	:1	- (0,839)
VIII	:1	- (0,667)
R	:1	3,727 (3,295)
Final Drive	:1	3,231 (2,813)
I illai Dilve	.1	3,23 (2,013)
Performance		
Power-to-weight ratio	kg/kW	11,2 (11,3)
Output per litre	kW/l	67,7
Acceleration 0–100 km/h	sec	7,5 (7,4)
standing-start	sec	27,9 (27,8)
In 4th/5th gear80–120 km/h	sec	6,3 / 8,1
Top speed	km/h	233 (228)
BMW EfficientDynamics		
BMW EfficientDynamics,	Е	Brake Energy Regeneration, electromechanical power steering, Automatic
standard features	S d E	Start/Stop function, ECO PRO mode, intelligent lightweight construction, on- lemand operation of ancillary units, map-regulated oil pump, air flap control, clectric Power Steering (EPS), detachable ac compressor, differential with iptimized-warm-up behaviour, tyres with reduced rolling resistance
Fuel Consump in EU Cycle		
Urban	ltr/100k	6,2 (5,7)
Extra-urban	Itr/100k	4,1 (4,1)
Combined	ltr/100k	4,8 (4,7)
CO ₂	g/km	127 (124)
Emission rating	g/KITI	EU5
With 7,5J x 16 wheels and 225/ wheels at front, 8,5J x 17 wheel 18 wheels and 225/45 R18 tyre	s at rear an s, with 8J x at rear, with	es, with 7,5J x 17 wheels and 225/50 R 17 tyres, with 7,5J x 17 d 225/50 R17 tyres at front, 255/45 R17 tyres at rear, with 8J x t 18 wheels at front, 8,5J x 18 wheels at rear and 225/45 R18 n 8J x 19 wheels at front, 8,5J x 19 wheels at rear and 225/40
Urban	ltr/100k	6,3 (5,8)
Extra-urban	ltr/100k	4,1 (4,2)
Combined	ltr/100k	4,9 (4,8)
CO ₂	g/km	128 (125)
Emission rating		EU5

Specifications apply to ACEA markets/data relevant to homologation apply in part only to Germany (weight) Figures in brackets apply to models with automatic transmission