**BMW** Media Information

1/2012

Valid from 3/2012

## Specifications. The new BMW 1 Series. 125i



		BMW 125i
Body		
No. of doors/seats		5/:
L/W/H <sup>1)</sup> (unladen)	mm	4324 / 1765 / 142
Wheelbase	mm	2690
Front/rear track	mm	1521 / 1556
Ground clearance	mm	140
Turning circle	m	10.9
Fuel capacity	approx. I	52
Cooling and heating system	арргол. Г	7.0 (7.6
reservoir capacity Engine oil capacity <sup>2)</sup>	<u>'</u>	5.75
Weight, unladen (DIN/EU)	kg	1345 / 1420
	ı vg	(1365 / 1440
Payload (DIN)	kg	530
Permitted total weight	kg	1875 (1895)
Permitted axle load, front/rear	kg	885 (895) / 1070
Permitted trailer load (12%) braked/unbraked	kg	1200 / 680
Permitted roof load/trailer download	kg	75 / 75
Luggage compartment capacity	I	360 – 1200
Aerodynamic drag	c <sub>c</sub> x A	0.32 x 2.14
Engine		
Type/no. of cylinders/valves		in-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology with twin-scroll turbocharger, HighPrecision Injection, VALVETRONIC fully variable valve control and Double-VANOS variable camshaft control
Effective capacity	CC	1997
Stroke/bore	mm	90.1/84.0
Compression ratio	:1	90.1784.0
<u>'</u>		min. RON 9
Fuel type	1.3 \$ 1/1= -=	
Output	kW/hp min <sup>-1</sup>	160 / 218
at rpm	Nm	
Torque (with overboost) at rpm	min <sup>-1</sup>	1350–4800
	111111	1000 4000
Electrical		
Battery charge/location	Ah/–	80 / luggage compartment
Alternator current/output	A/W	170 / 2380
Driving Dynamics and Safety		
Front suspension		Aluminium double-joint cross-strut axle
Rear suspension		Lightweight steel five-link with double elastic bearing
Front brakes		Single-piston sliding-caliper disc brakes
Diameter	mm	<sup>3)</sup> /air-cooled
Rear brakes		Single-piston sliding-caliper disc brakes
Diameter	mm	<sup>3)</sup> /air-cooled
Driving stability systems		As standard: DSC inc. ABS, ASC and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, hill assist
Safety equipment		As standard: driver and front-seat passenger airbags, driver and front-seat passenger side airbags, front and rear head airbags, three-point automatic seatbelts for all seats, seatbelt tensioners and seatbelt force limiters in front seats, crash sensors, tyre pressure warning
Steering		Electromechanical power steering (EPS). Optional: Servotronic function, Variable Sport Steering
Overall steering ratio	:1	15.0
		15.0
Overall steering ratio Front/rear tyres		205/50 R17 89W

## **BMW** Media Information

1/2012

Valid from 3/2012

## Specifications. The new BMW 1 Series.

		BMW 125i
BMW ConnectedDrive		
Comfort		Optional: BMW Assist including information service, remote functions, Real-Time Traffic Information, BMW TeleServices, mobile device integration
Information and entertainment		Optional: Internet connectivity, BMW Online including parking information, country information, Google business search, news, real-time weather, BMW Routes, office functions, Bluetooth audio streaming, online music title update, apps
Safety		Optional: Adaptive Headlights with turning lights, variable light distribution, Adaptive Headlight range adjustment, high beam assistance, park distance control, reversing camera, cruise control with brake function, parking assistant, Lane Departure Warning with Collision Warning, speed limit and no passing information, extended emergency call
Transmission		
Type of gearbox		6-speed manual (optional: 8-speed automatic with Steptronic)
Gear ratios I	:1	3.683 (4.714)
	:1	2.062 (3.143)
	:1	1.313 (2.106)
IV	:1	1.000 (1.667)
V	:1	0.809 (1.285)
VI	:1	0.677 (1.000)
VII	:1	- (0.839)
VIII	:1	- (0.667)
R	:1	3.348 (3.295)
Differential ratio	:1	3.909 (3.077)
Performance		
Weight-to-power ratio (DIN unladen)	kg/kW	8.4 (8.5)
Specific power output	kW/l	80.1
Acceleration 0–100 km/h	sec.	6.4 (6.5)
0–1,000 m	sec.	26.0 (26.5)
in 4th/5th gear 80–120 km/h	sec.	5.9/7.5
Max. speed	km/h	245 (243)
BMW EfficientDynamics		
BMW EfficientDynamics Feature included as standard	es	Brake Energy Regeneration, electromechanical power steering, Automatic Start/Stop function, gear shift indicator (manual), ECO PRO mode, intelligent lightweight construction, automatically disconnecting ancillary components, map-regulated oil pump, differential with optimized-warm-up behaviour, tyres with reduced rolling resistance
Fuel consumption (EU)		
	l/100 km	8.6 (8.2)
	1/100 km	5.4 (5.3)
	1/100 km	5.4 (3.3)
CO <sub>2</sub> emissions	g/km	154 (149)
		134 (143)

Technical data valid for ACEA countries/Some permitted weights valid only for Germany Figures in brackets are for vehicles with automatic transmission

Height with roof aerial: 1440 mm
 Oil change volume
 Not yet available