\mathbf{BMW}

Media Information

12/2013

Valid from 3/2014

Specifications BMW X1. X1 sDrive20d EfficientDynamics Edition



		BMW X1 sDrive20d EfficientDynamics Edition
D. d.		
Body No of doors/seats		5/5
		4477 / 1798 / 1545
Length/width/height ¹⁾ (unladen)	mm	
Wheelbase	mm	2760
Track, front/rear	mm	1500 / 1529
Turning circle	m	11.3
Tank capacity	approx. l	61
Cooling system incl heating		7.2
Engine oil ²⁾		5.2
Weight, unladen, to DIN/EU	kg	1490 / 1565
Max load to DIN	kg	550
Max permissible weight	kg	2045
Max axle load, front/rear	kg	940 / 1160
Max trailer load, braked (12%)/unbraked	kg	1700 / 750
Max roof load/towbar download	kg	75 / 80
Luggage comp capacity		420 – 1350
Air drag	c _d x A	0.32 x 2.33
Engine		
Configuration/No of cyls/valves		R/4/4
Engine technology		BMW TwinPower Turbo technology: turbocharger with variable intake geometry, common-rail direct injection, max injection pressure: 1800 bar
Effective capacity	cm ³	1995
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel grade		diesel
Output	kW/hp	120 / 163
at	rpm	4000
Torque	Nm	380
at	rpm	1750 – 2750
Electrical system		
Battery/Installation	Ah/-	80 / luggage comp
Alternator	A/W	180 / 2520
Driving dynamics and safety	,	
Suspension, front		Double-joint spring strut tie bar axle
Suspension, rear		Five-arm axle with longitudinal control arm and double wishbone
Brakes, front		Single-piston floating-calliper disc brakes
Diameter	mm	312 x 24/vented
Brakes, rear	111111	Single-piston floating-calliper disc brakes
Diameter	mm	300 x 20/vented
Driving stability systems	111111	Standard: DSC incl ABS and DTC (Dynamic Traction Control),
		CBC (Cornering Brake Control), DBC Dynamic Brake Control), Dry Braking function, Fading Compensation, Hill Start Assist
Safety equipment		Standard: Airbags for driver and front passenger, side airbags for driver and front passenger, head airbags front and rear, three-point inertia-reel seatbelts on all seats with belt latch tensioner and belt force limiter in the front, crash sensors, Tyre Defect Indicator
Steering		EPS (Electric Power Steering), optional: Servotronic
Steering ratio, overall	:1	16.1
Tyres, front/rear		225/50 R17 94W

12/2013

Valid from 3/2014

Specifications BMW X1.

			BMW X1 sDrive20d EfficientDynamics Edition	
BMW Connec	tedDrive			
Convenience	CUDINC	Optional: Concierge Services, remote-control functions, Real Time Traffic Information, BMW TeleServices, integration of mobile devices		
Infotainment		Optional: Internet access, BMW Online incl inter alia Park Info, National Info, Google Local Search, News, Realtime Weather, BMW Routes, Office functions, Bluetooth Audio Streaming, Online Update Music Tracks, Apps		
Safety		Optional: Adaptive Headlights with cornering lights, High-Beam Assistant, Park Distance Control, rear-view camera, Cruise Control with braking function, Automatic/Advanced Emergency Call		
Transmission				
Type of gearbox	X		Six-speed manual	
Gear ratios			4.110	
	II	:1	2.248	
	III	:1	1.403	
	IV	:1	1.000	
	V	:1	0.802	
	VI	:1	0.659	
	R	:1	3.727	
Final drive		:1	2.929	
Performance				
Power-to-weigh	nt ratio (DIN)	kg/kW	12.4	
Output per litre		kW/l	60.2	
Acceleration	0-100 km/h	S	8.3	
	0–1000 m	S	29.3	
in 4th/5th gear	80-120 km/h	S	7.1 / 9.5	
Top speed		km/h	215	
Offroad specif	fications			
Overhang angle	e, front/rear		18.0 / 22.2	
Ramp angle		0	16,8	
Ground clearand	ce unladen	mm	179	
BMW Efficient	tDynamics			
BMW EfficientD standard feature	•		Brake Energy Regeneration, Optimum Shift Indicator, Auto Start-Stop function, ECO PRO mode (optional), EPS (Electric Power Steering), on-demand operation of ancillary units, final drive with optimised warm-up running qualities, intelligent lightweight design, disengageable climate compressor, tyres with reduced rolling resistance	
Eugl eg :: ::::::	ation Ell			
Fuel consump	ouon EU	1/100 1/	5.2	
Urban Extra-urban		I/100 km	4.1	
Combined		I/100 km	4.1	
CO ₂			4.5	
	~	g/km		
Emissions rating	9		EU5	

Specifications apply to ACEA markets; data relevant to homologation applicable in part only to Germany (weight, top speed)

Height including roof antenna: 1567 mm
 Oil change quantity