BMW Media Information

2/2015

Valid from 3/2015

Specifications BMW 5 Series Sedan. 520d xDrive.



		BMW 520d xDrive
Body		
No of doors/seats		4/5
Length/width/height 1) (unladen)	mm	4907 / 1860 / 1464
Wheelbase	mm	2968
Track, front/rear	mm	1600 / 1627
Ground clearance	mm	141 12.0
Turning circle Tank capacity	app ltr	70
Cooling system incl heater	app Iti	7.0
Engine oil 2)	Itr	5.0
Weight, unladen, to DIN/EU	kg	
Max load to DIN	kg	600
Max permissible weight	kg	2330
Max axle load, front/rear	kg	1170 / 1300
Max trailer load (12%), braked/unbraked	kg	2000 / 750
Max roofload/max towbar downloa	ad kg	100 / 90
Luggage comp capacity	ltr	520
Air resistance	Cd x A	0.25 x 2.35
		V
Engine		
Config/No of cyls/valves		Straight-four / 4
Engine technology		BMW TwinPower Turbo technology:
		variable-geometry turbocharger, Common Rail direct injection with solenoid valve injectors (max. injection pressure: 2000 bar)
Capacity, effective	CC	1995
Stroke / bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel grade	• • • • • • • • • • • • • • • • • • • •	Diesel
Max output	kW/hp	140 / 190
at	rpm	4000
Max torque	Nm	400
at	rpm	1750 – 2500
Electrical System		
Battery/installation	Ah/-	90 / luggage comp
Alternator	A/W	220 / 3080
Driving Dynamics and Safety		
Suspension, front		Double track control arm axle with separate lower track arm level, aluminium, small steering roll radius, anti-dive
Suspension, rear		Integral-V multi-arm axle, aluminium, anti-squat and anti-dive, double acoustic separation
Brakes, front		Single-piston aluminium floating-calliper disc brakes in frame structure
Diameter	mm	330 x 24 / inner-vented
Brakes, rear		Single-piston aluminium floating-calliper disc brakes
Diameter	mm	330 x 20 / inner-vented
Driving stability systems	Ç	Standard: DSC incl ABS and Dynamic Traction Control (DTC), Cornering Brake Control (CBC), Dynamic Brake Control (DBC), Dry Braking function, Fading Compensation, Start-Off Assistant, linked to xDrive all-wheel-drive system in Integrated Chassis Management (ICM); optional: Dynamic Damper Control
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags for front and rear seats, three-point inertia-reel belts on all seats with belt stopper, belt tightener and belt force limiter at the front, crash-activated headrests at the front, crash sensors, Tyre Defect Indicator
Steering		Hydraulic rack-and-pinion power steering with Servotronic
Steering transmission, overall	:1	17.1
Tyres, front/rear		225/55 R17 97W
Rims, front/rear		8J x 17 light-alloy

BMW

Media Information

2/2015

Valid from 3/2015

Specifications BMW 5 Series Sedan.

			BMW 520d xDrive
Transmission	n		
Type of gearbo	OX		8-speed Steptronic
Gear ratios	I	:1	5.000
	II	:1	3.200
	III	:1	2.143
	IV	:1	1.720
	V	:1	1.314
	VI	:1	1.000
	VII	:1	0.822
	VIII	:1	0.640
	R	:1	3.456
Final drive		:1	2.929
Performance	<u> </u>		
Power-to-weig	ht ratio (DIN)	kg/kW	12.4
Output per litre	Э	kW	70.2
Acceleration	0-100 km/h	sec	7.9
in 5th gear	80-120 km/h	sec	-
Top speed		km/h	230
BMW Efficier	ntDynamics		
BMW Efficient standard featur			Brake Energy Regeneration with recuperation display, Auto Start Stop function, ECO PRO mode with coasting function, intelligent lightweight construction, on-demand operation of ancillary units, air flap control, detachable alc compressor, efficiency-optimised rear differential and power divider, tyres with reduced roll resistance, BMW BluePerformance technology
Fuel consum	ption EU ³⁾		
With standard	wheels and tyre	s: 8J x 17 v	heels, 225/55 R17 tyres
Urban		ltr/100 km	5.2
Extra-urban		ltr/100 km	4.1
Combined		ltr/100 km	4.5
CO ₂		g/km	119
With 8J x 18 w	heels and 245/4	45 R18 tyre	s and with winter tyres
Urban		ltr/100 km	5.4

4.3

4.7

124

5.7

4.5

4.9

129 EU6

Specifications applicable to ACEA markets. data relevant to homologation applicable in part only to Germany (weight)

With 8J x 18 wheels at front, 9J x 18 at rear and 245/45 R18 tyres at front, 275/40 R18 at rear With 8.5J x 19 wheels at front, 9J x 19 at rear and 245/40 R19 tyres at front, 275/35 R19 at rear With 8.5J x 20 wheels at front, 9J x 20 at the rear and 245/35 R20 tyres at front, 275/30 R20 at the rear

Extra-urban

Combined

Urban

CO₂

Extra-urban

Combined

Emission rating

Itr/100 km

Itr/100 km

ltr/100 km

Itr/100 km

Itr/100 km

g/km

g/km

 $^{^{1)}}$ Height with roof aerial: 1475 mm $^{2)}$ Oil change $^{3)}$ Fuel consumption and CO_2 emissions depend on the selected tyre format