BMW Media Information

10/2018 Page 1

Technical specifications. The new BMW 3 Series Sedan. 330i.



		DMW 220: Coden
		BMW 330i Sedan
Body		
No of doors/seats		4/5
Length/width/height 1)	mm	4709 / 1827 / 1442
(unladen)		
Wheelbase	mm	2851
Track, front/rear	mm	1589 / 1604
Ground clearance	mm	136
Turning circle	m	11.4
Fuel tank capacity	approx. I	59
Engine oil ²⁾	1	5.25
Weight, unladen, to DIN/EU	kg	1470 / 1545
Max load to DIN	kg	580
Max permissible weight	kg	2060
Max axle load, front/rear	kg	985 / 1160
Max trailer load, braked	kg	
(12%)/unbraked		1600 / 750
Max roofload/max towbar	kg	75 / 75
download		
Luggage comp capacity	<u> </u>	480
Air resistance	C _d x A	0.24 x 2.22
Power Unit		
Config/No of cyls/valves		In-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology: TwinScroll turbocharger, High Precision
		Direct Injection, VALVETRONIC fully variable valve control,
		Double-VANOS variable camshaft timing
Effective capacity	CC	1998
Stroke/bore	mm	94.6 / 82.0
Compression ratio	:1	10.2
Fuel	1.1.47/1	min. RON 91
Max output	kW/hp	190 / 258
at	rpm	5000 – 6500
Max torque	Nm	400
at	rpm	1550 – 4400
Electrical System		
Battery/installation	Ah/–	Q0 / luggago compartment
Datter y/II istaliation	AIII	90 / luggage compartment
Driving Dynamics and Saf	fotv	
Suspension, front	ety	Double-joint spring-strut axle in lightweight aluminium-steel construction,
Suspension, none		hydraulically damped torque strut bearings
Suspension, rear		Five-link axle in lightweight aluminium-steel construction
Brakes, front		Single-piston floating-calliper disc brakes, vented
Brakes, rear		Single-piston floating-calliper disc brakes, vented
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering
Driving diability dydicinio		Brake Control), DBC (Dynamic Brake Control), Performance Control, Dry Braking
	•	function, Fading Compensation, Start-Off Assistant;
		optional: Adaptive M suspension, M Sport differential
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and front
, , ,		passenger, head airbags front and rear, three-point inertia-reel seatbelts for all
		seats, front seats with belt stopper, belt latch tensioner and belt force limiter,
		crash-active front head restraints, crash sensors, tyre pressure indicator
Steering		Electric Power Steering (EPS) with Servotronic function;
		optional: variable sport steering
Steering ratio, overall	:1	14.1
Tyres, front/rear		225/50 R17 98Y XL
Rims, front/rear		7.5J x 17 light-alloy

		BMW 330i Sedan
Transmission		
Type of transmission		Eight-speed Steptronic transmission
Gear ratios	l :1	5.250
	ll :1	3.360
	III :1	2.172
	IV :1	1.720
	V :1	1.316
	VI :1	1.000
	VII :1	0.822
	VIII :1	0.640
	R :1	3.712
Final drive	:1	2.813
Performance		
Power-to-weight ratio (DII	V) kg/kW	7.7
Output per litre	kW/l	95.1
Acceleration 0-100 k	m/h s	5.8
Top speed	km/h	250
BMW EfficientDynamic	cs	
BMW EfficientDynamics standard features		Brake Energy Regeneration with recuperation display, Electric Power Steering (EPS), Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with coasting function and Proactive Driving Assistant, BMW EfficientLightweight, optimised aerodynamic attributes, active air flap control, on-demand operation of ancillary units, map-regulated oil pump, differential with optimised warm-up behaviour, tyres with reduced rolling resistance
Fuel Consumption ECI	.	
Urban	I/100 km	7.7 – 7.2
Extra-urban	l/100 km	5.2 – 5.0
Combined	l/100 km	6.1 – 5.8
CO ₂	g/km	139 – 132
Emission rating	5,,,,,,	Euro 6d-TEMP

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight)

The fuel consumption, CO_2 emissions and electric power consumption figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are already based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO_2 emissions, the CO_2 values may differ from the values stated here (depending on national legislation).

Further information on official fuel consumption figures and specific CO_2 emission values of new passenger cars is included in the following guideline: Leitfaden über den Kraftstoffverbrauch, die CO_2 -Emissionen und den Stromverbrauch neuer Personenkraftwagen' (Guide to the fuel economy, CO_2 emissions and electric power consumption of new passenger cars), which can be obtained free of charge from all dealerships, from Deutsche Automobil Treuhand GmbH (DAT), Hellmuth-Hirth-Str. 1, 73760 Ostfildern-Scharnhausen and at https://www.dat.de/co2/.

¹⁾ Height including roof fin ²⁾ Oil change

The new BMW 3 Series Sedan. 320d.

No of doors/seats	
No of doors/seats	
Length/width/height ¹⁾ mm 4709 / 1827 / 1442 (unladen) Wheelbase mm 2851 Track, front/rear mm 1589 / 1604 Ground clearance mm 136 Turning circle m 11.4 Fuel tank capacity approx. I 40 Engine oil ²⁾ I 5.5 Weight, unladen, to DIN/EU kg 1450 / 1525 (1455 / 1530) Max load to DIN kg 610 Max permissible weight kg 2075 (2085) Max axle load, front/rear kg 970 / 1180 Max trailer load, braked kg 1600 / 745 (750) Max roofload/max towbar kg 75 / 75 download Luggage comp capacity I 480 Air resistance C _d x A 0.23 x 2.22 Power Unit Config/No of cyls/valves In-line / 4 / 4	
(unladen) Wheelbase mm 2851 Track, front/rear mm 1589 / 1604 Ground clearance mm 136 Turning circle m 11.4 Fuel tank capacity approx. I 40 Engine oil 29 I 5.5 Weight, unladen, to DIN/EU kg 1450 / 1525 (1455 / 1530) Max load to DIN kg 610 Max permissible weight kg 2075 (2085) Max axle load, front/rear kg 970 / 1180 Max trailer load, braked kg 1600 / 745 (750) Max roofload/max towbar kg 75 / 75 download Luggage comp capacity I 480 Air resistance cd x A 0.23 x 2.22 Power Unit Config/No of cyls/valves In-line / 4 / 4	
Wheelbase mm 2851 Track, front/rear mm 1589 / 1604 Ground clearance mm 136 Turning circle m 11.4 Fuel tank capacity approx. I 40 Engine oil 20 I 5.5 Weight, unladen, to DIN/EU kg 1450 / 1525 (1455 / 1530) Max load to DIN kg 610 Max permissible weight kg 2075 (2085) Max axle load, front/rear kg 970 / 1180 Max trailer load, braked kg 1600 / 745 (750) Max roofload/max towbar kg 75 / 75 download Luggage comp capacity I 480 Air resistance C _d x A 0.23 x 2.22 Power Unit Config/No of cyls/valves In-line / 4 / 4	
Track, front/rear mm 1589 / 1604 Ground clearance mm 136 Turning circle m 11.4 Fuel tank capacity approx. I 40 Engine oil ²⁾ I 5.5 Weight, unladen, to DIN/EU kg 1450 / 1525 (1455 / 1530) Max load to DIN kg 610 Max permissible weight kg 2075 (2085) Max axle load, front/rear kg 970 / 1180 Max trailer load, braked kg (12%)/unbraked Max roofload/max towbar kg 75 / 75 download Luggage comp capacity I 480 Air resistance C _d x A 0.23 x 2.22 Power Unit Config/No of cyls/valves In-line / 4 / 4	
Ground clearance mm 136 Turning circle m 11.4 Fuel tank capacity approx. I 40 Engine oil 2) I 5.5 Weight, unladen, to DIN/EU kg 1450 / 1525 (1455 / 1530) Max load to DIN kg 610 Max permissible weight kg 2075 (2085) Max axle load, front/rear kg 970 / 1180 Max trailer load, braked kg (12%)/unbraked Max roofload/max towbar download kg 75 / 75 Luggage comp capacity I 480 Air resistance cd x A 0.23 x 2.22 Power Unit Config/No of cyls/valves In-line / 4 / 4	
Turning circle m 11.4 Fuel tank capacity approx. I 40 Engine oil 2) I 5.5 Weight, unladen, to DIN/EU kg 1450 / 1525 (1455 / 1530) Max load to DIN kg 610 Max permissible weight kg 2075 (2085) Max axle load, front/rear kg 970 / 1180 Max trailer load, braked kg (12%)/unbraked Max roofload/max towbar download kg 75 / 75 Luggage comp capacity I 480 Air resistance cd x A 0.23 x 2.22 Power Unit In-line / 4 / 4	
Fuel tank capacity approx. I 40 Engine oil 2) I 5.5 Weight, unladen, to DIN/EU kg 1450 / 1525 (1455 / 1530) Max load to DIN kg 610 Max permissible weight kg 2075 (2085) Max axle load, front/rear kg 970 / 1180 Max trailer load, braked kg (129%)/unbraked Max roofload/max towbar download kg 75 / 75 Luggage comp capacity I 480 Air resistance cd x A 0.23 x 2.22 Power Unit Config/No of cyls/valves In-line / 4 / 4	
Engine oil 2) I 5.5 Weight, unladen, to DIN/EU kg 1450 / 1525 (1455 / 1530) Max load to DIN kg 610 Max permissible weight kg 2075 (2085) Max axle load, front/rear kg 970 / 1180 Max trailer load, braked kg (1290)/unbraked 1600 / 745 (750) Max roofload/max towbar download kg 75 / 75 480 Air resistance cd x A 0.23 x 2.22 Power Unit Config/No of cyls/valves In-line / 4 / 4	
Weight, unladen, to DIN/EU kg 1450 / 1525 (1455 / 1530) Max load to DIN kg 610 Max permissible weight kg 2075 (2085) Max axle load, front/rear kg 970 / 1180 Max trailer load, braked kg 1600 / 745 (750) Max roofload/max towbar kg 75 / 75 download Luggage comp capacity I 480 Air resistance cd x A 0.23 x 2.22 Power Unit Config/No of cyls/valves In-line / 4 / 4	
Max load to DIN kg 610 Max permissible weight kg 2075 (2085) Max axle load, front/rear kg 970 / 1180 Max trailer load, braked kg 1600 / 745 (750) Max roofload/max towbar download kg 75 / 75 Luggage comp capacity I 480 Air resistance cd x A 0.23 x 2.22 Power Unit Config/No of cyls/valves In-line / 4 / 4	
Max permissible weight kg 2075 (2085) Max axle load, front/rear kg 970 / 1180 Max trailer load, braked kg 1600 / 745 (750) Max roofload/max towbar kg 75 / 75 download Luggage comp capacity I 480 Air resistance C _d x A 0.23 x 2.22 Power Unit Config/No of cyls/valves In-line / 4 / 4	
Max axle load, front/rear kg 970 / 1180 Max trailer load, braked kg 1600 / 745 (750) Max roofload/max towbar kg 75 / 75 download Luggage comp capacity I 480 Air resistance C _d x A 0.23 x 2.22 Power Unit Config/No of cyls/valves In-line / 4 / 4	
Max trailer load, braked (12%)/unbraked kg (12%)/unbraked 1600 / 745 (750) Max roofload/max towbar download kg 75 / 75 Luggage comp capacity I 480 Air resistance Cd x A 0.23 x 2.22 Power Unit Config/No of cyls/valves In-line / 4 / 4	
(12%)/unbraked 1600 / 745 (750) Max roofload/max towbar download kg 75 / 75 Luggage comp capacity I 480 Air resistance cd x A 0.23 x 2.22 Power Unit Config/No of cyls/valves In-line / 4 / 4	
Max roofload/max towbar download kg 75 / 75 Luggage comp capacity I 480 Air resistance c _d x A 0.23 x 2.22 Power Unit Config/No of cyls/valves In-line / 4 / 4	
download Luggage comp capacity I 480 Air resistance cd x A 0.23 x 2.22 Power Unit Config/No of cyls/valves In-line / 4 / 4	
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	
Air resistance C _d x A 0.23 x 2.22 Power Unit In-line / 4 / 4	
Config/No of cyls/valves In-line / 4 / 4	
Config/No of cyls/valves In-line / 4 / 4	
Engine technology BMW TwinPower Turbo technology: multi-stage turbocharging, turbo	
with variable inlet geometry, common-rail direct injection with	١
solenoid valve injectors (max. injection pressure: 2000 bar)	
Effective capacity cc 1995	
<u>Stroke/bore</u> mm 90.0 / 84.0	
Compression ratio :1 16.5	
<u>Fuel</u> <u>Diesel</u>	
Max output kW/hp 140 / 190	
at rpm 4000	
Max torque Nm 400	
<u>at rpm 1750 – 2500</u>	
Electrical System	
Battery/installation Ah/– 80 (90) / luggage compartment	
Dattery/installation 7411 00 (55) haggage compartment	
Driving Dynamics and Safety	
Suspension, front Double-joint spring-strut axle in lightweight aluminium-steel constru	uction,
hydraulically damped torque strut bearings	
Suspension, rear Five-link axle in lightweight aluminium-steel construction	
Brakes, front Single-piston floating-calliper disc brakes, vented	
Brakes, rear Single-piston floating-calliper disc brakes, vented	
Driving stability systems Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Control)	Cornering
Brake Control), DBC (Dynamic Brake Control), Performance Control, D	ry Braking
function, Fading Compensation, Start-Off Assistant;	
optional: Adaptive M suspension	
Safety equipment Standard: airbags for driver and front passenger, side airbags for driver	
passenger, head airbags front and rear, three-point inertia-reel seatbe	
seats, front seats with belt stopper, belt latch tensioner and belt force	
crash-active front head restraints, crash sensors, tyre pressure ind	ıcator
Steering Electric Power Steering (EPS) with Servotronic function;	
optional: variable sport steering	
Steering ratio, overall :1 14.1	
Steering ratio, overall :1 14.1 Tyres, front/rear 205/60 R16 96W XL Rims, front/rear 6.5J x 16 light-alloy	

		BMW 320d Sedan
		Diffit 0200 0300ii
Transmission		
Type of transmission		Six-speed manual (eight-speed Steptronic transmission)
Gear ratios	I :1	4.110 (5.250)
	II :1	2.248 (3.360)
	III :1	1.403 (2.172)
	IV :1	1.000 (1.720)
	V :1	0.786 (1.316)
	VI :1	0.601 (1.000)
	VII :1	- (0.822)
	VIII :1	- (0.640)
	R :1	3.727 (3.712)
Final drive	:1	3.154 (2.813)
Performance		
Power-to-weight ratio (DIN)) kg/kW	10.4 (10.4)
Output per litre	kW/l	70.2
Acceleration 0–100 km	n/h s	7.1 (6.8)
Top speed	km/h	240 (240)
BMW EfficientDynamics	.	
BMW EfficientDynamics		Brake Energy Regeneration with recuperation display, Electric Power Steering
standard features		(EPS), Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with
		coasting function (automatic transmission) and Proactive Driving Assistant,
		BMW EfficientLightweight, optimised aerodynamic attributes, active air flap
		control, on-demand operation of ancillary units, map-regulated oil pump,
		differential with optimised warm-up behaviour, tyres with reduced rolling
		resistance, BMW Blue Performance technology with SCR catalyst
F 10		
Fuel Consumption ECE Urban	I/100 km	5.7 5.4/5.1 4.0\
		5.7 – 5.4 (5.1 – 4.9)
Extra-urban Combined	I/100 km	4.1 – 3.8 (4.1 – 3.8)
	I/100 km	4.7 – 4.4 (4.5 – 4.2)
CO ₂	g/km	122 – 115 (117 – 110)
Emission rating		Euro 6d-TEMP

Specifications apply to ACEA markets/data relevant to homologation applies in part only to Germany (weight) Figures in brackets apply to models with automatic transmission

The fuel consumption, CO_2 emissions and electric power consumption figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are already based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO_2 emissions, the CO_2 values may differ from the values stated here (depending on national legislation).

Further information on official fuel consumption figures and specific CO_2 emission values of new passenger cars is included in the following guideline: Leitfaden über den Kraftstoffverbrauch, die CO_2 -Emissionen und den Stromverbrauch neuer Personenkraftwagen' (Guide to the fuel economy, CO_2 emissions and electric power consumption of new passenger cars), which can be obtained free of charge from all dealerships, from Deutsche Automobil Treuhand GmbH (DAT), Hellmuth-Hirth-Str. 1, 73760 Ostfildern-Scharnhausen and at https://www.dat.de/co2/.

¹⁾ Height including roof fin ²⁾ Oil change

The new BMW 3 Series Sedan. 320d xDrive.

		BMW 320d xDrive Sedan
Body		
No of doors/seats		4/5
Length/width/height 1) (unladen)	mm	4709 / 1827 / 1442
Wheelbase	mm	2851
Track, front/rear	mm	1573 / 1587
Ground clearance	mm	135
Turning circle	m	11.95
Fuel tank capacity	approx. I	40
Engine oil 2)	- 1	5.5
Weight, unladen, to DIN/EU	kg	1540 / 1615
Max load to DIN	kg	600
Max permissible weight	kg	2170
Max axle load, front/rear	kg	1055 / 1195
Max trailer load, braked (12%)/unbraked	kg	1600 / 750
Max roofload/max towbar download	kg	75 / 75
Luggage comp capacity	I	480
Air resistance	c _d x A	0.25 x 2.22
Power Unit		
Config/No of cyls/valves		In-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology: multi-stage turbocharging, turbocharger with variable inlet geometry, common-rail direct injection with solenoid valve injectors (max. injection pressure: 2000 bar)
Effective capacity	CC	1995
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel		Diesel
Max output	kW/hp	140 / 190
at	rpm	4000
Max torque at	Nm rpm	400 1750 – 2500
		1,700 2000
Electrical System	A1./	00.11
Battery/installation	Ah/–	90 / luggage compartment
Driving Dynamics and Saf	ety	
Suspension, front		Double-joint spring-strut axle in lightweight aluminium-steel construction, hydraulically damped torque strut bearings
Suspension, rear		Five-link axle in lightweight aluminium-steel construction
Brakes, front		Single-piston floating-calliper disc brakes, vented
Brakes, rear		Single-piston floating-calliper disc brakes, vented
Driving stability systems		Standard: DSC incl. ABS and DTC (Dynamic Traction Control), CBC (Cornering Brake Control), DBC (Dynamic Brake Control), Performance Control, Dry Braking function, Fading Compensation, Start-Off Assistant, xDrive all-wheel-drive system networked with DSC; optional: Adaptive M suspension
Safety equipment		Standard: airbags for driver and front passenger, side airbags for driver and front passenger, head airbags front and rear, three-point inertia-reel seatbelts for all seats, front seats with belt stopper, belt latch tensioner and belt force limiter, crash-active front head restraints, crash sensors, tyre pressure indicator
Steering		Electric Power Steering (EPS) with Servotronic function; optional: variable sport steering
Steering ratio, overall	:1	14.9
Tyres, front/rear		225/50 R17 98Y XL
Rims, front/rear		7.5J x 17 light-alloy

		BMW 320d xDrive Sedan
Transmission		
Type of transmission		Eight-speed Steptronic transmission
Gear ratios I	:1	5.250
I	l :1	3.360
I	ll :1	2.172
	V :1	1.720
\	√ :1	1.316
	√l :1	1.000
\	/II :1	0.822
١	√III :1	0.640
	R :1	3.712
Final drive	:1	2.813
Performance		
Power-to-weight ratio (DIN)	kg/kW	11.0
Output per litre	kW/l	70.2
Acceleration 0–100 km/	h s	6.9
Top speed	km/h	233
BMW EfficientDynamics		
BMW EfficientDynamics		Brake Energy Regeneration with recuperation display, Electric Power Steering
standard features		(EPS), Auto Start Stop function, Optimum Shift Indicator, ECO PRO mode with
		coasting function and Proactive Driving Assistant, BMW EfficientLightweight,
		optimised aerodynamic attributes, active air flap control, on-demand operation
		of ancillary units, map-regulated oil pump, efficiency-optimised all-wheel drive,
		rear differential with optimised warm-up behaviour, tyres with reduced rolling
		resistance, BMW Blue Performance technology with SCR catalyst
Fuel Consumption ECE		
Urban	I/100 km	5.5 – 5.2
Extra-urban	I/100 km	4.4 – 4.1
Combined	1/100 km	4.8 – 4.5
CO ₂	g/km	125 – 118
Emission rating	<u>_</u>	Euro 6d-TEMP

 $Specifications\ apply\ to\ ACEA\ markets/data\ relevant\ to\ homologation\ applies\ in\ part\ only\ to\ Germany\ (weight)$

²⁾ Oil change

The fuel consumption, CO_2 emissions and electric power consumption figures were determined according to the European Regulation (EC) 715/2007 in the version applicable. The figures refer to a vehicle with basic configuration in Germany. The range shown considers the different sizes of the selected wheels/tyres and the selected items of optional equipment, and may vary during configuration.

The values are already based on the new WLTP test cycle and are translated back into NEDC-equivalent values in order to ensure comparability between the vehicles. With respect to these vehicles, for vehicle-related taxes or other duties based (at least inter alia) on CO_2 emissions, the CO_2 values may differ from the values stated here (depending on national legislation).

Further information on official fuel consumption figures and specific CO_2 emission values of new passenger cars is included in the following guideline: Leitfaden über den Kraftstoffverbrauch, die CO_2 -Emissionen und den Stromverbrauch neuer Personenkraftwagen' (Guide to the fuel economy, CO_2 emissions and electric power consumption of new passenger cars), which can be obtained free of charge from all dealerships, from Deutsche Automobil Treuhand GmbH (DAT), Hellmuth-Hirth-Str. 1, 73760 Ostfildern-Scharnhausen and at https://www.dat.de/co2/.

¹⁾ Height including roof fin

BMW Media Information 10/2018 Page 7

Output and torque diagrams. The new BMW 3 Series Sedan. 330i.



BMW Media Information 10/2018 Page 8 The new BMW 3 Series Sedan. 320d.

BMW Media Information 10/2018 Page 9 The new BMW 3 Series Sedan. 320d xDrive.

Exterior and interior dimensions. The new BMW 3 Series Sedan.







