

Specifications.

BMW 4 Series Convertible.

420i, 430i



		BMW 420i Convertible	BMW 430i Convertible
Body			
No. of doors/seats		2 / 4	2 / 4
Length/width/height (unladen)	mm	4638 / 1825 / 1384	4638 / 1825 / 1384
Wheelbase	mm	2810	2810
Front/rear track	mm	1545 / 1594	1545 / 1594
Ground clearance	mm	130	130
Turning circle	m	11.3	11.3
Fuel capacity	approx. l	60	60
Engine oil capacity ¹⁾	l	5.25	5.25
Weight, unladen (DIN/EU)	kg	1700 / 1775 (1715 / 1790)	1710 / 1785 (1735 / 1810)
Payload (DIN)	kg	470	460
Permitted total weight	kg	2170 (2185)	2170 (2195)
Permitted axle load, front/rear	kg	960 / 1250	965 / 1255
Permitted trailer load (12%) braked/unbraked	kg	1400 (1500) / 695	1600 / 745
Permitted roof load/trailer download	kg	- / 75	- / 75
Luggage compartment capacity	l	370	370
Aerodynamic drag	c _x x A	0.30 x 2.16	0.30 x 2.16
Engine			
Type/no. of cylinders/valves		in-line / 4 / 4	in-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology: twin-scroll turbocharger, direct injection system High Precision Injection, fully variable valve control (VALVETRONIC) and double VANOS variable camshaft timing	
Effective capacity	cc	1998	1998
Stroke/bore	mm	94.6 / 82.0	94.6 / 82.0
Compression ratio	:1	11.0	10.2
Fuel type		min RON 91	min RON 91
Output	kW/hp	135 / 184	185 / 252
at rpm	min ⁻¹	5000	5200
Torque	Nm	270	350
at rpm	min ⁻¹	1350 – 4600	1450 – 4800
Electrical			
Battery charge/location	Ah/-	90 / luggage compartment	90 / luggage compartment
Driving Dynamics and Safety			
Front suspension		Aluminium double-joint spring-strut axle with displaced camber, small positive steering roll radius, compensation of lateral forces, anti-dive	
Rear suspension		Five-link axle in lightweight steel construction	
Front brakes		Single-piston floating-calliper disc brakes, inner-vented	
Rear brakes		Single-piston floating-calliper disc brakes, inner-vented	
Driving stability systems		Standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, start-off assistant; optional: Adaptive Suspension	
Safety equipment		Standard: driver and front-seat passenger airbags, driver and front-seat passenger side airbags with combined head airbags, three-point automatic seatbelts for all seats, seatbelt tensioners and seatbelt force limiters in front seats, crash sensors, roll-over protection system, tyre pressure indicator	
Steering		Electromechanical rack-and-pinion power steering (EPS) with Servotronic function; optional: Variable Sport Steering	
Overall steering ratio	:1	15.0	15.0
Front/rear tyres		225/50 R17 94W	225/50 R17 98W XL
Front/rear wheels		7,5J x 17 light-alloy	7,5J x 17 light-alloy

Specifications. BMW 4 Series Convertible.

		BMW 420i Convertible	BMW 430i Convertible
Transmission			
Type of gearbox	6-speed manual (optional: 8-speed Steptronic)		
Gear ratios	I	:1 4.002 (5.000)	3.683 (5.000)
	II	:1 2.130 (3.200)	2.062 (3.200)
	III	:1 1.396 (2.143)	1.313 (2.143)
	IV	:1 1.000 (1.720)	1.000 (1.720)
	V	:1 0.781 (1.314)	0.809 (1.314)
	VI	:1 0.668 (1.000)	0.677 (1.000)
	VII	:1 – (0.822)	– (0.822)
	VIII	:1 – (0.640)	– (0.640)
	R	:1 3.647 (3.456)	3.348 (3.456)
Differential ratio		:1 3.462 (2.813)	3.909 (2.813)
Performance			
Weight-to-power ratio (DIN unladen)	kg/kW	12.6 (12.7)	9.2 (9.4)
Specific power output	kW/l	67.6	92.6
Acceleration 0–100 km/h	sec	8.2 (8.4)	6.4 (6.3)
in 5th gear 80–120 km/h	sec	10.7 (–)	8.0 (–)
Max. speed	km/h	230 (230)	250 (250)
BMW EfficientDynamics			
BMW EfficientDynamics Features included as standard	Brake Energy Regeneration with recuperation display, electric power steering (EPS), Auto Start Stop function, gear shift indicator, ECO PRO mode with coasting function (automatic), intelligent lightweight construction, optimised aerodynamic attributes, on-demand operation of ancillary units, map-regulated oil pump, differential with optimized-warm-up behaviour, tyres with reduced rolling resistance		
Fuel consumption (EU) ²⁾			
with standard wheels and tyres			
Urban	l/100 km	8.0 (7.6)	8.6 (7.5)
Extra-urban	l/100 km	5.1 (4.8)	5.5 (5.0)
Total	l/100 km	6.2 (5.8)	6.6 (5.9)
CO ₂ emissions	g/km	145 (136)	154 (138)
With 8J x 18" rims and 225/45 R18 tyres and winter tyres, With 8J x 18" front rims, 8.5J x 18" rear rims, 225/45 R18 front tyres and 255/40 R18 rear tyres, With 8J x 19" front rims, 8.5J x 19" rear rims, 225/40 R19 front tyres and 255/35 R19 rear tyres			
Urban	l/100 km	8.6 (8.1)	9.0 (7.9)
Extra-urban	l/100 km	5.5 (5.1)	5.8 (5.3)
Total	l/100 km	6.6 (6.2)	7.0 (6.3)
CO ₂ emissions	g/km	153 (144)	162 (146)
Emissions standard		EU6	EU6

Technical data valid for ACEA countries/Some permitted weights valid only for Germany
Figures in brackets are for vehicles with automatic transmission

¹⁾ Oil change volume

²⁾ Fuel consumption and CO₂ emissions depend on the selected tyre format